

Part C: Supporting Documents



Appendix A: Flood and Floodplain Management

Flood Management

Flood management is used in the broad context of Emergency Management as described in the Emergency Management Manual Victoria (EMV 2016). The objectives are to ensure that the following components of emergency management are organised to facilitate planning, preparedness, operational coordination and community participation:

Prevention: the elimination or reduction of the incidence or severity of emergencies and the mitigation of their effects, which are part of the work plans and Strategy Action Plan requirements under the under the *Emergency Management Act 2013*.

Response: the combating of emergencies and the provision of rescue and immediate relief services. Note that the Victoria State Emergency Service is the combating agency for floods.

Recovery: the assisting of people and communities affected by emergencies to achieve a proper and effective level of functioning.

The **Figure A-7** below (adapted from the Emergency Management Manual 2016) shows this model as it relates to flood management. It should be noted that prevention, response and recovery activities overlap. These are not necessarily phases or stages of emergency management, as the relevant activities are carried out as needed and not always sequentially.



Figure A-7: Flood Management in the Emergency Management Context

Floodplain management

Floodplain management comprises the prevention activities of flood management together with related environmental activities as illustrated in Figure A-8 (adapted from Victoria Flood Management Strategy 1998). The significance of the distinction between flood management and floodplain management is that various lead agencies, such as CMAs, have key roles in floodplain management activities while other agencies such as Emergency Management Victoria, Victoria State Emergency Service and Department of Health and Human Services have key roles in response and recovery activities.



- Flood Warning
- **Community Awareness**
- **Education & Training**
- Research

- Landscape interest areas
- Traditional Owner interest areas
- Archaeologic interest areas
- Water quality

Figure A-8: Floodplain Management in the Flood Management Context

Appendix B: Consultation Material to Promote Stakeholder Discussions and Input

Consultation material was prepared for stakeholder consultation in two formats: firstly by local government areas (for urban centres), and secondly by one single whole of region area (for rural areas along large river/creek reaches).

A stocktake of past studies and achievements was summarised for urban centres and rural areas, including an assessment of information gaps and potential flood risks in tabular format. A first "best" assessment rankings were applied to the four tools used to enhance flood resilience (i.e. Flood mitigation, Total Flood Warning System, Land-use Planning and Municipal Flood Emergency Plans)

The same background wording was applied to the eight local government/regional areas with locality plans that was distributed at the 15 community workshops and placed on the Goulburn Broken CMA's website, allowing opportunities for submissions.

Below is a copy of the introductory wording used for each local government/regional area followed by specific tables providing information on rankings, stocktakes and priorities.

Flood risk assessment and draft priority rankings for stakeholder discussion

Community input is needed to prioritise where flood knowledge needs to be improved through flood studies and flood mapping in (LGA/region) and to determine actions to reduce the risk of flooding.

This summary provides a list of studies for towns in (LGA/region) and draft priorities for flood mitigation actions.

How to read the table below

The column to the left ranks flood risks (1: low, and 5: high), taking into account the possible damage from different sized floods and how often they are expected to happen. The measure of the yearly average cost of floods is known as Annual Average Damage (AAD).

The two columns in the centre of the table show:

- Flood studies that have been (or soon will be) completed for towns in your local government area.
- Recommendations from these studies that have been implemented (or are under way) and other relevant comments or observations.

The columns to the right of the table show DRAFT priority rankings [Low (L), Medium (M), High (H) and No Action (-)] for actions that reduce risk of flooding such as:

- Mitigation works (e.g. levees, retardation basin, and floodways)
- Flood warning systems (e.g. flood watch, flood warning broadcasts and action plans)
- Land use planning (e.g. flood overlay control in planning schemes)
- Municipal flood emergency plans (developed by council, VICSES and other agencies with flood-management responsibilities)

Please review this summary and provide feedback by:

- attending one of the community sessions being held across the catchment during February; or
- completing the feedback form on the website <u>www.gbcma.vic.gov.au</u>

Terminology

Annual Average Damage (AAD), expressed in dollar terms, is the average damage per year that would occur in a particular area from flooding over a very long period of time. This provides a basis for comparing the economic effectiveness of different projects. For more information on risk assessment methodology, please see the Regional Floodplain Management Strategy section of the website.

Annual Exceedance Probability (AEP) is the likelihood of occurrence of a flood of given size or larger occurring in any one year.

FloodSafe is a whole community program designed to prepare and empower the community with the skills and knowledge to appropriately prepare for, respond to, and recover from floods.

Municipal Flood Emergency Plan (MFEP) is a plan prepared and maintained by each municipal council, under the *Emergency Management Act 1986*, which identifies the municipal resources available, and how they are to be used, for flood prevention, response and recovery.

Regional Floodplain Management Strategy (RFMS) (under development) will replace the previous regional strategy (2002) and aims to help manage flood risk by seeking community input to prioritise where flood knowledge needs to be improved. The priorities will be detailed in a rolling three-year regional work plan that can be used by local communities to secure funding for various flood management activities.

Specific Local Government/Regional area tables and maps

Benalla Rural City Council



Figure 1. Benalla Rural City Council area showing towns and planning scheme flood overlay controls

 Table 1.
 Benalla Rural City risk assessment (ranking 1: low, and 5: high)

 Draft priority rankings for stakeholder discussion: Low (L), Medium (M), High (H) and No Action (-) (for urban centres)

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Baddaginnie	2	 Documentation & Review of the 1993 Victorian Floods Volume 4 Broken River Catchment Floods (Hydro Technology, 1995) Granite Creek Regional Flood Study (Water Technology, nearing completion) 	 No flood zone or overlay controls exist Upload mapping products from study into planning scheme Prepared 1% flood contour in Flood Atlas online Update MFEP Consider possible flood warning arrangements. Likely to rely on BoM flood warning products such as Flood Watch 	-	L	н	н
Benalla	5	 Benalla Floodplain Management Study (SR&WSC, 1984) Benalla Flooding Investigation: Flood of 3-4 October 1993 (Willing & Partners, 1994) Documentation & Review of the 1993 Victorian Floods Volume 4 Broken River Catchment Floods (Hydro Technology, 1995) Total Flood Warning System (CT Management, 1997) Flood Response Guidelines, Benalla Township and Surrounds (Delatite Shire (1997) Benalla Floodplain Management Study (Cardno Willing, 2002). Benalla Floodplain Management Study – Flood Study (Willing & Partners, 2005) Lake Nillahcootie Flood Study (Cardno, 2008) Benalla: Review of Floodplain Management Works (Cardno, 2009) Benalla Flood Risk Review of Flood Cut Option (Cardno 2009) Benalla Flood Information Portal Report (Cardno, 2016) 	 1% AEP flood levels declared Total Flood Warning System implemented Benalla Water Management Scheme Implemented including vegetation thinning. Additional installation of railway culverts proved ineffective and impracticable and on hold indefinitely Flood Smart property information rolled out in 2009. Benalla Flood Information System web portal (Cardno, 2016) is being developed FloodSafe Guide drafted Property Information Statements prepared Need new flood zone and overlay controls for planning scheme Council remains commitment to manage water management scheme 	-	-	н	н
Devenish	0	• Nil	 Approx. 60 buildings identified (from 2015 aerial photography) Flood overlay controls are required as evident by captured 2012 peak flood levels Suspect that flooding occurs from Broken Creek overflow Scoping Study is required to at least to provide flood mapping No LiDAR or detailed ground information exists 	-	-	М	м
Glenrowan (Rural City of Wangaratta)	0	• Nil	 Town has a number of deeply incised waterways commending very small catchments in the order of 100 ha. There may be some overland drainage issues beyond the scope of this RFMS 	-	-	-	-
Swanpool	1	• Nil	 LiDAR shows that the town is on a significant high terrace above the floodplain by some three to four metres No further action 	-	-	-	-
Tatong	1	• Nil	 LiDAR shows that the bulk of the town is several metres above the adjacent floodplain. Town has two localised waterways Dwellings located west of town are relatively low Consider scoping flood study to improve flood mapping. This will assist to identify any further work 	-	-	М	L
Thoona	0	• Nil	 The bulk of the buildings are on land significantly above the Boosey Creek floodplain Several buildings could be exposed to flood risk Desktop investigation required to prepare flood overlay controls to safeguard from flood risk for new buildings 	-	L	М	L

Campaspe Shire



Figure 1. Campaspe Shire area showing towns and planning scheme flood overlay controls

Table 2. Campaspe Shire risk assessment (ranking 1: low, and 5: high)

Ditt			, Medium (M), High (H) and No Action (-) (for ur		,	b0	
Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood
Colbinabbin	1	Corop Lakes Scoping Study (GHD, 2012)	 Cornella Creek and its floodplain lies east of town The land upon which the primary school is located is subject to flooding. A house east of town is reported to have water under it. Recent Shire works have resolved flooding issues for other houses GMW has operational procedures for the Waranga Channel and a number of flood doors Improvement in communications about flood operations between GMW and communities is ongoing (a recommendation of scoping study) Parts of the town is known to be subject to overland flooding from the Camel Ranges that lie to the west. However, no knowledge of any above house floor flooding 	-	М	L	м
Girgarre	0	 Flooding of Tongala-Stanhope Irrigation District - March 1950 & Recommendations for Improving the Surface Drainage (SR&WSC, 1951) 	 No known flooding issues to date. Shire has no records of any above house floor flooding over the past 40 years. Shire has recently installed a retardation basin, which is designed to cater for a 1% AEP flood 	-	-	-	-
Kyabram	5	 Kyabram Drainage System – Design Basis Report on Kyabram Drainage Improvement Works (GHD, 1995) Kyabram Drainage System – Surface Drainage Strategy (GHD, 1996) Flood Contour Review (GBCMA, 2011) Shire is currently designing 1% AEP upgrade to McEwen Road east and west retardation basins 	 Low-lying areas are subject to overland flooding from localised intense rainfall Study recommendations implemented including pump station to remove excess floodwater to storage areas to the south of town Other recommendations from the 1994 report still remain outstanding, i.e. upgrade of McEwen Road sumps and construction of Waratah Street are still to be completed. Once completed there will still be a number of houses inundated by a 1% AEP flood. Require scoping study to review old study assumptions against new methods contained in Australian Rainfall and Runoff, and to identify any further work. For instance, the setting of floor levels could be based on pump failure (i.e. no pumps) Flood overlay controls need updating (partly completed by GB CMA) 	L	_	Н	_
Rushworth	0	 Rushworth Overland Flood Study comprising the following: Southern catchment design (Moore and Esmonde Streets) Western Catchment Design (Parker and Esmonde Streets) Norther Catchment Design (Moore and High Streets) CBD – High Street These studies and designs were all finalised in 2014 	 Mitigation works implemented to reduce exposure from over floor flooding to some commercial buildings Need overlay flood controls for identified overland flow paths in planning scheme Rely on available BoM flood warning products such as Flood Watch 	-	_	М	М
Stanhope	1	 Stanhope Drainage Scheme 1973 Flood Data Transfer – Flood Mapping (NRE, 1998) 	 Low-lying depression exists south of the town. However, there is no known history of flooding within the township boundary Further studies are not warranted at this time 	-	-	-	-
Tongala	1	 Tongala Drainage Scheme (Proposed Drainage Master Plan) (GHD, 1984) 	 The edge of the town (to the north) lies within a natural depression, which is shown in the flood overlay controls in the planning scheme Elsewhere, a significant number of recorded peak 1974 flood levels exist but without any flood overlay controls. However: The Shire of Campaspe has advised (during the preparation of the 2002 RFMS) that the area is served by a drainage scheme incorporating Retardation Basins that caters for the 1% AEP storm Drainage works since that time has meant that areas outside the retardation basin do not flood. In 2012 water in the basin reached the boundaries of the 1% AEP storage No further study is envisaged other than for the Shire to monitor the performance of the drainage system 	-	-	M-H	м

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Wyuna	1	• Nil	 Localised drainage path identified to the west of town No known flooding issues identified 	-	-	-	-

Greater Bendigo City Council



Figure 1. Greater Bendigo City Council area showing towns and planning scheme Rural Living Zone (RLZ)

Table 1. Greater Bendigo City Council risk assessment (ranking 1: low, and 5: high)

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Costerfield	0	• Nil	 There is approx. 20 buildings scattered throughout the area This location is on top of the catchment and has two minor drainage lines No further action 	-	-	-	-
Costerfield South	0	• Nil	 Similar to Costerfield Several small tributaries meet south of the area and suspect some minor flash flood issues 	-	-	-	-
Heathcote East (Rural Living)	0	• Nil	 The area zoned Rural Living has transformed the area into a significant number of lots and dwellings. There are a significant number of waterway with relatively small catchment of few square kilometres. No known flooding issues, but possibly subject to flash flooding 	-	L	-	-
Heathcote North (Rural Living)		• Nil	 The area zoned Rural Living has transformed the area into a significant number of lots and dwellings There are a significant number of waterway with relatively small catchment of few square kilometres No known flood issues, but possibly subject to flash flooding 	-	L	-	-
Mount Camel	0	• Nil	 Several buildings identified Available LiDAR indicates building are located on high land above the Cornella Creek floodplain 	-	-	-	-
Redcastle	0	• Nil	 Some 90 small lots exist (approx. 1,000 square metres) with some 15 buildings Redcastle Creek flows to the west of the subdivision and has a catchment area of some 18 square kilometres No known flood issues No ground information exist to assess possible flood impact. 	-	L	L	L

Greater Shepparton City Council



Figure 1. Greater Shepparton area showing towns and planning scheme flood overlay controls

Table 2. Greater Shepparton risk assessment (ranking 1: low, and 5: high)

		hepparton risk assessment (ranking 1: low, and s rity rankings for stakeholder discussion: Low (L),		ban cei	ntres)		
Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Bunbartha	1	 Documentation and Review of the 1993 Victorian Floods Volume 5 Lower Goulburn River Floods (Hydro Technology, 1995) Lower Goulburn Floodplain Rehabilitation Scheme (Water Technology, 2005) 	 Potential flood impact from levee failure/overtopping upstream of town Potential flood impacts from Loch Garry boards being removed Flood warning arrangements augmented by Goulburn Murray Water. Also from Greater Shepparton to Daintons Bridge (Shepparton Gauge provide the triggers for Loch Garry board removal operation) 	-	-	L	-
Cooma	1	 Flooding of Tongala-Stanhope Irrigation District - March 1950 & Recommendations for Improving the Surface Drainage (SR&WSC, 1951) 	 Available data indicates Mosquito Depression (to the west of Cooma) does not impact on the Cooma No further action 	-	-	-	-
East Murchison	1	 Murchison Flood Mapping Study Report (Water Technology, 2015) MFEP update provided (Water Technology) 	 New flood controls need to be incorporated into planning scheme MFEP update FloodSafe Guide prepared Flood Warning Services to Murchison in place 	-	L	н	-
East Shepparton	5	 Peak 2013 flood levels captured Shepparton East Flood Study (BMTWBM) final draft completed 	• Nil	-	-	н	н
Katandra West	0	 Nil 	 Not subject to riverine flooding Flood overlay controls are required as evident by captured 2012 peak flood levels Scoping flood study is required with a focus of improved flood mapping FloodSafe Guide prepared Flood intelligence in MFEP 	-	-	н	-
Kialla West	1	This now part of the Shepparton Mooroopna Flood Intelligence Study	See Shepparton Mooroopna	-	-	-	-
Merrigum	3	Merrigum Flood Study (WBM, 2005)	 Planning flood controls, incorporated into planning scheme 1% AEP flood levels declared MFEP updated Flood warning relies on BoM products such as flood watch FloodSafe Guide should be considered 	-	-	-	L
Murchison	1	See "East Murchison" above	See East Murchison	-	L	н	н
Shepparton/ Mooroopna	5	 Shepparton-Mooroopna Flood Study 2 volumes (Sinclair Knight Partners, 1982) Shepparton-Mooroopna Flood Mitigation Design – Report on Works Options, Draft Discussion Document on Options, and Assessment of Levee Options – Summary Report and Appendices (Sinclair Knight & Partners (1986, 1987 & 1989) Mooroopna Flood Mitigation Scheme (RWC, 1989) Documentation and Review of the 1993 Victorian Floods Volume 5 Lower Goulburn River Floods (Hydro Technology, 1995) Mooroopna Water Management Scheme: Proposed Mooroopna Levees – Report on Submissions to Exhibited Scheme Document (NRE, 1997) Shepparton-Mooroopna Floodplain Management Scoping Study – Final Report (Sinclair Knight Merz, 1998). Shepparton Mooroopna Floodplain Management Study – Stage 1 Technical Report (SKM, 2002) Shepparton Mooroopna Floodplain Management Study – Stage 2 Technical Report (SKM, 2002) Greater Shepparton City Council Flood Warning and Emergency Management Project (Water Technology, 2007) Shepparton Mooroopna Flood Intelligence and Mapping Study (Water Technology – ongoing) 	 Large length of GMW Irrigation Channel 19/12 along Wanganui Road has been placed underground (circa mid 1980s) Several properties purchased by RWC within low- lying areas along River Road between Shepparton and Mooroopna Proposed new urban levees abandoned in 1997 due to lack of agreement Total Flood Warning System implemented in 2007 including flood warning service by BoM and community information MFEP updated 2007 Flood zone and overlay controls incorporated into planning scheme in 2004 1% AEP flood levels declared. MFEP, mapping, flood levels and community intelligence require updating upon completion of the latest study. FloodSafe Guide prepared in 2014. 	-	-	н	н

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Tally- garoopna	1	 Documentation and Review of the 1993 Victorian Floods. Volume 4 – Broken River Catchment Floods (Hydro Technology, (1995) Recorded 2012 peak flood levels 	 FloodSafe Guide prepared Flood intelligence in MFEP Flood controls needs updating 	м	-	Н	-
Tatura	5	 Mosquito Drain 36 (Tatura Bypass Drain) Concept Report (SKM, 1999) Tatura Floodplain Management Plan (WBM, 2006) 	 Flood control integrated into planning scheme 1% AEP flood levels declared Civil mitigation works implemented (railway culverts, Undera Road culvert, lowering pathway and Retardation Basin embankment) Council remains committed is managing civil works Mapping in MFEP No specific flood warning – rely on Flood Watch products from BoM 	-	_	_	-
Toolamba	1	• Nil	 Desktop review of LiDAR (ground level) data indicates a low-lying depression exist that would flood from the Goulburn River, otherwise the town is well above flood level Require new flood overlay controls Further desktop study to determine need for TFWS, MFEP 	-	L	М	м

Mansfield Shire



Figure 1. Mansfield Shire Council area showing towns and planning scheme flood overlay controls

Table 1. Mansfield Shire risk assessment (ranking 1: low, and 5: high)

Name	AAD	Tty rankings for stakeholder discussion: Low (L	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Bonnie Doon	1	• Nil	 LiDAR ground level information indicates that the land is well above both the Full Supply Level of Lake Eildon and the 1% AEP flood level. No further action. 	-	-	-	-
Castle Point (A1 Mine Settlement)	0	 Design Flood Hydrographs for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 Three buildings have been identified (from 2015 aerial photography) for the area. The Raspberry Creek flows to the east of the development and has a catchment of some twelve square kilometres No detailed ground level information exists. However, from past site visits, the buildings appear elevated above the floodplain level No further action 	-	-	-	-
Howqua	1	 Design Flood Hydrographs for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 The site essentially includes buildings and works associated with a school camp LiDAR ground level information indicates that the site of the buildings are well above Howqua Valley floodplain. Need to confirm that the above judgement by undertaking a regional floodplain hydraulic modelling assessment with input from the hydrologic study (flow estimates) findings 	-	L	L	L
Jamieson	2	 Jamieson Flood Scoping Study (SKM, 2002) Design Flood Hydrographs for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 This town is possibly the most at risk community in the Mansfield Shire Flood overlay controls now incorporated into planning scheme; however, the mapping methodology is somewhat arbitrary Several homes have been identified as potentially at risk of over floor flooding, including significant flood risk at the caravan park At the very least the town needs a further hydraulic modelling assessment based on new LiDAR capture and river surveys (to determine flood extents etc.) with input from the hydrologic study (flow estimates) findings Scoping study into possible flood warning improvement is required – the BoM flood warning products such as Flood Watch is currently the only tool available 	-	Н	н	н
Maindample	1	• Nil	 Field reconnaissance carried out by GB CMA staff mapped the floodplain extents for the newly adopted flood overlay controls. This assessment suggests a small proportion of buildings maybe exposed to flood risk. 	-	-	L	L
Mansfield	3	 Mansfield Flood Study – Final Report (Earth Tech, 2005) Mansfield Flood Study Extension – Supplementary Report (Earth Tech, 2006) Mansfield Flood Intelligence and Mapping (GB CMA, 2014) Design Flood Hydrographs for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 Flood zone and overlay controls have been updated to reflect latest mapping. There are approx. three dwellings at risk of over floor flooding and a further 50 properties subject to flood inundation for a 1% AEP type flood Suggest a review of possible flood warning needs Carry out floor level survey to determine appropriate property listing in the MFEP 	-	М	-	М
Merrijig	1	 Design Flood Hydrographs for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 Approx. 75 buildings exist in Merrijig which are elevated above the Delatite River floodplain No further Action 	-	-	-	-
Merton	0	• Nil	 Approx. 30 buildings exist in the town and located well above the floodplain areas. No further action 	-	-	-	-
Woods Point	0	 Design Flood Hydrographs for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 Field reconnaissance carried out by GB CMA staff mapped flood extents for newly adopted flood overlay controls in the Mansfield Planning Scheme. Mapping suggests that a small proportion buildings maybe exposed to flood risk. LiDAR ground level information is consistent with the above findings. This town should be included as part of the regional study area for upper Goulburn 	-	-	L	L

Mitchell Shire



Figure 1. Mitchell Shire Council area showing towns and planning scheme flood overlay controls

Table 1.Mitchell Shire risk assessment (ranking 1: low, and 5: high)

Draft priority rankings for stakeholder discussion: Low (L), Medium (M), High (H) and No Action (-) (for urban centres) l Flood Warnir System and Use Plannin Summary of completed activities (Other comments) Summary of past and existing studies Flooding from both Sunday and Dry creeks has • some flood impacts on the town as well as overland flooding issues Broadford 2 н н Μ Nil -• Requires a flood study (a study could be coupled • with other towns and regional areas along Dry and Sunday creeks) Update MFEP • • Kilmore Flood Study and Intelligence Study (BMT Kilmore 0 н н Place flood overlay controls in planning scheme L L ٠ WBM, ongoing) • Flash flood warning services to be considered • Dry Creek flows along the eastern side of the town and railway. LiDAR ground information indicates that the town is well above Dry Creek Several small drainage lines traverse through the Μ L Kilmore East 0 • L • Nil town and may have some overland flooding issues • Investigate flooding in a regional approach along Dry and Sunday creeks including its towns Approx. 170 buildings have been identified (from ٠ 2015 aerial photography) • The town has developed as two distinct areas, namely to the north (Township Zone) and in the south (Rural Living Zone). • Mollisons Creek flows through the northern Pyalong L L 0 • Nil portion of town LiDAR ground information indicates that Mollisons • Creek is deeply incised and flooding of the urban areas is unlikely Carry out a desktop study (or scoping study) to • confirm or otherwise any flooding issues Approx. 65 buildings have been identified (from • 2015 aerial photography) • Dabyminga Creek flows along the east of the developed areas and commands a catchment area of approx. 38 square kilometres. • LiDAR ground information indicates that **Reedy Creek** 0 н L • Nil Dabyminga Creek is deeply incised and flooding of the urban areas is unlikely . Investigate flooding in a regional approach along Dry and Sunday creeks including its towns

•

Flood warning rely on BoM flood warning products such as Flood Watch

Name	AAD	Summary of past and existing studies	Summary of completed activities (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Seymour	5	 Seymour – Report on Flooding from Goulburn River (SR&WSC, 1981) Appendix F: Lake Eildon – Effect on Flood Frequencies at Eildon (SR&WSC, 1981) Seymour Floodplain Management Study (SR&WSC, 1984) Seymour Flood Mapping Study – Final Report (WBM Oceanics Australia, 2001) Total Flood Warning System–Goulburn River to Seymour Seymour Flood Mitigation Communication Investigation – Final Consultants Report to Council (WBM Oceanics Australia, 2006) Seymour Flood Mitigation Project - Preliminary Design Report (John Webb Consulting, 2009) Seymour Flood Mitigation Project - Draft Report (GHD, 2013) Letter report on the cost of compensation to landowners for land acquisition (PW Newman P/L, 2013) Letter report on the outcomes of flood modelling (BMT WBM, 2013) Seymour Flood Mitigation Project – Preliminary Cost Estimate (Flagstaff Consulting Group, 2013) Letter report on the outcomes of flood modelling (BMT WBM, 2013) Seymour Flood Mitigation Project – Preliminary Construction Methodology (Flagstaff Consulting Group, 2013) Letter report on increase in land values from rezoning (PW Newman P/L, 2014) Memorandum – Seymour Flood Mitigation Cost Benefit Analysis (Aither, 2014) Terrestrial and aquatic assessment for the proposed Seymour levee – proposed realignment (Ecology and Heritage Partners, 2015) Proposed Flood Levee, Seymour – Draft Cultural Heritage Management Plan (Heritage Insight, 2014) 	 Total Flood Warning System has been delivered MFEP has been updated to reflect existing conditions without proposed levees Information Guides prepared in 2001 has been updated with FloodSafe guides by VicSES (2015) Flood zone and overlay controls have been updated to reflect existing conditions without proposed levees. Functional levee design is underway A planning scheme amendment for the levee is in preparation and consideration. 	Н	Μ	Н	Н
Tallarook	1	Tallarook Flood Investigation (GB CMA, 2008)	 Dabyminga Creek flows along the eastern side of town and commends a catchment of some 145 square kilometres. Approx. 60 buildings have been identified from 2015 aerial photography, with the bulk of them above the 1% AEP flood level Flood overlay controls require updating Flood Warning needs to rely of BoM flood products such as Flood Watch MFEP need to ensure buildings in low-lying land are documented – This can be done using LiDAR and field visits 	-	-	Μ	М
Tyaak	0	• Nil	 Approx. 25 buildings have been identified (from 2015 aerial photography) Dabyminga Creek flows through the town and commands a catchment area of approx. 60 square kilometres. LiDAR ground information indicates that Dabyminga Creek is deeply incised and flooding of the urban areas is unlikely Investigate flooding in a regional approach along Dry and Sunday creeks including its towns 	-	-	н	L
Whiteheads Creek	1	 Whiteheads Creek and Overland Flood Mapping Study (Cardno, ongoing) 	 Update MFEM Flood zone and overlay controls required in planning scheme Flash flood warning services needs consideration – Whitehead Creek Gauge exists 	М	н	н	н

Moira Shire



Figure 9. Moira Shire Council showing towns and planning scheme flood overlay controls

 Table 1.
 Moira Shire risk assessment (ranking 1: low, and 5: high)

		re risk assessment (ranking 1: low, and 5: high) rity rankings for stakeholder discussion: Low (L),	Medium (M) High (H) and No Action (-) (for ur	han cer	ntres)		
Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Barmah	5	 Murray River Floodplain Management Study (GHD, 1986) Flood Mitigation Study (GHD, 1994) Lower Goulburn Floodplain Rehabilitation Scheme Assessment of Flood Risk to the Township of Barmah and preliminary flood mitigation review (SKM, 2008) Barmah Township Flood Mitigation – Functional Design (Water Technology, 2012) 1% AEP Flood Contour Atlas available 	 Flood mitigation unlikely to proceed given cost and impracticalities Flood overlay controls are in the planning scheme Prepare a FloodSafe Guide Check to see MFEP requires updating with property listing available (use floor levels to assessment possible above floor flooding) River gauge established with flood class levels and BoM flood warning service 	L	-	-	-
Bearii	1	• Nil	 Approx. 60 buildings identified (from 2015 aerial photography) Current flood overlay controls are of low reliability and new flood mapping would be part of combined regional flood mapping study, i.e. part of rural levee review May consider future FloodSafe Guide 	-	L	L	L
Cobram	5	 Murray River Floodplain Management Study (GDH, 1986) Cobram Town Levees Study Final Design (CMPSF 1993) Cobram Flood Mitigation Proposals Water Management Scheme Approved Scheme Document (NRE, 1996) Murray River Regional Floodplain – Dicks/Seppelts levees to downstream of the Ulupna Creek Confluence Study Report (WT, 2011) 	 Levee system constructed in mid-2000 to protect the Town from a 1% AEP flood Further work required to explore flood protection options to protect town from overland flooding from the East Flood overlay controls require updating (at regional level) MFEP has been updated Council recommitted to operate and maintain the levee scheme 	н	-	-	-
Katamatit	.e 2	 Documentation and Review of the 1993 Victorian Floods Volume 4 (HT, 1995) FloodSafe Guide prepared (VicSES, 2015) 	Flood scoping study required	-	м	L	м
Koonoomo	00 1	 Documentation and Review of the 1993 Victorian Floods Volume 4 (Hydro Technology, 1995) Murray River Regional Floodplain – Dicks/Seppelts levees to downstream of the Ulupna Creek Confluence Study Report (WT, 2011) 	 Approx. sixty buildings have been identified (from 2015 aerial photography) MFEP has been updated New food controls need to be implemented from regional flood study Flood contour Atlas needs to be revised Prepare FloodSafe Guide 	-	-	L	L
Lake Rowa	an O	• Nil	 Approx. 15 buildings have been identified (from 2015 aerial photography) Located on the Boosey Creek floodplain Flood overlay controls are required as evident by captured 2012 peak flood levels Scoping flood study is required with a focus of improved flood mapping 	-	-	Н	L
Marungi	1	• Nil	 Approx. 10 buildings identified (from 2015 aerial photography) No riverine type flooding identified Limited low-lying land subject to localised drainage inundation shown in flood overlay controls in planning scheme No further action 	-	-	-	-
Nathalia	2	 Nathalia Flood Mitigation Report (SR&WSC, 1978) Documentation and Review of the 1993 Victorian Floods Volume 4 (Hydro Technology, 1995) Nathalia Flood Mitigation Scheme Audit Report (FIDS, 1996) Broken Creek Management Strategy (SKM, 1998) Nathalia Floodplain Management Plan (SMEC Victoria, 2005) Detailed design (SKM?) TFWS Investigation CT Management? 	 Approx. eight kilometres of levees constructed in the late 1980s. The levees system was upgraded and augmented in late 2000s, including temporary flood barriers Council remains committed in managing the flood protection system TFWS Implemented including new flow gauges, and new BoM prediction services MFEP has been updated FloodSafe Guide to be prepared New flood mapping required in planning scheme (rural study area) 	-	-	-	-

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Numurkah	5	 Documentation and Review of the 1993 Victorian Floods Volume 4 (Hydro Technology, 1995) Broken Creek Management Strategy (SKM, 1998) Numurkah Flood Study (WT, 2012) Numurkah Floodplain Management Study (ongoing) 	 Flood study component completed in 2014 Further work to extend modelling is now underway Mitigation options are currently being explored including structural works and TFWS The MFEP has been updated and proved useful during 2016 floods New flood zone and overlay controls are required Flood contour Atlas needs updating 	н	н	н	н
St James	1	No flood study	 Approx. 45 buildings identified (from 2105 aerial photography) New flood overlay controls are required as evident by captured 2012 peak flood levels Scoping flood study is required 	-	-	н	м
Tungamah	3	• 1% AEP Flood Declaration Project (RWC, 1984)	Floodplain management study required	н	н	н	н
Waaia	0	 Nil Significant Drainage Line Mapping within the SIR (GBCMA, 1998) 	 Approx. 55 buildings have been identified (from 2015 aerial photography) Not identified prone to riverine type flooding Part of Waaia subject to drainage issues along natural drainage lines 	-	L	L	L
Wilby	0	• Nil	 Approx. 55 buildings have been identified (from 2015 aerial photography) Located on the Sandy Creek Floodplain Flood overlay controls are required as evident by captured 2012 peak flood levels Scoping Study is required 	-	-	Н	L
Wunghnu	3	• Nil	Flood scoping study required	МН	М	М	М
Yarrawonga	4	 Murray River Floodplain Management Study (GDH, 1986) Overland Drainage and Flood Study (BMT WBM, 2015) 	 Local drainage options are being explored New flood overlay controls are required Flood contour Atlas needs updating 	Н	-	Н	н

Murrindindi Shire



Figure 1. Murrindindi Shire Council area showing towns and planning scheme flood overlay controls

 Table 1.
 Murrindindi Shire risk assessment (ranking 1: low, and 5: high)

 Draft priority rankings for stakeholder discussion: Low (L), Medium (M), High (H) and No Action (-) (for urban centres)

Name	AAD		Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood
Alexandra	2		Nil	 Flooding occurred from UT creek in 1975 that forms the bench mark for land use planning. This is the current basis of overlay controls in the planning scheme Overland flooding has been experienced in the town particularly from a tributary north west of town Riverine and overland flood study required 	L	-	н	н
Buxton	3	•	Acheron River Flood Hydrology Study (BMT WBM, ongoing)	Floodplain Management Study required	м	м	Н	н
Eildon	0	•	Nil	 There are two waterways that flow through the town that have catchments under five square kilometres. Furthermore, the waterways traverse through wide open-spaced corridors. There are some minor drainage lines that feed stormwater to the waterways There are no current identified riverine flooding issues Overland flooding associated with drainage lines is unknown Consider overland flood study BoM flood warning products such as Flood Watch is possibly the only feasible product given no warning times 	-	-	L	L
Kinglake Central	0	•	Nil	 The town is located at the very top of the Great Dividing Range, and has some minor waterways have small catchments that are deeply incised. As such, there are no identified riverine or overland type flooding issues. No further action 	-	-	-	-
Kinglake East	0	•	Nil	 The town is located at the very top of the Great Dividing Range, and has waterways commanding small catchments that are deeply incised. As such, there are no identified riverine or overland type flooding issues. However, several drainage lines have been identified that drain into the waterways These drainage lines may have some overland flood issues Overland flood study should be considered BoM flood warning products such as Flood Watch is possibly the only feasible product given no warning times 	-	-	L	L
Marysville	1	•	Acheron River Flood Hydrology Study (BMT WBM, ongoing)	Floodplain Management Study required	-	-	М	м
Molesworth	1	•	Eildon to Murchison Flood Modelling Project - Goulburn River GPU Model Documentation (Water Technology, 2015 – internal document)	 Approx. 25 buildings have been identified (from 2015 aerial photography) in the town and a caravan park located on further north adjacent to the Goulburn River and are affected by depths of flooding up to 500 mm for a 1% AEP type flood. Scoping study required (with floor level survey), with finding linked to the MFEP Flood warning opportunity needs to be explored 	-	L	М	м
Narbethong	0	•	Nil	 This town is largely undeveloped and rural in nature with approx. 20 buildings Minor deeply incised waterways traverse the town, which commands catchment areas of around five square kilometres. There are no identified riverine or overland flooding issues No further action 	-	-	-	-
Pheasant Creek & Kinglake West	0	•	Nil	 Both towns are located at the very top of the Great Dividing Range There are numerous waterways throughout the towns and likely to be associated some overland flooding. Overland flood study required BoM flood warning products such as Flood Watch is possibly the only feasible product given little or no warning times 	-	-	L	L
Strath Creek	1	•	Nil	 The waterway of Strath Creek runs along the western edge of the hamlet and commands a catchment of approx. 62 square kilometres. 	-	-	L	L

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
			 Approx. 25 buildings have been identified (from 2015 aerial photography) in the town that appears to be somewhat elevated. Flood risk is not clear Carry out a regional flood mapping study that includes this town 				
Taggerty	1	 Acheron River Flood Hydrology Study (BMT WBM, ongoing) 	Floodplain Management Study required	-	L	н	M-H
Thornton	3	 Eildon to Murchison Flood Modelling Project - Goulburn River GPU Model Documentation (Water Technology, 2015 – internal document) 	 Approx. 30 out of an estimated 110 buildings (from 2015 aerial photography) are affected by depths of flooding up to 500 mm for a 1% AEP type flood. Also, the caravan park is partial impacted Scoping study required (with floor level survey) to inform the MFEP i.e. property listings relating to over floor flooding 	-	-	-	М
Toolangi	0	• Nil	 Yea River runs north of the town and is deeply incised There are no identified riverine of overland flooding issues No further action 	-	-	-	-
Yea	2	• Yea Flood Study (Water Technology, 2005)	 Flood zone and overlays incorporated into planning scheme MFEP has been updated The main issue for Yea is the caravan park exposed to flood hazard Flood Warning Prediction Service is now available at Yea's new gauge (2016). Further work is now required to link new gauge to flood mapping intelligence to MFEP FloodSafe Guide has been released (check) In 1973 a major storm over the town created major overland flooding issues Carry out an overland flood study 	-	-	-	Н

Strathbogie Shire



Figure 1. Strathbogie Shire Council area showing town localities and existing flood controls

Table 1.Strathbogie Shire risk assessment (ranking 1: low, and 5: high)	
---	--

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Work	Total Flood Warni System	Land Use Plannin	Municipal Flood Emergency Plan
Avenel	2	 Internal Rural Water Commission file used by GB CMA to prepare 1% AEP flood contours (Flood Atlas) for Hughes Creek together with infield flood overlay controls for planning scheme inclusion. Granite Creek Regional Flood Mapping Study (check name) (Water Technology, ongoing) 	 Update flood zone and overlay controls in planning scheme Update 1% AEP flood contours in Flood Atlas Flood scoping study required to assess flood warning needs and emergency planning 	м	м	Н	м
Euroa	4	 Euroa Flood Study – Final Report (CMPSF, 1993) Euroa Flood Study – Hydraulic Assessment (Lawson & Treloar 1997) Euroa Floodplain Management Study - 2 volumes (SKM, 1997). Total Flood Warning System (CT Management 1997) Check Euroa Water Management Scheme (Steering Committee, 1999) Urban Levee Review (SKM, 2013) Euroa Post Scheme Flood Mapping Study (Cardno, 2014) Levee Upgrade Report (GMR, 2016 – ongoing) 	 Total Flood Warning System implemented (need better access to flood data by community) Flood warning services are provided by BoM Water Management Scheme Implemented by Council including formalising the Castle Creek levee and waterway/floodplain vegetation thinning. Note that vegetation thinning along the Seven Creeks were achieved by significant exotic tree and weed removal as part of river health program by GB CMA Flood zone and overlay controls in place but require some revision based on latest Study M AEP flood contours declared and part of Flood Atlas but need to be revised based on latest Study Property-specific flood information should be rolled out Castle Creek levee refurbishment required to ensure 1% AEP performance Monitoring action plan required to manage sand slugs under rail and Old Hume bridge structures Council remains committed for manage the water management scheme 	Н	Н	Н	н

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Graytown	0	• Nil	 A waterway, with a 26 square kilometre catchment, flows west of the town with small localised drainage lines through the settlement The area is largely undeveloped and rural in nature Less than ten buildings identified from available aerial photography Possible scoping study required 	-	-	L	L
Locksley	1	 Granites Creek Regional Flood Mapping Project (Water Technology, ongoing) 	 Pranjip (Burnt) Creek commends a catchment of some 36 square kilometres LiDAR ground level data and flood mapping indicates some 25 buildings (identified from 2015 aerial photography) are on high land above the estimated 1% AEP flood levels. Update flood overlay controls in planning scheme Flood warning requirements may rely on BoM flood watch products 	-	-	М	L
Longwood	2	• Nil	 Some 100 building exists (from 2015 aerial photography) LiDAR ground level data suggest some possible exposure to flood risk Some broad-brush mapping included in planning scheme Scoping flood Study required 	-	-	L	L
Mangalore	0	• Nil	 Eight Mile Creek commands a catchment area of some 10 square kilometres that passes the town to the north. A smaller waterway flows south of the town No detailed ground level information is available Major storms passed over the area in early 2016 but the flood impact is unknown Scoping study is required 	-	L	М	L
Nagambie	1	 Flood Risk Assessment for Chinaman's Caravan Park (SKM, 1999) Nagambie Flood Study – Draft Hydraulics Report (BMTWBM – ongoing) 	 Flooding of Low-lying areas including Tabilk Depression identified Flood zone and overlay controls are required in planning scheme MFEP needs updating Flood warning requirements may rely on BoM's Flood Watch products 	-	-	н	н
Old Longwood	0	• Nil	 Largely undeveloped with few buildings Winding Creek flows west of town commanding a catchment of some ten square kilometres A small drainage line identified through the town flowing west to east Rely on available BoM's products such as Flood Watch Possible scoping study 	-	-	L	L
Ruffy	0	• Nil	 Small waterway flows east of town commending a catchment of some three square kilometres Possible localised drainage issues rather than riverine type flooding No further action 	-	-	-	-
Strathbogie	0	• Nil	 Some sixty buildings exist in the town (identified from 2015 aerial photography) Spring, Magiltans and Seven Creeks flow through the town. LiDAR ground level data reveals that these creeks are deeply incised and unlikely to create flooding issues. Possible scoping study require to determine flood extents 	-	-	L	L
Violet Town	4	 Violet Town Flood Scoping Study – Final Report (GHD/GEO ENG, 2002) Violet Town Flood Study (Water Technology, 2007) MFEM Updated Drafted (2011) Flood Warning arrangements (GMR, 2011) Violet Town Floodplain Management Plan (2012, Water Technology) Violet Town Floodplain Management Scheme (2012, Water Technology) Detail design for civil mitigation works (GMR Engineering – ongoing) FloodSafe Guide prepared 	 Flood zone and overlay controls prepared and not yet in planning scheme (await the implementation of mitigation works) 1% AEP flood in Flood Atlas online Flash flood arrangements have been formulated but not implemented FloodSafe guide distributed Community negotiation on civil mitigation works are continuing MFEM updated 	н	Η	Н	-



Figure 1. Showing rural study areas

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Broken Creek							
Broken Effluent Tributaries (Pine Lodge, Daintons, Congupna Guilfus & O'Keefe Creek)	5	 Documentation and Review of the 1993 Victorian Floods Volume 4 (Hydro Technology, 1995) 	 Flood overlay controls exist in the planning scheme based on flood information from 1993, which is a reference flood for the 1% AEP flood MFEP updated for towns within the regional area (Congupna and Tallygaroopna) A regional flood study is unlikely to improve flood knowledge for the 1% AEP type flood. However, it may be warranted to explore flooding patterns for a range for flood magnitudes to improve flood intelligence and mapping warning information 	-	М	L	м
Lower Broken Creek	5	 Documentation and Review of the 1993 Victorian Floods Volume 4 (Hydro Technology, 1995) Broken Creek Management Strategy Part 1 - 2 volumes (Sinclair Knight Merz, 1996) Broken Creek Management Strategy Part 2 - 2 volumes (Sinclair Knight Merz, 1996) Nathalia Floodplain Management Plan (SMEC Victoria, 2005) include regional mapping from Walshs Bridge to Narioka Nathalia Floodplain Management Study (SMEC, 2005) 	 New mapping to be incorporated into the planning scheme. Inventory of levees completed in 2005 as part of Nathalia Floodplain Management Study Regional mapping between Narioka and the Murray River could be carried out but considered a low priority. Implication of flood warning to Nathalia will be of a benefit to downstream areas regional areas to the Murray. 	-	М	н	н
Mid Broken Creek	5	 Broken Creek Management Strategy Part 1 - 2 volumes (Sinclair Knight Merz, 1996) Broken Creek Management Strategy Part 2 - 2 volumes (Sinclair Knight Merz, 1996) Numurkah Floodplain Management Study – Includes regional mapping from Broken Creek Katamatite to Walshs Bridge stream gauges (Water Technology, ongoing) 	 Flood overlay controls exist in planning schemes that require updating New flood height prediction services are currently being explored by the BoM to Numurkah Draft MFEP has been prepared 	н	н	Н	н
Muckatah Depression	3	 Documentation and Review of the 1993 Victorian Floods. Volume 4 – Broken River (HydroTechnology, 1995) Broken Creek Management Strategy Part 1 - 2 volumes (Sinclair Knight Merz, 1996) Broken Creek Management Strategy Part 2 - 2 volumes (Sinclair Knight Merz, 1996) 	 Flood overlay controls exist in planning scheme Could carry out a rural flood study to better define flood intelligence and mapping See further comments in the "Upper Broken Creek" 	-	L	L	L
Upper Broken Creek	4	 Broken Creek Management Strategy Part 1 - 2 volumes (Sinclair Knight Merz, 1996) Broken Creek Management Strategy Part 2 - 2 volumes (Sinclair Knight Merz, 1996) 	 A regional study is required that will include numerous townships – refer to Moira Shire risk assessment for "urban centres" Stream gauge exist in Tungamah The 1996 Study highlights land management practices has altered drainage within the region. Land management practices needs to be managed Rural drainage plan required to address both drainage and water quality (not necessary part of the floodplain management strategy) 	-	М	н	м
Broken River			·				
Lower Broken River	5	 Documentation and Review of the 1993 Victorian Floods Volume 4 (Hydro Technology, 1995) 	 Flood mapping is poor downstream of Benalla to Stewarton New flood study required to improve flood intelligence and mapping. This would provide information of flow patterns (including flow distribution into both the upper and lower Broken Creek study areas, and provide intelligence for flood warning and emergency management 	-	L	н	н
Upper Broken River	2	 Some rural flood mapping and flood level capture Design Flood Hydrology for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 This rural study area includes Holland Creek Some flood overlay controls exist in planning schemes A regional flood intelligence and flood mapping study is required, which can include the towns outlined in the "urban centres" Note the assessment of urban centre at a regional rural scale may provide preliminary insight before deciding to carry out a full flood study 	-	М	н	м
Goulburn Syste	m	,					
Acheron River	2	Acheron River Flood Hydrology Study (BMT WBM, ongoing)	 Some flood overlay controls exist in the planning scheme but based on limited information Stream gauge is established in Buxton with flood prediction services provided by BoM 	-	L	н	L

Name

Summary of past and existing studies

Summary of implemented study recommendations (Other comments)

otal Flood Warnin System and Use Planning

Goulburn Syster	m (cont.						
Corop Lakes	5	Corop Lakes Scoping Study (GHD, 2012)	 Flood overlay controls exist in the planning. Minor improvements could be included east of Colbinabbin. Flood warning arrangements between GMW and community are in place 	-	-	L	L
Dabyminga Creek	1	• Tallarook Flood Study (GB CMA, 2008) extends into this regional area	 Flood mapping required to be updated in the planning scheme New regional flood study may be carried out but should be extended to include Tyaak and Reedy Creek No current buildings known to be at risk to over floor flooding 	-	L	Н	L
Delatite River	2	 Design Flood Hydrology for the Goulburn and Broken River Catchments (Jacobs, ongoing) Desktop flood mapping completed for 2016 flood overlays using limit recorded peak 2010 flood level and LiDAR ground information 	Regional flood study required to improve flood intelligence and flood mapping utilising hydrologic data from current Jacobs study	_	L	L	м
Ford Creek	1	 Mansfield Flood Intelligence and Mapping Study (GB CMA, 2014) Design Flood Hydrology for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	Regional flood mapping required to improve flood intelligence and mapping to assist with future long-term growth around Mansfield	-	L	н	м
Seymour to Shepparton	5	 Documentation and Review of the 1993 Victorian Floods. Volume 1 – Summary Report (Hydro Technology, (1995) Declaration of 1% AEP flood level 	 Flood mapping exists in planning schemes but found to be inaccurate in some areas Requires regional flood study including operations of Nagambie Weir 	-	М	М	м
Granite Creeks	5	 Granite Creeks Regional Flood Study (Water Technology, ongoing) 	 Flood overlay mapping exist in planning schemes Planning schemes will need to be updated following completion of the regional flood study 	-	L	м	м
Howqua River	1	 Design Flood Hydrology for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	Regional flood modelling required following the completion of design hydrology report	-	L	L	L
Lower Goulburn	5	 Inquiry into the Lower Goulburn River (Parliamentary Inquiry, 1968) Lower Goulburn Floodplain Management Study – 2 volumes (Cameron McNamara (1987) Documentation and Review of the 1993 Victorian Floods Volume 5 (Hydro Technology, 1995) Lower Goulburn Waterway and Floodplain Management Plan – 2 volumes (Sinclair Knight Merz, 1996) Lower Goulburn Levee Audit (SMEC, 1998) Lower Goulburn Business Case Summary (PricewaterhouseCoopers, 1998) Lower Goulburn Modified Findlay Scheme (SMEC, 1999) Lower Goulburn Floodplain Rehabilitation Scheme – 2 Volumes (Water Technology, 2005) Rural Levee Assessment (Water Technology, 2013) 	 Flood mapping products exist that should be integrated into planning schemes. A flood intelligence map exists relative to the Shepparton and McCoys Bridge river gauges. The Lower Goulburn Floodplain Rehabilitation Scheme project was abandoned in 2005 following no funding agreement Requires community workshop to specifically address its willingness to re-examine management options including operation and maintenance costs associated with the lower Goulburn levees Flood warning arrangements are in place at the Shepparton Gauge that provides adequate warning to the lower Goulburn. Also, Goulburn Murray Water has arrangements in place for those within the Loch Garry Flood Protection District 	м	-	Н	н
Lower King Parrot Creek	1	 Nil 1% AEP flood levels has been estimated based on a limited number of recorded peak flood levels. Rural flood. 	 Flood overlay controls exist in the planning scheme, based on limited information. A regional flood study would improve flood intelligence and mapping. Ground LiDAR exists that would be used to carry out such a study The area is mostly rural in nature with pockets of rural living along the creeks 	-	L	L	L
Maindample Region	1	• Nil	 Flood mapping was carried out by on-site inspections around Maindample Inspection of aerial photograph indicate few buildings within the rural areas that surrounds Maindample A regional flood study is not considered warranted 	-	-	-	-
Mid Goulburn	5	 Goulburn Broken Flood Atlas of 1% AEP flood contours (GB CMA, 2005) Memo - Eildon to Murchison Flood Mapping Project (Water Technology, 2015) Total Flood Warning System 	 Flood overlay controls exist in planning schemes that requires updating Flood Atlas requires updating Total Flood Warning System implemented in 2000 with forecasts to Seymour. Community guides were also prepared Review flood guides to new FloodSafe format 	-	Μ	н	м

Goulburn System (cont.)

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Sunday & Dry Creeks	1	 Some rural flood mapping and peak flood level capture No detailed flood studies 	 Some flood overlay control exist in the planning scheme This regional study area would include the townships of Wandong, Heathcote Junction, Kilmore East, Coulson Crossing, Waterford Park and Broadford 	-	н	Н	н
Tatura/ Tongala Region	5	 Flooding of Tongala-Stanhope Irrigation District – March 1950 	 The nature of flooding is largely contained within a series of depression systems Flood overlay controls exist in planning schemes A regional flood study is not warranted as it would be unlikely to provide any significant new flood knowledge 	-	L	L	L
Upper Goulburn	1	 Design Flood Hydrology for the Goulburn and Broken River Catchments (Jacobs, ongoing) 	 This area is between Jamieson to Woods Point Regional flood study could be carried out using hydrologic data from study 	-	м	М	м
Upper King Parrot Creek	1	 Flowerdale Flood Study – Flood Intelligence and Mapping (GB CMA, 2014) 	 Flood overlay controls exist in planning schemes, but should be updated to reflect flood study findings MFEP should also reflect study findings Flood warning requirements needs to be explored 	-	м	н	н
Whiteheads Creek	1	Whiteheads Creek Flood Study (Cardno, ongoing)	 Flood mapping controls exist in the planning scheme The current study includes overland flood mapping Flood warning is less than 6 hours. A local warning system needs to be explored 	-	н	н	н
Yea River	1	 Yea Flood Study (Water Technology, 2005) 1% AEP flood levels are currently estimated by adding a margin (determined by NRE) to historic profiles of a moderate flood. 	 Regional Flood Study would greatly improve flood intelligence and mapping 	-	I	М	м
Murray System				1	<u> </u>		1
Barmah to Echuca	4	 Murray River Floodplain Management Study (GHD, 1986) Lower Goulburn Floodplain Rehabilitation Scheme (Water Technology, 2005) 1% AEP Flood Contour Atlas available 	 Stream gauges are established in Barmah and Echuca with flood class levels Flood overlay controls exist in planning schemes, but needs to be updated with new mapping from the 2005 study The regional study area includes Echuca Village and Lower Moira (Woodbine Drive) Further work around flood warning products would be useful 	-	М	L	м
Cobram to Ulupna	5	 Murray River Floodplain Management Study (GHD, 1986) Murray River Regional Floodplain Study – Dicks/Seppelts levees to downstream of Ulupna Creek Confluence Study Report (Water Technology, 2011) Rural Levee Assessment (Water Technology, 2013) 	 Flood overlay controls exist in the planning scheme, but needs to be updated with new information A number of stream gauges exist where the BoM will issue flood warnings. Need to review MFEP for regional study area in light of 2016 floods – document weak levees Require community workshop to specifically address its willingness to examine a project to include operation and maintenance costs of the rural levees 	м	М	Н	М
Piree Creek to Barmah	1	 Murray River Floodplain Management Study (GHD, 1986) Barmah-Millewa Hydrodynamic Model (Water Technology 2005) Rural Levee Assessment (Water Technology, 2013) 	 Flood overlay control exists in the planning scheme Extend the Murray River Regional Floodplain Study from Ulupna to Barmah to improve flood intelligence and mapping Require community workshop to specifically address its willingness to examine a project to include operation and maintenance costs of the rural levees 	_	М	L	м
Ulupna to Piree Creek	3	 Murray River Floodplain Management Study (GHD, 1986) Rural Levee Assessment (Water Technology, 2013) 	Join this regional study area with Murray Piree Creek to Barmah				
Upstream of Yarrawonga	1	• Murray River Floodplain Management Study (GHD, 1986)	 Flood overlay control exists in planning scheme This section of the river is mostly within the confines of Lake Mulwala Regional flood study would be unlikely to bring substantial new flood knowledge 	-	L	L	L

Name	AAD	Summary of past and existing studies	Summary of implemented study recommendations (Other comments)	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Yarrawonga to Cobram	2	 Murray River Floodplain Management Study (GHD, 1986) No detailed flood study exists 	 Flood overlay control exists in the planning scheme Flooding is largely confined within the Murray Valley until Cobram East Regional flood study required to gained flood intelligence and mapping 	-	Н	М	н

Appendix C: Program logic for program delivery

The logic for the four long-term programs outlined in Section1.5 are

- Flood Mitigation (refer to Figure C-10);
- Total Flood Warning Systems (refer to Figure C-11);
- Land-use Planning (refer to Figure C-12); and
- Emergency Management and Access to Flood Information (refer to Figure C-13).

In preparing this regional Strategy with stakeholders it has become apparent that the four programs considerably overlay. For instance, the access to flood information not only applies within the emergency management program but is very much a large part of TFWS where access to fit for purpose flood information can provide important education and awareness material to ensure flood resilience. As such, a new program logic for the access to, and sharing of flood information has been developed (see **Figure C-14**).



Figure C-10: Program logic for flood mitigation program

OBJECTIVES (>10 years)		Reduce existing flood	risks - Flood warnings	Build a flood resilient community
OUTCOMES (3-10 years)	Floed warning information is built and maintained where it is cost effective and socially and envroomentally feasible.	viding Interviced intelligence Platform providing s with emergency managers with high-quality level of services	Accountability and auditing regime to provide better understanding of risks of failure	Communities determining her own flood warning service needs
MANAGEMENT ACTIONS (Annual)	war	ommunities through the national teleph ning system (Emergency Alert), BoM CSES website, local dissemination sys used by LGAs and media	Agencies acce	erpretation and educate communities on how
	flood informat systems (Floo	n and maintenance of tion and interpretation d Database and Flood latform (FloodZOOM) warnings l	ing, warnings and p n and VICSES into impa	edications by cts at the local
FOUNDATIONAL ACTIVITIES - INFORMATION, PLANNING AND INVESTMENT		Establishment, maintenance and - Data collection network infrasi - Flood prediction service mainte - Message construction and dis - Flood emergency planning and	ructure inance semination	
		velopment and review of State and re lood Warning System development pla Floodplain Management Strategie Assess flood risk and	n. Implementation plans for Regi s and outputs of flood studies	
	Governance of Victorian			
FOUNDATIONAL ACTIVITIES - GOVERNANCE AND STANDARDS	Flood Warning Consultative Committee for agency co-operation (with regional representation)	Review of National Arrangements for Flood Forecasting services	mework for for TFWS w ent of TFWS the Inspector DELWP lead, Managemen	of assurance process revisives reported to General for Emergency established under the Management Act 2013

Figure C-11: Program logic for Total Flood Warning Systems



Figure C-12: Program Logic for land-use planning



Figure C-13: Program logic for emergency management



Figure C-14: Program logic for sharing of flood information
Appendix D: Summary of Flood Studies, Plans, Work Plans

Table D-18: List of completed scoping studies

Scoping Studies

- 1. Shepparton Mooroopna Flood Scoping Study (1998)
- 2. Jamieson Flood Scoping Study (SKM, 2003)
- 3. Violet Town Flood Scoping Study (GHD, 2002)
- 4. Corop Lakes Flood Scoping Study (GHD, 2012)

Table D-19: List of completed flood studies

Flood Studies

- 1. Broken Creek Management Study Stages 1 & 2 (SKM, 1998)
- 2. Flood Risk Assessment for Chinaman's Bridge Caravan Park (1999)
- 3. Seymour Floodplain Mapping Study (WBM Oceanics Australia, 2001)
- 4. Seymour Floodplain Mapping Study Addendum to Final Report Whiteheads Creek Flood Mapping (WBM Oceanics Australia, 2001)
- 5. Lower Goulburn Rehabilitation Project Socio-economic Issues Assessment (Earth Tech, 2002)
- 6. Yea Flood Study (Water Technology, 2005)
- 7. Merrigum Flood Study (WMB Oceanics Australia, 2005)
- 8. Mansfield Flood Study (Earth Tech, 2005)
- 9. Barmah-Millewa Forest Hydrodynamic Model Study (Water Technology, 2005)
- 10. Lower Goulburn Floodplain Rehabilitation Project Hydraulic Modelling Report (Water Technology, 2005)
- 11. Lower Goulburn Floodplain Study Geomorphology (SKM, 2006)
- 12. Lower Goulburn Floodplain Rehabilitation Scheme Addendum A Hydraulic Performance of the Engineered Option 2 (Water Technology, 2006)
- 13. Mansfield Flood Study Extension (Earth Tech, 2006)
- 14. Tatura Floodplain Management Study (WBM Oceanics Australia, 2006)
- 15. Violet Town Flood Study (Water Technology, 2007)
- 16. Lake Nillahcootie Flood Study (Cardno, 2008)
- 17. Tallarook Flood Investigation (Goulburn Broken CMA, 2008)
- 18. Barmah-Millewa Hydrodynamic Modelling Model Re-calibration (Water Technology, 2009)
- 19. Goulburn River Environmental Flows Hydraulics Study (Water Technology, 2010)
- 20. Murray River Regional Flood Study Dicks/Seppelts levees to downstream of the Ulupna Creek confluence (Water Technology, 2011)
- 21. Rural Levee Assessment (Water Technology, 2013)
- 22. Flowerdale Flood Intelligence and Mapping Study (GBCMA, 2014)
- 23. Mansfield 1% AEP Flood Mapping Project (GBCMA, 2014)
- 24. Murchison Flood Mapping Study Report (Water Technology, 2014)
- 25. Eildon to Murchison Flood Modelling Project GPU Documentation (Water Technology, 2015)
- 26. Flood Assessment of Irrigation Infrastructure in the Goulburn Murray Irrigation District (Goulburn Broken & North Central CMAs, 2016).
- 27. Shepparton East Overland Flow Urban Flood Study (BMT WBM, 2017)
- 28. Design Flood Hydrographs for the (Upper) Goulburn and Broken River Catchments (Jacobs, 2017)
- 29. Nagambie Flood Study (BMT WBM, 2017)
- 30. Shepparton Mooroopna Flood Mapping and Intelligence Study (Water Technology, Ongoing)

- 31. Granite Creeks Regional Flood Mapping Study (WT, Ongoing)
- 32. Kilmore Flood Study (BMT WBM, Ongoing)
- 33. Flood Study of the Goulburn and Broken Rivers (Ongoing)
- 34. Whiteheads Creek Catchment Flood Mapping Project (Cardno, Ongoing)
- 35. Acheron River Flood Hydrology Study (Jacobs, Ongoing)
- 36. Sunday and Dry Creek Regional Flood Mapping Study (yet to be announced)

Table D-20: List of completed Floodplain Management plans

Floodplain Management Studies

- 1. Euroa Floodplain Management Study (1997)
- 2. Lower Goulburn Waterway and Floodplain Management Plan and Supporting Document (SKM, 1998)
- 3. Lower Goulburn Floodplain Rehabilitation Scheme Modified Findlay Scheme (SMEC, 1998)
- 4. Lower Goulburn Floodplain Rehabilitation Scheme Business Plan (Summary) (PcW, 1999)
- 5. Lower Goulburn Levee Audit Report Main Report and Appendices (1999)
- 6. Shepparton Floodplain Management Study (Stage 1 and 2) (SKM, 2002)
- 7. Benalla Floodplain Management Study (Cardno Willing, 2002)
- 8. Nathalia Floodplain Management Plan (SMEC, 2005)
- 9. Seymour Flood Mitigation Communication Investigation (WBM Oceanics Australia, 2006)
- 10. Assessment of Flood Risk to the Township of Barmah and Preliminary Flood Mitigation Review (Water Technology, 2008)
- 11. Benalla: Review of Floodplain Management Works (2009)
- 12. Violet Town Floodplain Management Scheme (Water Technology, 2012)
- 13. Yarrawonga Flood Management & Drainage Master Plan (BMT WBM, 2013)
- 14. Euroa Post Flood Mapping and Intelligence Project (Cardno, 2015)
- 15. Numurkah Floodplain Management Study (Water Technology, 2017)

Table D-21: List of flood (mitigation implement actions

Flood (Mitigation) Implementation Actions

- 1. Murray River Levee Works Program Design and Construct Programs (1998-2002)
- 2. Euroa Water Management Scheme Technical Report (1999)
- 3. Euroa Water Management Scheme (FPM Plan) (2000)
- 4. Cobram urban levees upgrade (SKM, 2003)
- 5. Water Management Scheme Benalla Revision 1 April 2003
- 6. Nathalia Floodplain Management Plan (Webb Consulting, 2005)
- 7. Benalla Water Management Scheme: Vegetation Management Plan (CT Management, 2006)
- 8. Shepparton Mooroopna Flood Warning and Emergency Management Project (Water Technology, 2007)
- 9. Flood Atlas (on website) (Goulburn Broken CMA, 2008)
- 10. Nathalia Mitigation Scheme Implementation (Moira Shire, 2009-2012)
- 11. Seymour Flood Mitigation Project Preliminary Design Report (Webb Consulting, 2009)
- 12. Seymour Pre-Detailed Flood Mitigation (2010 Consultation Plan)
- 13. Euroa Mitigation Plan Implementation Castle Creek Levee (2011)
- 14. Barmah Township Flood Mitigation Functional Design (2012)
- 15. Violet Town Functional Mitigation Design (GMR Engineering, 2012 to date)
- 16. Tatura Floodplain Mitigation (Railway Culverts and floodway works 2012)
- 17. Violet Town Levee Upgrade Report (GMR, 2016 to date)

- 18. Benalla Flood Information Portal Report (Cardno, 2016)
- 19. Seymour Levee Detailed Design (Mitchel Shire, 2016)

Table D-22: List of Local Flood Guides

Local Flood Guides

- 1. Katamatite
- 2. Nathalia
- 3. Numurkah
- 4. Muckatah Depression Fact Sheet
- 5. Tungamah
- 6. Congupna
- 7. Katandra West
- 8. Mooroopna Shepparton
- 9. Murchison
- 10. Tallygaroopna
- 11. Violet Town
- 12. Seymour
- 13. Yea
- 14. Jamieson
- 15. Benalla

Table D-23: List of 1% AEP flood level declarations

Declaration of 100-year flood levels (Water Act 1989)

Location	Date of Declaration
Broken River – Benalla	19 July 2001
Euroa – Seven Creeks and Castle Creek	7 March 2002
Seymour – Goulburn River	22 August 2002
Shepparton - Mooroopna	22 August 2002
Tatura - Mosquito Depression	18 January 2007
Murray River – Lake Mulwala to Echuca (15 Sheets)	19 August 2004
Merrigum - Mosquito Depression	18 January 2007
Nathalia District – Broken Creek	18 January 2007
Yea – Yea River (Boundary Creek)	18 January 2007
Mansfield – Ford Creek	18 January 2007
Jamieson – Goulburn River	18 January 2007

Appendix E: 2002 Regional Strategy Program Review

Asset Management - Program 1

Table E-24: 2002 Regional Strategy Delivery – Asset Management (below) documents in detail the extent to which this program has been delivered.

The Asset Management program has largely been addressed and remains ongoing in terms of operation and maintenance of urban levees. Consistent with the VFMS, operation and maintenance of urban levees is carried out by local government.

Any maintenance works on 'private' levees that are located on Crown land fall under the new permitting system managed by the Goulburn Broken CMA (otherwise such works may be subject for permits under planning schemes).

Other levees of significance are those currently being planned for Numurkah, Seymour and Violet Town.

Ref	Task	Status at 2017
Asset Reg	ister	
AR1	Upgrade and Maintain Asset Register by Goulburn Broken CMA	The Goulburn Broken CMA plays a support role, as required, and does not hold or maintain any asset register in terms of mitigation infrastructure such as town or rural levees. The construction authority is responsible maintaining an asset register, and particularly an operation and maintenance plan. Therefore, not relevant to CMAs.
PWD Leve	ees	
PWD1	Resolve legal liabilities	Despite lobbying groups such as the Cobram and Strathmerton over the
PWD2	Resolve arrangements for funding for O&M	past two decades, no traction has ever been reached to have the PWD levees maintained.
PWD3	Prepare a management plan	This is a statewide issue that has not been resolved and subject to recent Parliamentary Inquiry into mitigation infrastructure review
PWD4	Maintain levees	(Parliament of Victoria, 2012). The Victorian Floodplain Management Strategy has now clarified roles and responsibilities, accountabilities, and policies that specifically address rural levees.
Lower Go	ulburn Levees – includes part of Be	attie Depression levees along the Murray
LG1	Resolve legal liability issues	The levees do not form part of any formal scheme that has an O&M authority, so the levees remain unmanaged. See comments in PWD Levees above in relation to the VFMS.
LG2	Resolve arrangements for funding for O&M	See LG4 below
LG3	Formalise agreement with G-M Water over future arrangements for managing assets they currently maintain	Discussions with GMW confirm it only operates and maintains Loch Garry regulation and associated nine kilometres of levee around the Loch Garry wetland. This is largely funded through rates from beneficiaries within the Deep Creek floodplain. No agreement is required as this is an obligation under the legislative transitional arrangements under the Water Act when GMW was established in 1994.
LG4	Prepare a management plan	A significant number of past studies and plans have been carried out as part of a project called the Lower Goulburn Floodplain Rehabilitation Scheme (2005). This was prepared following the 1993 floods, as a result of the State Government request to find a solution to managing the rural levees. The plan relied 100% capital funding from State and

Table E-24: 2002 Regional Strategy Delivery – Asset Management

Ref	Task	Status at 2017
		Commonwealth with ongoing O&M provided by beneficiaries. It was never implemented.
LG5	Maintain levees	See LG4 above
Beattie De	pression Levees	
BD1	Maintain as required	These levees form part of the irrigation drainage network arrangement where the Beattie Depression receives drainage water from the Deakin Main Drain and Mosquito Depression. The levees minimise flooding of low lying areas including backwater flooding from the Murray River (near Echuca) in times floods. GMW continue to manage the Beattie Depression and the associated
0 - h		levees
Cobram To	own Levees	
CTL1	Prepare a management plan	Completed by Moira Shire Council
CTL2	Maintain the levees	Carried out by Moira Shire Council
Nathalia To	own Levees	
NTL1	Prepare a management plan	Completed by Moira Shire Council
NTL2	Maintain the levees	Completed by Moira Shire Council
NTL3	Acquire easement rights for levees	Preference to negotiate agreement rather using easements
Private Stra	ategic Rural Assets	
PSR1	Allow self-management either individually or through	There has been virtually no request for assistance to maintain private levees or any other assets.
	community or advisory committees via a floodplain management plan.	The flood overlay control captures most floodplain areas where new works require a permit. Under the new arrangements permits for maintenance works for levees on Crown land can be granted by the CMAs (since 2017), which was an action from the VFMS.
Asset Man	agement Review	
AMR1	Review/audit asset management plans every 5 years	This is part of the O&M by the asset manager and is ongoing. There have been two state-wide urban levee audits carried out

Flood Studies and Floodplain Management Plans – Program 2

The 2002 regional Strategy adopted a systematic, risk management approach for the conduct of studies, as outlined in the Victoria Flood Management Strategy (1998). Community engagement, including community reference groups, are important steps and have been largely employed during the life of the studies. This allows for the sharing flood knowledge and the vetting of study outputs such as flood mapping, mitigation measures and recommendations.

 Table E-25 (below) documents the extent to which this program has been delivered.

	1	-1 1 - 1 - 11		
Table E-25: 2002 Regiona	il Strateav Deliverv -	– Flood Studies a	and Floodnlain	Manaaement Plans
1001C E 20. 2002 negione	n Strategy Denvery	11000 3100103 0	ina nooapiani	in an agement i rans

Ref	Task		Status at 2	2017
Abbreviati Completed		⊠ = S	Study/Plan Completed	☑ = Study/Plan Mostly
	n Scoping Study	UFMS	S = Urban Floodplain Management Study	L = Low Priority
RSS = Rural	Scoping Study	RFMS	5 = Rural Floodplain Management Study	M = Medium Priority
UFS = Urba	n Flood Study	UFMI	P = Urban Floodplain Management Plan	H = High Priority
RFS = Rural	Flood Study	RFMF	P = Rural Floodplain Management Plan	
Murray Riv	ver Basin			
MU1	Barmah Urban Study (UFMS) (L)		Two studies have been completed. Asset Township of Barmah and Preliminary Flo Technology, 2008) and Barmah Townshi Design (Water Technology, 2012). Outco infrastructure greatly outweigh the bene proceed.	ood Mitigation Review (Water p Flood Mitigation Functional ome is the cost of mitigation
MU2 1	Yarrawonga Urban Study (UFS) (M)	/	Yarrawonga Flood Management & Drain 2013). This study was carried out to info drainage management and at the same t flood mapping.	orm Moira Shire on future
MR1-1	Murray River: Dick's Leve Piree Creek Stage 1 (RSS) (H)	ee to	The Murray River Regional Flood Study - downstream of the Ulupna Creek conflu was a departure from the three-staged a regional Strategy.	ence (Water Technology, 2011)
MR1-2 ☑	Murray River: Dick's Leve Piree Creek Stage 2 (RFS) (H)	ee to	This is an example of a partnership approach. New technology (LiDAR) became available and both NSW and Victoria formed a partnership to look at an important reach of Murray River from Cobram East to	
MR1-3 Murray River: Dick's Levee to Piree Creek Stage 3 (RFMP) (H)		ee to	downstream of Ulupna Creek and Murra investigated the performance on urban Cobram and Tocumwal (NSW) and was u works. It also covered the more populat and Strathmerton. Flood intelligence ha	flood mitigation schemes at used to seek further mitigation ted areas including Koonoomoo
			It was not possible to extend this study t allow for additional LiDAR Capture. The most of the three stages, but did not cor around the PWD levees maintenance. Se Management Program 1.	completed study did address nsider future arrangements
MR2-1	Murray River: Piree Cree Barmah Stage 1	k to	This was considered a low priority, which	h indicates no further action.
	(RSS) (L)			
MR2-2	Murray River: Piree Cree Barmah Stage 2	k to	This was considered a low priority, which	h indicates no further action.
	(RFMP) (L)			
Goulburn F	River Basin		1	
GU1 ☑	Avenel Urban Study (UFS) (L)		This was considered a low priority, which However, this town sits inside an ongoin Study and not only maps Hughes Creek b waterways through the north of Town.	g Granite Creek Flood Mapping
GU2	Buxton Urban Study (UFS) (L)		This was considered a low priority. Follo the priority to fully understand the natur part of the ongoing Acheron River Flood Ongoing) and a flood study is currently b Broken CMA.	re of flooding is high. This forms Hydrology Study (Jacobs,

Ref	Task		Status at 2	2017
Abbreviatio Completed	ns	⊠ = S	itudy/Plan Completed	☑ = Study/Plan Mostly
USS = Urbar	n Scoping Study	UFMS	5 = Urban Floodplain Management Study	L = Low Priority
RSS = Rural	Scoping Study	RFMS	= Rural Floodplain Management Study	M = Medium Priority
UFS = Urbar	n Flood Study	UFM	P = Urban Floodplain Management Plan	H = High Priority
RFS = Rural	Flood Study	RFMF	P = Rural Floodplain Management Plan	
GU3 ☑	Jamieson Urban Study (USS) (M)		The Jamieson Flood Scoping Study (SKM incorporated into Mansfield Planning Sc MFEP.	
GU4	Kilmore Urban Study (UFS) (M)		The Kilmore Flood Study (BMT WBM) is v	well advanced.
GU5 ☑	Mansfield Urban Study (UFS) (M)		Mansfield Flood Study (Earth Tech, 2005 Extension (Earth Tech, 2006) and Mansfi Project (GBCMA, 2014) have been utilise Mansfield Planning Scheme and Flood In	eld 1% AEP Flood Mapping ed and incorporated into
GU6 ☑	Merrigum Urban Study (UFS) (M-H)		Merrigum Flood Study (WMB Oceanics A completed and utilised and incorporated and Flood Intelligence for MFEP.	
GU7	Molesworth Urban Study (UFS) (L)		This was considered a low priority, which However, broad regional flood mapping Eildon to Murchison Flood Modelling Pro Technology, 2015).	work carried out under the
GU8 ☑	Murchison Urban Study (UFS) (L)		Murchison Flood Mapping Study Report been completed and utilised and incorpo Scheme and Flood Intelligence for MFEP	prated into Mansfield Planning
GU9 ☑	Nagambie Urban Study (UFS) (M)		Nagambie Flood Study (BMT WBM, 2017 Information need to be translated into a	
GU10	Rushworth Urban Study (UFS) (L)		This was considered a low priority, which Campaspe Shire has carried out drainage	
GU11 ☑	Seymour Urban Study (UFMP) (H)		Seymour Floodplain Mapping Study (WB Seymour Flood Mitigation Communicatio Australia, 2006), Seymour Flood Mitigati Report (Webb Consulting, 2009), have be Levee Detailed Design (Mitchel Shire, 20	on Investigation (WBM Oceanics on Project – Preliminary Design een completed and Seymour
GU12	Stanhope Urban Study (USS) (L)		This was considered a low priority, which depression exist south of town and no kn with the township of Stanhope.	
GU13 ☑	Tallarook Urban Study (UFS) (L)		Tallarook Flood Investigation (Goulburn but flood mapping not incorporated into investigation concludes that the bulk of AEP flood extent.	Mitchell Planning Scheme. The
GU14 ☑	Tatura Urban Study (UFMP) (H)		Tatura Floodplain Management Study (V and Tatura Floodplain Mitigation (Railwa 2012) are completed	
GU15	Thornton Urban Study (USS) (M-H)		Broad regional flood mapping work carri Murchison Flood Modelling Project GPU Technology, 2015). No study on Thornto	Documentation (Water
GU16	Toolamba Urban Study (UFMS) (L)		This was considered a low priority, which	h indicates no further action.

Ref	Task		Status at 2	017
Abbreviatio Completed	ins	☑ = S	tudy/Plan Completed	☑ = Study/Plan Mostly
USS = Urbar	n Scoping Study Scoping Study		5 = Urban Floodplain Management Study 5 = Rural Floodplain Management Study	L = Low Priority M = Medium Priority
	n Flood Study		P = Urban Floodplain Management Plan	H = High Priority
	Flood Study		P = Rural Floodplain Management Plan	
GU17-1 ☑	Violet Town Study - Stage (USS) (H)		Violet Town Flood Scoping Study (GHD, 2 overlay should be incorporated into plan	
GU17-2 ☑	Violet Town Study - Stage (UFMP) (H)	2	Both the Violet Town Flood Study (Wate Violet Town Flood Study (Water Technol Detailed design now underway by Strath	ogy, 2007) are completed.
GU18 ☑	Yea Urban Study (UFS) (M-H)		Yea Flood Study (Water Technology, 200 utilised and incorporated into Mansfield Intelligence for MFEP.	
GR1-1 ☑	Goulburn River: Eildon to Seymour Stage 1 (RSS) (L)		This was considered a low priority, which However, broad regional flood mapping Eildon to Murchison Flood Modelling Pro Technology, 2015).	work carried out under the
GR1-2	Goulburn River: Eildon to Seymour Stage 2 (RFMS) (L)		This was considered a low priority, which	n indicates no further action.
GR2-1 ☑	Goulburn River: Seymour to Shepparton Stage 1 (RSS) (L)		This was considered a low priority, which However, broad regional flood mapping Eildon to Murchison Flood Modelling Pro Technology, 2015).	work carried out under the
GR2-2	Goulburn River: Seymour to Shepparton Stage 2 (RFMS) (L)		This was considered a low priority, which	n indicates no further action.
GR3-1 ☑	Goulburn River: Sheppart to Murray River – Stage 1 (RFS) (VH)		These stages have been completed throu Goulburn Waterway and Floodplain Mar Document (SKM, 1998), Lower Goulburn Scheme Modified Findlay Scheme (SMEC	nagement Plan and Supporting Floodplain Rehabilitation
GR3-2 ☑	Goulburn River: Sheppart to Murray River – Stage 2 (RFS) (VH)		Floodplain Rehabilitation Scheme Business Plan (Summary) (PcN Lower Goulburn Levee Audit Report Main Report and Appendic Lower Goulburn Rehabilitation Project Socio-economic Issues A (Earth Tech, 2002), and Lower Goulburn Floodplain Rehabilitation Hydraulic Modelling Report (WT, 2005), Lower Goulburn Floodplain Rehabilitation Geomorphology (SKM, 2006), Lower Goulburn Floodplain Rehal Scheme Addendum A Hydraulic Performance of the Engineered (WT, 2006). The scheme was ultimately abandoned as not agree could be reached on funding arrangement for 100% of capital w the State and Commonwealth governments with O&M being pr from beneficiaries.	
GR4 ☑	Castle & Seven Creeks downstream of Euroa (RFS) (M-H)		Now underway as part of the Granite Gr which is an extensive regional flood map indicative intelligence for emergency ma planning. The study extends over many Creek) to Baddaginnie (Folly Creek).	ping study to provide good nagement and land-use

Ref	Task		Status at 2	2017
Abbreviation Completed	ons	⊠ = S	itudy/Plan Completed	☑ = Study/Plan Mostly
USS = Urbai			5 = Urban Floodplain Management Study	L = Low Priority
			= Rural Floodplain Management Study	M = Medium Priority
			P = Urban Floodplain Management Plan	H = High Priority
RFS = Rural	Flood Study	RFMF	P = Rural Floodplain Management Plan	
GR5 ☑	Corop Lakes (RFS) (L-M)		The Corop Lakes Flood Scoping Study (G recommendation around GMW operatic Community. It study found the current f Campaspe Planning Scheme are mostly s could be carried out at Colbinabbin Prim priority.	ons to be shared with the flood overlay controls within the sound. Some minor inclusion
GR6 ☑	King Parrot & Strath Creek (RFS) (L)	<s< td=""><td>This was considered a low priority, which However, the Flowerdale Flood Study Flo Project (GBCMA, 2014) covered some of some 20 kilometres of King Parrot Creek and several other areas.</td><td>ood Intelligence and Mapping the area. The study mapped</td></s<>	This was considered a low priority, which However, the Flowerdale Flood Study Flo Project (GBCMA, 2014) covered some of some 20 kilometres of King Parrot Creek and several other areas.	ood Intelligence and Mapping the area. The study mapped
GR7	Murrindindi River and Yea River (RFS) (L)	1	This was considered a low priority, which	h indicates no further action.
GR8	Sunday and Dry Creeks, including Broadford (RFS) (L)		This was considered a low priority, which However, these areas are now considered urban demands for growth due close nation for this study is ready to start pending co Disaster Funding Program.	ed a high priority given the peri- ture to Melbourne. A proposed
Broken Rive	er Basin			
BR1 ☑	Broken River: Benalla to Shepparton (RFS) (M)		Not yet carried out. Some Internal GBCI of Greater Shepparton Planning Amendr community) and further work using LiDA to update flood mapping for Benalla Rur Amendment. The area now has a very hi	nent (in field intelligence with R and 1% historical flood surface al City Planning Scheme
Broken Cre	ek Basin			
BCU1	Katamatite (USS) (L-M)		Not yet carried out.	
BCU2	Numurkah (UFMP) (H)		A flood study was underway prior to the was abandoned in favour of carrying out Management Study (Water Technology, array of mitigation options. The preferre for community input as the time of writi mitigation scheme will be considered by adoption.	the Numurkah Floodplain 2017) that has explored large ed options are to be presented ng this Strategy. A preferred
BCU3 ☑	Nathalia (UFMP) (VH)		The Nathalia Floodplain Management Pl Flood Mitigation Scheme Implemented (upgraded levee system was tested by th and included the flood warning prediction and used during 2012 flood.	Moira Shire, 2009-2012). The e highest flood of record (2012),
BCU4	Tungamah (UFMP) (H)		Not yet carried out. LiDAR has been con catchment to allow the study to proceed	
BCU5 ☑	Wunghnu (USS) (L)		No scoping study carried out. However, completed as part of the extended Num Study, which will adequate for scoping p	urkah Floodplain Management

Ref	Task		Status at 2	017
Abbreviatio Completed	ons	☑ = S	tudy/Plan Completed	🗹 = Study/Plan Mostly
USS = Urbar	n Scoping Study	UFMS	5 = Urban Floodplain Management Study	L = Low Priority
RSS = Rural	Scoping Study	RFMS	5 = Rural Floodplain Management Study	M = Medium Priority
UFS = Urbar	n Flood Study	UFMF	P = Urban Floodplain Management Plan	H = High Priority
RFS = Rural	Flood Study	RFMF	P = Rural Floodplain Management Plan	
BCR1	Pine Lodge, Daintons, Congupna and O'Keefe Creeks (RFS) (L)		This was considered a low priority, which	n indicates no further action.
BCR2-1	Nine Mile, Boosey, Mucl Creeks. – Stage 1 (RFS) (L-M)	katah	Not yet carried out.	
BCR2-2 (RFMS)	Nine Mile, Boosey, Mucl Creeks. – Stage 2 (L-M)	katah	Not yet carried out.	

Table E-26: 2002 Regional Strategy Delivery - Floodplain Work Delivery

Ref	Task	2017 Status			
Water Ma	Water Management Schemes – Urban Areas				
FPW1	Benalla	Waterway Management Scheme completed, which was largely about removal of selected vegetation. Continued operation and maintenance is carried out by Benalla Rural City Council. Total Flood Warning System implemented separately in the mid-2000s.			
FPW2	Euroa	Water Management Scheme completed which was largely about augmentation of Castle Creel and removal of selected vegetation along creek corridors. Continued operation and maintenance is carried out by Shire of Euroa. Total Flood Warning System implemented separately in the mid-2000s.			
FPW3	Shepparton	Shepparton Mooroopna Flood Warning and Emergency Management Project was delivered as the recommended scheme. Structural mitigation measures were dismissed following community consultation.			
FPWU	Implement works for future urban studies and FPM Plans	Additional work included: Cobram levee augmentation, Tatura railway culverts and floodway works, Nathalia levee augmentation and TFWS, and detailed design of levees for Seymour and Violet Town.			
Rural Area	as	·			
FPW4	Upgrade PWD (Murray River) levees	The Department funded repairs of known levee defects, based on the Levee Audit (Coffey, 1997), primary from Cobram to Koonoomoo. See Table E-25 .			
FPW5	Lower Goulburn Floodplain Rehabilitation Scheme	See Table E-25 for further background. No works are currently planned			
FPWR	Implement works from future rural studies and FPM plans	No works are currently planned.			

In conclusion, this program delivery has been successful because of strong stakeholder partnership and financial commitment by all levels of government.

Statutory Land Use Planning – Program 3

At the outset of the development of the 2002 regional Strategy, the statutory land-use planning program was considered one of the most important of all programs because of the need to ensure that land-use and development proposals do not unduly add to legacy flood problems.

At the time of the formations of CMAs across Victoria, the new format planning schemes were being prepared using the standard set of zones and overlay contained in the Victoria Planning Provisions. The 2002 regional Strategy was conscious to utilise the new tools that were specifically made available for floodplain management to management the "future" flood problem (not making things worse).

The tools in the Victoria Planning Provisions, for floodplain management have not (for the most part) changed since its introduction in the mid-1990s, and include using:

- Urban Floodway Zone (UFZ), (Rural) Floodway Overlay (RFO or FO), Land Subject to Inundation Overlay (LSIO) and Special Building Overlay (SBO).
- Schedules to the FO, LSIO, and SBO that specifically allow for exemptions for unnecessary planning permit referrals.
- Local Floodplain Development Plans that provides a performance-based risk management criteria for those most common types of applications.
- Local Planning Policy Framework to sign post local issues relevant to LGAs and other prepared incorporated documents such as the Local Floodplain Development Plans.

All LGAs have zone and overlay controls within their planning schemes. Five of the eight LGAs have included the full suite of zone and overlay controls, schedules, local floodplain development plans and local planning policy.

Table E-25 and Table E-28 present the status of this program. Note that updating planning controls is never static and should always incorporate the best available information. Considerable effort is required under this Strategy to carry out a significant number of planning schemes amendments.

Ref	Task	Status at 2017
SP1	Draft VPP amendments. Shires of Murrindindi & Mitchell only	Completed and include the full suite of VPPs tool for floodplain management.
SP2	Incorporate FDT maps into planning schemes	Completed for all LGAs except Benalla Rural City Council where maps need updating beyond the FDT (Flood Data Transfer Project from Victoria to Shires and CMAs).
SP3	Improved flood maps. These are only where required.	On-going following completion of flood mapping studies.
SP4	Incorporate improved flood maps into planning schemes	Many updates from Studies incorporated and many have not and subject to priorities for the 2017 regional Strategy.
SP5	Review performance of planning measures every 5 years. Audit a representative selection of statutory planning responses across all municipalities and check for consistency in conditions.	Standard set of conditions has been established in a GIS Planning Database Platform known as IPAWs, which all CMAs are using across the State. No audits have been carried out except on processes and time performance in the Goulburn Broken CMA internal Audit in 2013.

Ref	Task	Status at 2017
	Audit a smaller selection of developments across all municipality and test compliance of approved works against conditions of permit.	Never carried out by Goulburn Broken CMA. Some audits carried out by LGAs
SP6	Inform VicRoads, V-Line, Goulburn-Murray Water & Power Authorities of recommended referral and consultation arrangements when appropriate	This is achieved by the planning scheme requirements and deemed unnecessary.

Table E-28: 2002 Regional Strategy Delivery – Flood mapping

Task/(Priority)	2017 Status			
Murray Catchment				
Murray/Ovens River confluence near Bundalong	Completed as part of Murray River Mapping for MDBA.			
(Low Priority)				
Goulburn River tributaries between Eildon and Seymour (e.g. Rubicon River, Acheron River, Home Creek, Dabyminga Creek, Yea River, Murrindindi River, King Parrot Creek, Strath Creek) (Low Priority)	About 20% complete and some incorporated into planning scheme. Low priority given due to other higher priorities			
Goulburn River tributaries between Seymour and Shepparton (e.g. Major Creek, Sugarloaf Creek, Mollison Creek, Gardiner Creek, Hughes Creek, Castle Creek, Seven Creeks, Pranjip Creek, Honeysuckle Creek, Stony Creek)	The current Granite Creek Flood Mapping Project will address most of the named tributaries			
(Medium Priority)				
Toolamba/Stanhope area generally north of Waranga Basin covering the numerous drainage lines and depressions through this area (update of 1950 flood extent information required)	The Corop Lake Scoping Study (GHD, 2012) indicates that the overlay controls are sound following a review of capture 2010 LiDAR information. No further detailed modelling is not warranted for this Strategy.			
Cornella Creek, Wanalta Creek and Corop Lakes	The Corop Lake Scoping Study (GHD, 2012) indicates that the overlay controls are sound following a review of capture 2010 LiDAR information. No further detailed modelling is not warranted for this Strategy.			
Broken River Catchment				
Broken River and Holland Creek upstream of Benalla (cleared areas only)	Flood Data Transfer Flood Mapping available but considered poor. LiDAR will assist in improving flood planning.			
Baddaginnie Creek	Currently part of the Granite Creeks Flood Mapping Project			
Broken River effluents between Benalla and Lake Mokoan and Stockyard Creek.	Preliminary work completed.			
Broken Creek Catchment				

Task/(Priority)	2017 Status
Upper reaches of Broken and Boosey Creeks, including effluent flow paths from Broken River between Broken Creek and Nalinga, and also near the Dookie Hills	This work has not been addressed. The first task is to study the hydrology and model the nature of flooding along the Broken River and its effluents into the Broken Creek catchment. This work in eminent and part of the Goulburn and Broken Flood Mapping Project. The upper reaches of the Boosey and Broken then be ready to be investigated as part of the Upper Broken Study Flood Mapping Study into the future. This is required as there are little overlay controls
Muckatah Depression and nearby depressions and areas of low lying land	Overlay exist in the planning scheme. However, improved understanding is required
Natural depressions between Broken Creek and the Murray River, north of Numurkah and Nathalia, including Drain 13 area near Nathalia	Need to include significant drainage line mapping into planning scheme as Floodway Overlay (FO) controls.
Broken Creek, downstream of Nathalia.	

Development Assessment Guidelines – Program 4

The guidelines are intended to link with Program 3 – Statutory Planning. The aim is to ensure that land-use and development assessments are consistent.

The major achievement is the incorporation of Local Planning Policy, Local Floodplain Development Plans and schedules to the flood provision in five of the eight planning schemes within the Goulburn Broken CMA, which form the bulk of the decision guidelines. It of note that incorporating decision guidelines into planning scheme provides transparency for all stakeholders.

The 2013 Internal Audit (Partners, 2013) recommended that the decision guidelines and processes be formally structured into the Goulburn Broken CMA Policy and Procedures to ensure all staff are aware of how to make decisions.

A review of the 2002 regional Strategy indicates that the guidelines align with the:

- State Planning Policy Framework
- Local Floodplain Development Plans
- Planning Practice Note 11 (Department of Environment, Land, Water and Planning, 2015)
- Urban Floodway Zone (Clause 37.03)
- Floodway Overlay (Clause 44.03)
- Land Subject to Inundation (Clause 44.04)
- Goulburn Broken CMA Policies and Procedures

Currently, Department of Environment, Land, Water and Planning are coordinating Development Guidelines on Flood Prone Land in conjunction with all CMAs and Melbourne Water.

Control of Works and Activities – Program 5

This program looked at seven possible ways to managed works and activities and seeks to identify and document procedures, particularly under the Victoria Planning Provisions (planning schemes),

Water Act declarations and By-laws. The latter is limited to the confines of waterways rather than floodplain areas. Declarations could however be applied to floodplain areas.

No action has been carried out for this program in this matter in preference of the planning controls in planning schemes.

The Goulburn Broken CMA has provided significant resources to support LGAs resolve "illegal" works. There are however, no formal documented arrangements in place.

Further discussion around this program is provided in the Strategy in Section 4.6.

Emergency Response Planning – Program 6

A large portion of this program has been delivered by LGAs and VICSES with support from the Goulburn Broken CMA.

This program is heavily reliant on the availability of good flood data. Many flood studies include components where emergency and flood warning considerations are examined.

 Table E-29 provides a description of completed tasks that mostly been advanced.

The proposed elements of the TFWS for each basin and priorities are discussed in **Section 2.4**. Only two Charters (which were agreements on how flood warning arrangements were to be delivered) exist - for Nathalia and Shepparton. There has been a significant number of flood warning prediction services implemented however, namely:

- Benalla (Benalla Rural City Council);
- Euroa (Strathbogie Shire);
- Seymour (and mid Goulburn Mitchell and Murrindindi Shires);
- Shepparton Mooroopna (Greater Shepparton);
- Lower Goulburn Loch Garry Scheme (Goulburn Murray Water);
- Nathalia (Moira Shire);
- Numurkah (in development); and
- NSW provide forecasts for the Murray River at the Yarrawonga and Tocumwal gauges.

Service Level Specification for Flood Forecasting and Warning Services for Victoria are documented by the BoM (Bureau of Meteorology, 2013)

	Task/(Priority)	2017 Status			
Ide	Identify Flood Warning System Needs.				
•	Develop flood warning service charter (for each Basin with LGAs and VICSES)	Not attempted. Currently, VICSES implementing catchment footprint EMCOP warning distribution.			
•	Establish prioritised program based on needs	This has been considered in Program 2: Flood Studies and Floodplain Management Plans			
•	Advise BoM of requirements	This has been carried out as part of study recommendations			
•	Review & update service charter as required	Not attempted			

Table E-29: 2002 Regional Strategy Delivery – Emergency response planning

Task/(Priority) 2017 Status				
Identify funding opportunities				
Data Network Management				
Developed Policy for CMA involvement in flood network management	This is done through the establishment of the Northern Regional Water Monitoring Partnership. The CMA has some role in water quality monitoring			
• Facilitate the development and implementation of a regional monitoring partnership (in consultation with NRE).	This is done through the establishment of the Northern Regional Water Monitoring Partnership, which is coordinated by the Department of Environment, Land, Water and Planning.			
Empower Community.				
Explore opportunities for public dissemination of BoM "Flood Advice" warning/information	This has been delivered through EMCOP where it value adds to BoM's flood warnings			
Develop Community Flood Response Guides (Consultancy)	Four flood guides were prepared as part of TFWs for Seymour, Shepparton, Benalla and Euroa prior to the FloodSafe initiative led by VICSES. A list of 15 guides are shown in Appendix D : Summary of Flood Studies, Plans, Work Plans			
Help raise and maintain community awareness by contributing to media articles, preparing brochures, speaking to community groups, etc.	The initiate in led by VICSES with support from LGAs and CMA. Note improved websites now available.			
Review and document actions undertaken by municipalities with improved flood warning systems to ensure all elements of the flood warning system are ready for future flood events.	This initiative is carried out by LGAs with review by VICSES and CMAs. The new Municipal Flood Emergency Plan standard template has most been applied across Victoria, which has led to greater ease of use.			
Resolve Anomalies in Roles and Responsibilities.				
Work with G-M Water and BoM to resolve anomalies in existing roles and responsibilities for flood forecasting and warning activities.	Completed. This service is now solely carried out by BoM.			

Flood Monitoring Action – Program 7

The implementation of this program has been significantly advanced. Five initiatives were completed, namely:

- State-wide Flood Response Action Plan template (Coordinated by Goulburn Broken CMA);
- Data needs for each of the four catchments in the Goulburn Broken region;
- Goulburn Broken CMA Flood Response Plan;
- Policy and Practice Procedures (internal); and
- GIS Platform

The GIS platform is a consolidation of the first three bullet points above, which provides rapid access to the actions that the Goulburn Broken CMA is required to perform in terms of flood data capture including: peak flood levels, aerial flood photography, and hydrographic flow measurements. At the same time, the Goulburn Broken CMA performs its role in the Intelligence Cell at the Incident Control Centres, assist VICSES in managing potential flood consequences.

A State-wide initiative known as FloodZoom, which is a web based platform of key flood intelligence products has been advanced over the past five years by DELWP in conjunction with CMAs and VICSES. This platform provides flood intelligence that is accessible by emergency management personnel.

The Goulburn Broken CMA role during recent major floods has been tested during 2010, 2011, 2012 and 2016. Debrief sessions have been carried out to improve procedures following each flood, particularly the Goulburn Broken CMA Internal Policy and Practice Procedures.

The Goulburn Broken CMA seeks to test its action plan and/or attend state-wide or regional incident control centre exercises coordinated by DELWP/VICSES since the recent floods, and in most part worked effectively.

The Strategy seeks to re-evaluate the data needs for flood data capture. Review of the performance of levee systems also needs to be addressed.

Information Management Systems – Program 8

This program is focused on the Goulburn Broken CMA internal processes that were of utmost priority to ensure effective and efficient functioning of the statutory planning and floodplain management program.

The Goulburn Broken CMA Information Communication Technology (ICT) team has provided significant support in addressing the requirements of this program. The IPAWS (Integrated Planning and Works System for statutory referrals, advices and permits) system and the Flood Response Action Plan GIS Platforms have been significantly affective in this program where significant resources have been employed. The Goulburn Broken CMA in fact led to the development of the Platform and its delivery to all CMAs.

Other activities include file management of both plans and documents (linkages via GIS), remote applications (to enable to use the CMA's corporate computer platforms away from the office), hydrology and hydraulic software, and a floodplain library.

This program included the future needs for flood data that is mostly covered in the flood action plan, but should be reviewed and joined to Program 7.

This program has been successfully implemented. However, ICT seeks to remain current and requires ongoing management.

Education, Promotion and Communication – Program 9

This program suggests a range of training programs, which are ongoing and mostly well attended. Professional development of staff has also been coordinated by the Goulburn Broken CMA's Human Resources Team including conflict management, taking evidence, interview techniques, etc.

The program set out community workshops to be carried out twice a year to raise flood awareness, which has been led by VICSES through the FloodSafe program.

Appendix F: Service levels – structural flood mitigation works

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
	Benalla Rural City Council	
Baddaginnie	None identified and not required	•
Benalla	 Description The Approved Water Management Scheme (2003) was implemented (circa 2006-08) comprising vegetation thinning (largely exotics) and management. The works extends from through the City. Also, TFFS in place. Management Authority Benalla Rural City Council maintains the Scheme and contributes to the maintenance of the rain and stream gauge network for the TFWS 	No other flood infrastructure proposed. Review should be carried out following the next major flood greater than 2% AEP flood. Banks associated with the old Mokoan Channel should be reviewed if they provide a service in protecting parts of Benalla – refer to Table F-32 at the end of this Appendix.
Devenish	None identified and not required	•
Lima South	None identified and not required	•
Glenrowan (Rural City of Wangaratta)	None identified and not required	•
Swanpool	None identified and not required	
Tatong	None identified and not required	
Thoona	None identified and not required	•
	Campaspe Shire	
Colbinabbin	None identified and not required	•
Girgarre	None identified and not required	•
Kyabram	 Description A pumping scheme and a retention basins have been implementation to reduce stormwater flooding. This is detailed in a report prepared by GHD (1995). Management Authority Shire of Campaspe 	•
Rushworth	 Description Northern, southern and western catchment stormwater plans were implemented in 2014 to reduce exposure of overland stormwater inundation. Management Authority Shire of Campaspe 	•

Table F-30: Service levels (urban centres) – Structure flood mitigation works

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Stanhope	 Description Stanhope drainage scheme implemented in the mid- 1970s to reduce exposure of overland stormwater inundation. 	•
	Management Authority Shire of Campaspe	
Tongala	 Description A drainage scheme, including retardation basins was implemented in the mid-1980s 2014 to reduce exposure of overland stormwater inundation. 	• -
	Management Authority	
	Shire of Campaspe	•
Wyuna	None identified and not required	•
	Greater Bendigo City Council	1
Costerfield	None identified and not required	• -
Costerfield South	None identified and not required	• -
Heathcote East (Rural Living)	None identified and not required	• -
Heathcote North (Rural Living)	None identified and not required	• -
Mount Camel	None identified and not required	• -
Redcastle	None identified and not required	• -
	Greater Shepparton City Council	·
Bunbartha	 Description The unmanaged rural levees, which forms part of the lower Goulburn levee system protects Bunbartha from flooding up to 2% AEP type flood. However, this cannot be relied upon as there are no operation of maintenance arrangements in place. 	 There is no proposal to have the lower Goulburn levees managed into the future.
	Management Authority Nil	
Cooma	None identified and not required	• -
East Murchison	None identified and not required	• -
East Shepparton	None identified and not required. However, overland stormwater flooding may be further scoped as part of Greater Shepparton drainage review, which is currently underway.	 Possible local drainage solutions
Katandra West	None identified and not required until a scoping stormwater study is carried out.	• -
Kialla West	None identified and not required	• -
Merrigum	None identified and not required	• -

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Murchison	 Description North of the Murchison-Bendigo Bridge crossing a levee has been constructed along the eastern bank of the Goulburn River, which is approximately onemetre in height This levee in some 200 metres in length and is thought to have been constructed following the 1916 flood where floodwaters entered into the town impacted on retail and residential areas. Management Authority Nil Levee condition and level of protection Despite no formal management arrangement, the levee in visually in very good condition and well grassed and mowed. Based on the Murchison Flood Study (WT, 2014) the height of the levee (determined from new survey information) is more than 610 mm above the 1% AEP flood level. 	 The levee and associated infrastructure (i.e. penstocks or values if they exist) need to be formally maintained in the future by Greater Shepparton City Council. A levee audit would provide information on the quality of the levee. Consideration to construct a permanent short levee upstream of town to prevent backdoor flooding should be given rather than the option of relying on sandbagging efforts – refer to the Murchison Flood Mapping Study (WT, 2014).
Shepparton/ Mooroopna (Part 1 of 4)	 PRINCESS PARK LEVEE (Shepparton) Description Approximately 1100 metres in length and around 2-3 metres in height. This levee protects two sporting ovals, club rooms and recreation buildings. Management Authority Nil Levee condition and level of protection Despite no formal management arrangements, the levee is visually in very good condition and well grassed with its crest sealed forming part of the bicycle path network. The crest and levee batters meet contemporary standards. The levee will begin to overtop at a peaked of 11.66 metres on the Shepparton gauge. Without freeboard, the level of protection is 5 cm below the 1993 flood, or level of protection of around 4% AEP (25-year ARI). Note the 1993 flood photograph take 0.01 m of the peak show little inundation. Assuming that 600 millimetre freeboard is required to determine the level of service, then it reduces to equivalent to the September 2010 flood or 14% AEP (7-year ARI) type flood. 	 A decision will need to be made if the benefits of the levee outweigh the long-term maintenance cost, particularly given the low level of protection provided. Greater Shepparton could commission an economic evaluation of the levee prior to deciding on taking on any formal management arrangements Refer to Murchison for further actions if management is likely to proceed.

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Shepparton/ Mooroopna (Part 2 of 4)	 MACGUIRE RESERVE (Shepparton) Levee Description Approximately 900 metres in length and around 2-3 metres in height this levee protects Shepparton's Lawn Tennis Courts, and open Crown land partly used for car parking. 	 A decision will need to be made if the benefits of the levee outweigh the t long- term maintenance cost, particularly given the low level of protection provided.
	 Management Authority Nil Despite no formal management arrangements, the levee is visually in fair good condition and grassed with its crest sealed forming part of the bicycle path network. The levee batters are relatively steep compared with contemporary standards. During the September 2010 flood, the levee marginally overtopped (stopped by sandbagging) and floodwater piped through the levee flooding parts of the tennis courts near Goulburn Valley Water's treatment plant. The levee will begin to overtop south of Daintons Bridge at 10.98 metres on the Shepparton Gauge. Without freeboard, the level of protection is around 17% AEP (or 6-year ARI). Assuming that 600 millimetre freeboard is required to determine the level of service, then it reduces 10.4 metres on the Shepparton Gauge that equates to around the 25% AEP (<4-year ARI) type flood.	 Greater Shepparton could commission an economic evaluation of the levee prior to deciding on taking on any formal management arrangements Refer to Murchison for further actions if management is likely to proceed.
Shepparton/ Mooroopna (Part 3 of 4)	 Balmoral Estate Levee (Kialla) Description Approximately 300 metres in length and around 300 millimetres in height this levee protects a number of rear backyards (west and of Furphy Avenue) from nuisance flooding. The floor levels are well above the height of the levee. 	 Given that the level of service protects several rear yards, there is no merit in formally maintaining this level. In fact, Greater Shepparton should limit any further modification to the levee in terms of its height and length.
	 Management Authority Nil Levee condition and level of protection Visually, the levee is low and narrow and of ad hoc construction. During the September 2010 flood (11.09 metres on the Shepparton Gauge), the levee was eminent of overtopping. The levee will begin to overtop at 11.10 metres on the Shepparton Gauge. Without freeboard, the level of protection is around 17% AEP (or 6-year ARI). Assuming that 600 millimetre freeboard is required to determine the level of service, then it reduces 10.4 metres on the Shepparton Gauge that equates to around the 25% AEP (<4-year ARI) type flood. 	

Name	Existing Flood Mitigation Infrastructure (levees)	Pro	posed Flood Mitigation Infrastructure (Levees)
Shepparton/ Mooroopna (Part 4 of 4)	 VICTORIA PARK LEVEE (Shepparton) Description Approximately 430 metres in length and around 600-800 millimetres in height this levee protects camping grounds associated with Victoria Lake Caravan Park. Management Authority Nil Levee condition and level of protection Visually, the levee is in poor to fair condition with varying crest widths and varying levee batters, and partially grassed with the presence of some trees. During the September 2010 flood, the levee marginally overtopped (stopped by sandbagging) and floodwater piped through the levee flooding parts of the tennis courts near Goulburn Valley Water's treatment plant. The levee will begin to overtop at 11.18 metres on the Shepparton Gauge. The September 2010 flood photography indicates that the camping grounds were protected. Without freeboard, the level of protection is around 14% AEP (or 7-year ARI). Assuming that 600 millimetre freeboard is required to determine the level of service, then it reduces 10.58 metres on the Shepparton for the reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it reduces 10.58 metres on the level of service, then it	•	The levee only provides protection from nuisance type flooding. The camping ground should rely on evacuation procedures as part of the Park's operation. Refer to Murchison for further actions if management is likely to proceed.
(East, North and Orrvale) Shepparton	Shepparton Gauge that equates to around 25% AEP (<4-year ARI) type flood. <u>Non-backbone Irrigation Removal along Wanganui Road</u> <u>Shepparton North, Shepparton East and Orrvale</u>	•	Greater Shepparton City Council will need to ensure that flooding is not transferred to the urban areas Greater Shepparton City Council to consider bringing the channels into a Water Management Scheme – refer to detailed Table F-32 at the end of Appendix
Tallygaroopn a	None identified	•	Mitigation measures could be explored as part of the floodplain management plan for Tallygaroopna as large parts are significantly impacted by flooding
Tatura	None identified and not required	•	-
Toolamba	None identified and not required	•	-
	Mansfield Shire Council		
Bonnie Doon	None identified and not required	•	-
Gaffney's Creek (A1 Mine Settlement)	None identified and not required	•	-

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Howqua	None identified and not required	• -
Jamieson	None identified and not required	• -
Maindample	None identified. Local drainage issues identified in the west of the township.	Shire to investigate drainage solutions
Mansfield	None identified and not required	• -
Merrijig	None identified and not required	• -
Merton	None identified and not required	• -
Woods Point	None identified and not required	• -
	Mitchell Shire Council	1
Broadford	None identified and not required	•
Kilmore	None identified. Overland stormwater management options are currently being explored by Council	 Stormwater management implementation proposed by Council
Kilmore East	None identified and not required	• -
Pyalong	None identified and not required	• -
Reedy Creek	None identified and not required	• -
Seymour	None identified and town levee scheme is in detailed design phase	Town Levee to protect against riverine flooding from Goulburn River and Sunday and Whiteheads Creek catchments.
Tallarook	None identified and not required	• -
Tyaak	None identified and not required	• -
Whiteheads Creek	None identified and not required	• -
	Moira Shire Council	
Barmah	 Barmah Town Levees Description The commencement of inundation by floodwater occurs around the low-lying outskirts of the town at around 96.0 metres AHD. Which is around the 50% AEP (or 5-year ARI) type flood. A system of levees (combined with the connecting roads) in the Barmah township has been constructed over the years, which appears to be carried out of on a needs basis privately. The standard of construction varies. Despite the town levees, the threat from flooding when river levels rise is still about the 96.0 metre AHD level or higher. The particularly levee heights are discussed below. Barmah Forest levee to Corry Street (north of Town) The Barmah Forest levee extends some 39 kilometres to the north to Piree Creek. The levee elevation north of Barmah Township is generally around 96.6 metres AHD. 	 The existing ad hoc levees, with the interconnecting road network does provide some benefit against low level flooding. The current ad hoc levees are not owned or managed by Moira Shire Council, and unlikely to be managed into the future.

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
	 Approximately 330 metres in length and around 800 millimetres in height, this levee runs along the northern side of Corry Street at the general elevation of around 97.0 metres AHD from Barmah Bridge Road. 	
	 Shier to Evans Street Levee (Barmah Caravan Park) Approximately 480 metres in length and around 600 millimetres in height this levee, which is runs through the Barmah Caravan Park, is at the general elevation of around 96.2 metres AHD. 	
	 Evans Street Levee Approximately 380 metres in length and around 500 millimetres in height, this levee, which is runs behind seven residential properties adjacent to the Murray River, is at a general elevation of around 96.5 metres AHD. 	
	 Murray Street The Murray Street itself acts as a levee at a general effective elevation of 96.7 metres AHD, which connects the Evans Street levee with the Riverview Drive Levee. 	
	 <i>Riverview Drive Levee</i> Approximately 600 metres in length and around 400-600 millimetres in height, this levee, which is runs from Murray Street to Swan Court, behind 18 properties adjacent to the Murray River, is at a general elevation of around 96.6 metres AHD. 	
	Management Authority	
	• Nil	
	 Levee condition and level of protection Visually, the levees are in poor condition with narrow crest widths with steep batters. The Caravan Park is at the most venerable to flooding. Leaving the Caravan Park levee aside, without freeboard, the level of protection for the town is around 3% AEP (or 30-year ARI) or 96.6 metres AHD. Assuming that 600 millimetre freeboard is required to determine the level of service, then it reduces 96.0 metres AHD that equates to around 20% AEP (5-year ARI) type flood. 	
Bearii	None identified and not required	• -
Cobram	1% AEP Approved Water Management Scheme (Water Act 1989) implemented. Further augmentation now identified as determined by the Regional Murray Flood Study (Water Technology, 2011)	 Moira Shire currently investigation augmentation options.
Katamatite	None identified and not required	•
Koonoomoo	None identified and not required	•
Lake Rowan	None identified and not required	•
Marungi	None identified and not required	•

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Nathalia	The 1978 Flood Study (SR&WSC) recommendations of some eight kilometres were completed in the mid-1980s and were tested during the 1993 flood where overtopping was documented. Since then, the Nathalia Floodplain Management Plan (SMEC, 2005) was completed leading to the augmentation levee works, temporary demountable barriers, completed in 2011. These proved successful during the highest flood in record in March 2012.). Aither (2014) economic review indicates that the damage avoided was in the order of \$35 million.	On-going maintenance and renewal work have been carried out since 2012 and will continue by Moira Shire Council
Numurkah	Following the 1974 and 1993 floods, as series of low level levees were put in place, typical 300-450 millimetres in height to protect floodwater entering the northern portion of the town and several residential homes and a Numurkah Caravan Park to the west of Melville Street. These were overwhelmed during the 2012 flood, which was the flood of record. The AAD is some \$730,000 pa.	 The Numurkah Floodplain Management Study and Plan has been investigating a range of flood mitigation options, which is nearing completion for the community consideration. Refer to Table F-32 at the end of this Appendix highlights irrigation channel along Kinnairds Road that would ultimately need to be part of the final scheme to be managed by Moira Shire Council.
St James	None identified and not required	•
Strathmerton	None identified	 Table F-32 at the end of this Appendix highlights irrigation channels south-east of the Town may provide urban flood protection. If decommissioned, Moira Shire Council should consider that these levees form part of a Water Management Scheme (or similar).
Tungamah	None identified. There is a community desire to look at options for mitigation	There is a need to determine mitigation needs through a Floodplain Management Plan
Waaia	None identified and not required	• -
Wilby	None identified and not required	• -
Wunghnu	None identified and not required	• -
Yarrawonga	None identified and not required	There are stormwater management investigation and implementation option currently being carried out by Moira Shire Council
	Murrindindi Shire Council	
Alexandra	None identified. Unknown if mitigation is required or effective. Suspect a low priority to determine if any mitigation is warranted.	Low priority

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Buxton	None identified. Unknown if mitigation is required or effective. Suspect a medium priority to determine if any mitigation is warranted given the significant number of floods since 1990s.	Medium priority
Eildon	None identified and not required	• -
Kinglake Central	None identified and not required	• -
Kinglake East	None identified and not required	• -
Marysville	None identified and not required	• -
Molesworth	Molesworth Caravan Park levee is privately managed. This levee in located adjacent to the Goulburn River and some 600 millimetres in height.	• -
Narbethong	None identified and not required	•
Pheasant Creek & King Lake West	None identified and not required	•
Strath Creek	None identified and not required	•
Taggerty	None identified and not required	•
Thornton	None identified and not required	•
Toolangi	None identified and not required	•
Yea	None identified and not required	•
	Strathbogie Shire Council	
Avenel	None identified and not required	•
Euroa	The existing Castel Creek is being augmented, upgraded and extended to the 1% AEP (100-year ARI) standard, as part of a Ministerial Approved Water Management Scheme	Ongoing maintenance, renewal work and vegetation and sediment management will be undertaken by Strathbogie Shire council.
Graytown	None identified and not required	•
Locksley	None identified and not required	•
Longwood	None identified and not required	•
Mangalore	None identified and not required	•
Nagambie	1. The existing Industrial Estate is inundated by floodwater from the Tabilk Depression above the 5% AEP (20-year ARI) event.	1. Pumping of the floodwater to the former VicRoads borrow pit is proposed.
	2. A rural levee located on the former Nagambie- Heathcote road reserve, together with a disused approach ramp to the Western side of the Old Chinamans Bridge, are restricting flood flows and raising flood risk at the Nagambie Regatta Centre and Chinamans Bridge Caravan Park.	2. Removal of the levee and the Western part of the approach ramp, both located within Municipal Road, is proposed.
Old Longwood	None identified and not required	•
Ruffy	None identified and not required	•
Strathbogie	None identified and not required	•

Name	Existing Flood Mitigation Infrastructure (levees)	Proposed Flood Mitigation Infrastructure (Levees)
Violet Town	 A rural drain, acting to divert floodwater away from an elevated section of the Old Hume Highway at Violet Town has been overtopped by flash flooding. There is a community desire to implement the proposed Violet Town Floodplain Management Scheme which proposes a new flood levee to reduce above floor flooding in a 1% AEP (100-year ARI) type event from 63 to 17 properties. 	 Upgrading and management of the Murray Street rural drain, together with localised bunding or floor raising of houses, needs to be considered. Council intends to proceed with the establishment of a Water Management Scheme under the <i>Water Act (1989),</i> when workable improvements are made by the State Government in relation to Councils legal liability under the Act.

Table F-31: Regional (rural) Service levels – Structure flood mitigation works

Name	Existing Flood Mitigation (Levees)	Proposed Flood Mitigation Infrastructure (Levees)		
	Broken Creek Catchment			
Broken Effluent Tributaries	t			
Lower Broken Creek	Miscellaneous private levees along Nine Mile and Broken Creeks downstream of Walshs Bridge Road, which have been surveyed as part of the Nathalia Floodplain Management Plan (SMEC, 2005). No formal management arrangements and quality is unknown. The height of the levee around the 1993 flood height (~5% AEP flood or 20-year ARI)			
Mid Broken Creek	Miscellaneous private levees along Nine Mile and Broken Creeks downstream of Katamatite. No formal management arrangements and quality is unknown. The height of the levee around the 1993 flood height (~5% AEP flood or 20-year ARI)	Nil		
Muckatah Depression	Some miscellaneous private levees exist along this system, extending from Dowdles Swamp to Numurkah. No information exists to their quality and level of service.	Nil		
Upper Broken Miscellaneous private levees exist along several Creek locations of the Broken and Boosey Creeks. No formal management arrangements and quality is unknown. The height of the levee are generally 300-600 millimetres in height.		Nil		
	Broken River Basin			
Lower Broken River	None identified and not required			
Upper Broken River	None identified and not required			
	Goulburn Basin	1		

Existing Flood Mitigation (Levees)	Proposed Flood Mitigation Infrastructure (Levees)		
None identified	Nil		
Miscellaneous private levees exist throughout the area. No formal management arrangements and quality is unknown. The height of the levees are generally 450 – 1,000 millimetres in height.	Nil		
None identified and not required			
A large private levees identified.	nil		
None identified and not required			
None identified and not required			
Some miscellaneous private levees is suspected identified by the Granite Creeks Regional Flood Mapping Study.	Nil		
None identified and not required			
Collectively some 170 kilometres of levees exists that flanks both sides of the Goulburn River from Bunbartha to the Murray River, and along the Deep Creek system, Wells Creek and Kanyapella Basin.	Nil unless opportunities arise to integrate environmental outcomes, such as the rehabilitation scheme (or similar)		
None identified and not required			
None identified and not required	、		
Miscellaneous private levees exist throughout the area. Some survey locations are shown on the 1936 River Survey Plan (Molesworth to Eildon). No formal management arrangements and quality is unknown.			
None identified and not required			
None identified and not required			
None identified and not required			
None identified and not required			
None identified and not required			
Murray Riverina			
 Description Uncoordinated construction of levees by private land owners commenced as early as 1870 but coordinated construction began in 1895 by the Public Works Department (PWD) from Cobram to Piree Creek (near Picola). Levees continue from Piree Creek to Barmah by uncoordinated construction. Management Authority Nil 	Landowners may carry out routine maintenance works under a permit process coordinated by Goulburn Broken CMA where levees are located on Crown land. Permits for levee maintenance on private land are subject to the provision of the planning scheme.		
	Miscellaneous private levees exist throughout the area. No formal management arrangements and quality is unknown. The height of the levees are generally 450 – 1,000 millimetres in height. None identified and not required A large private levees identified. None identified and not required None identified and not required Some miscellaneous private levees is suspected identified by the Granite Creeks Regional Flood Mapping Study. None identified and not required Collectively some 170 kilometres of levees exists that flanks both sides of the Goulburn River from Bunbartha to the Murray River, and along the Deep Creek system, Wells Creek and Kanyapella Basin. None identified and not required Miscellaneous private levees exist throughout the area. Some survey locations are shown on the 1936 River Survey Plan (Molesworth to Eildon). No formal management arrangements and quality is unknown. None identified and not required None identified and not required Description • Uncoordinated construction of levees by private land owners commenced as early as 1870 but coordinated construction began in 1895 by the Public Works Department (PWD) from Cobram to Piree Creek (near Picola). Levees continue from Piree Creek to Barmah by uncoordinated construction.		

Name	Existing Flood Mitigation (Levees)	Proposed Flood Mitigation Infrastructure (Levees)
	• Variable condition and largely poor. The level of service is less than 20% AEP (20-year ARI), particularly accounting for a 600 millimetre freeboard. In the 2016 freeboard, in places, was zero.	
Murray River Echuca Village to Echuca	 Description History of the levee construction is unknown. Management Authority Nil Levee condition and level of protection Variable condition unknown. The level of service is some 33% AEP (30-year ARI), particularly accounting for a 600 millimetre freeboard. 	

Where possible flooding impact to urban areas from non-backbone irrigation removal has been identified, LGAs will review whether such irrigation channels should be managed under a Water Management Scheme (or similar) – refer to **Table F-32**.

Table F-32: Possible flood impact to urban areas from irrigation channel removal

Name	Urban Impact from Channel Removal
	Benalla Rural City Council
Benalla	Yes. CH014612 & CH014611 near parallel to Price Rd, CH014610 parallel to Morey Rd, CH014609 & CH014608 crossing Kilfeera Rd.
	Campaspe Shire Council
	Greater Bendigo City Council
	-
	Greater Shepparton City Council
Shepparton East	Yes, CH002406, CH002405, CH008700, CH008699, CH0017290, CH0017291, CH0017292, CH008701, CH0017289, along Channel Road area.
Shepparton/ Mooroopna	Yes, CH015154, CH001663 and CH001666 near Wanganui Rd
Orrvale	Yes, CH002423 near Midland Hwy, CH001594 & CH014537 meet at the corner of Central Av and Poplar Av, CH008702 near Channel Rd, CH008686 parallel to Prentice Rd, CH008688 & CH008689 near Prentice Rd, CH014227, CH014226 & CH008685 meet near Orrvale Rd, CH008680 & CH014225 near Prentice Rd, CH017289 near Doyles Rd.
	Mansfield Shire Council
	-
	Mansfield Shire Council
	•
	Moira Shire Council
Numurkah	Yes, CH005353 parallel to Kinnairds Rd, CH014530 crossing Kinnairds Rd
Yarroweyah	Yes, CH009937 crossing Singapore Rd, CH009938 crossing Kokoda Rd
	Murrindindi Shire Council
	- Strathbogie Shire Council
	•

Appendix G: Service levels – Land-use planning

Terminology

DSL:	Desirable Service Level	L:	Low
FDTP:	Flood Data Transfer Project (SKM, 1999	M :	Medium
LFDP	Local Floodplain Development Plan (incorporated doc)	H:	High
LUP:	Land Use Planning	UFZ:	Urban Floodway Zone
-	No further action	FO:	Floodway Overlay
		LSIO:	Land Subject to Inundation Overlay

The following Table provides a guide (tool) to assign existing and desirable Service Levels for LGAs planning schemes in relation to floodplain management.

Service Level	Descriptor	Flood Information	Guiding Policy	Flood Zone and Overlays	LFDP
				(and schedules)	
0 (Low)	Little to no development or future growth potential, e.g. Crown land, land with low- intensity rural uses and broad-acre cropping, livestock farming.	No mapping is available. Some anecdotal evidence available.	Unlikely to be addressed in MSS. Unlikely to have a local policy on flooding	Nil	No
1	Some development potential, but not	Flood extents available from past	May be addressed in MSS. May	LSIO (base-level schedule).	No
(Low-medium)	designated for growth.	flood events. Some anecdotal evidence available.	have local policy on flooding.	Potentially UFZ.	
	E.g.: rural land, land abutting townships.				
2 (Medium)	Designated for high-intensity rural uses and low levels of urban development and growth. Typical areas: Small towns, peri- urban areas and lifestyle farms.	Flood extents available from past flood events. Some anecdotal evidence available. Rudimentary, low accuracy flood mapping, often based on historic floods, or non- calibrated 1D modelling.	Addressed in MSS at a minimum. May have a local policy on flooding. May have a LFDP (depending on expected level of development in flood prone areas).	LSIO and FO (base-level schedules). Potentially UFZ.	Maybe
3 (Medium-high)	Designated for modest levels of low- density urban development, growth and possible urban expansion (large towns).	Flood extents available from past flood events, or calibrated 1D or 2D flood modelling.	Addressed in MSS. Likely to have a local policy on flooding. Usually includes a LFDP.	LSIO, FO and SBO (detailed locally specific schedules).	Maybe
4 (High)	Designated for high-density urban development, high growth and urban expansion (major regional centres).	Calibrated 2D flood modelling.	Addressed in MSS. Includes a local policy on flooding. A LFDP exists to guide applications and decisions.	LSIO, FO and SBO (detailed locally specific schedules).	Maybe

The following Tables provide an assessment and actions to address Service Level scores to improve planning schemes in terms of land-use planning relating to floodplain management for urban centres (for each LGA) and regional (rural) area. Also, an overall LGA-wide assessment is included against the tools available in planning schemes.

Benalla Rural City Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Clause 21.02-1, 21.04- 1 21.05-1, and 21.08 provides good coverage of floodplain management matters	Nil	Agreement in place until Schedules are incorporated into planning scheme	Poor coverage in current planning Scheme	Very High

Specific locations (urban centres)

Location	Land Use	Existing Planning Scheme Information				
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level	
Baddaginnie	2	Nil	Parts of the town are known to be subject to flooding as documented in the FDTP. Introduce flood overlay controls using following completion of the Granite Creek Regional Flood Mapping Study.	Nil	0	
Benalla	4	UFZ, LSIO	Mapping based on 1993 flood information and early flood study by Willing and Partners in 1994. Benalla is subject to widespread flooding during large floods and continues to grow.	Nil	3	
Devenish	2	Nil	Evidence of flooding from recorded peak flood levels	Nil	0	
Swanpool	-	Not Required	Town is located on a high terrace some three metres above the Broken River floodplain.	-	-	
Tatong	1	Nil	Bulk of the Town is elevation. The eastern portion of the Town is however suspected to be liable to flooding from the Holland Creek.	Nil	0	
Thoona	1	Nil	Bulk of the Town is elevation above the Boosey Creek floodplain. The southern end of Town maybe subject to flooding	Nil	0	
Winton	1	Nil	The Town has landlocked area and subject to flooding from Winton and Seven Mile Creeks	Nil	0	

	Benalla Rural City Council
Baddaginnie	LUP DSL = 2; Service Level = 0 As part of LGA-wide amendment adopt the FDTP flood mapping and check mapping from the Granite Creek Regional Flood Mapping Study. This lifts the service level above 2.
Benalla	LUP DSL = 4; Service Level = 3 As part of LGA-wide amendment, the Goulburn Broken CMA, in conjunction with Benalla Rural City Council, will prepare UFZ, FO and LSIO mapping based on the reference 1993 flood together to Cardno modelling work of 2009. This lifts the service level to 4.
Devenish	LUP DSL = 2; Service Level = 0 As part of LGA-wide amendment, the Goulburn Broken CMA, in conjunction with Benalla Rural City Council, will prepare rudimentary mapping based on 2017 LiDAR and historic flood information. In the longer term, utilise mapping if and when the Upper Broken Creek Regional Flood Study becomes available. This lifts the service level to 2.
Tatong	LUP DSL = 1; Service Level = 0 As part of LGA-wide amendment adopt the FDTP flood mapping and check against available LiDAR. This lifts the service level above 2.
Thoona	LUP DSL = 1; Service Level = 0 As part of LGA-wide amendment, the Goulburn Broken CMA, in conjunction with Benalla Rural City Council, could prepare rudimentary mapping based on 2017 LiDAR and a 1% flood level estimate. This lifts the service level to 2.
Winton	LUP DSL = 1; Service Level = 0 There is currently no available detailed ground or flood information to allow any flood mapping. A scoping flood study could be carried out that may inform rudimentary mapping. This lifts the service level above 1.

Actions to address Service Level Scores – Benalla Rural City Council

Campaspe Shire Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Flood Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Clause 21.03-1, 21.03- 3, 21.04-1, 21.04-2, 21.04-5, 21.05-2, 21.05-3, 21.09-1, 21.09-3, 21.09-6 provides good coverage of floodplain management matters.	Yes	Six LFDP have been incorporated into the planning scheme. They require a review	Generally good.	Low

Specific locations (urban centres)

Location Land Use		Existing Planning Scheme Information					
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Colbinabbin	2	FO and LSIO	Mapping based on 1973, 1974 flood information. Overlays could be extended over east of town (school site).	Yes	2		
Girgarre	-	Not Required	The Town is not known to be subject to flooding.	Yes	-		
Kyabram	3	LSIO	Broad brush LSIO exist, which requires a review as part of a flood study	Nil	2		
Rushworth	-	Not Required	Local overland flooding is managed with stormwater works.	-	-		
Stanhope	1	Nil	No known history of flooding in Town.	Nil	0		
Tongala	1	Nil	Local overland flooding is managed with stormwater works.	Nil	0		
Wyuna	1	Nil	Localised drainage path has been mapped.	Nil	0		

Actions to address Service Level scores – Campaspe Shire Council

	Campaspe Shire Council		
Kyabram	LUP DSL = 3; Service Level = 2		
	Carry out a new flood study to review the current mitigation scheme and to improve flood intelligence and mapping.		
	This lifts the service level above 3		

Greater Bendigo City Council

Specific locations

Location Land Use		Existing Planning Scheme Information					
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Costerfield	-	Not required		-	-		
Costerfield South	-	Not required		-	-		
Heathcote East (RLZ)	-	Not required	These areas lie on very small isolated catchment and therefore little benefit of introducing overlay controls	-	-		
Heathcote North (RLZ)	-	Not required		-	-		
Mount Camel	-	Not required		-	-		
Redcastle	0	Mapping would be useful	Catchment through this area is some 18 square kilometres and there would be some merit of having rudimentary overlay controls but not likely to be implemented during the course of this Strategy.	Nil	-		

Actions to address Service Level scores – Greater Bendigo Shire Council

	Greater Bendigo City Council		
Redcastle	LUP DSL = 0; Service Level = - Rural land mapping at a rudimentary scale would be required to address the desirable service level but is regarded as a low priority, and unlikely to be implemented during the course of this Strategy. No further action. This lifts the service level above 0.		

Greater Shepparton City Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Flood Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Provides good coverage of floodplain management matters.	Yes	Six LFDPs have been incorporated into the planning scheme. They require an update	Generally good.	Low

Specific locations (urban centres)

Location	Land Use	Existing Planning Scheme Information				
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level	
Bunbartha	1	FO and LSIO	Minor updates are available as part of the lower Goulburn regional flood study	Yes	1	
Cooma	-	Not Required	The Town is not known to be subject to flooding.	-	-	
Katandra West	2	Nil	Some aerial 2012 oblique photography available that could be used for broad- brush mapping. No detailed ground level information is currently available	Nil	-	
Merrigum	2	Not Required	Flood mapping is based on a detailed flood study (2005)	Yes	3	
Murchison / Murchison East	2	FO and LSIO	Flood mapping is based on limited historical information. New detailed mapping available from the Murchison Flood Mapping Study, which needs to be utilised to update planning scheme.	Yes	1	
Shepparton East	4	Limited LSIO	LSIO based on limited 1993 aerial photography. Shepparton East Overland Flow Urban Flood Study, is now available and should be utilised to update the planning scheme.	Nil	-	
Shepparton Mooroopna	4	UFZ, FO and LSIO	Based on floodplain management study (2002). Requires updating based on the latest Flood Intelligence and Mapping Study.	Yes	3	
Tallygaroopna	1	Mostly Nil	Recorded peak flood levels available but no ground level information. Only broad-brush overlays could be prepared at this stage, until a floodplain management plan is carried out.	Nil	0	

	Land Use	Existing Planning Scheme Information				
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level	
Tatura	3	UFZ, FO and LSIO	Based on Tatura Flood Study.	Yes	3	
Toolamba	1	FO and LSIO	Some minor improvement is required that will be part of the Regional Goulburn and Broken Flood Mapping project.		1	

Actions to address Service Level Scores – Greater Shepparton City Council

	Greater Shepparton City Council
Katandra West	LUP DSL = 2; Service Level = - Only rudimentary low level mapping could be prepared, based on available flood photography. This lifts the service level to 2.
Murchison/ Murchison East	LUP DSL = 2; Service Level = 1 Update planning scheme with new detailed flood mapping from the Murchison Flood Mapping Study This lifts the service level to 4.
Shepparton East	LUP DSL = 4; Service Level = - Update planning scheme with new detailed flood mapping from the Shepparton East Overland Flow Urban Flood Study This lifts the service level to 4.
Shepparton Mooroopna	LUP DSL = 4; Service Level = 3 Update planning scheme with new detailed flood mapping from the Shepparton Mooroopna Flood Intelligence and Mapping study. This lifts the service level to 4
Tally- garoopna	Only rudimentary low level mapping could be prepared, based on available flood photography.
Mansfield Shire Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Provides good coverage of floodplain management matters	Yes	Shire-wide LFDP in place	Yes including UFZ through Mansfield.	-

Location	Land Use	Existing Planning Scheme Information					
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Bonnie Doon	-	-	-	-	-		
Gaffney's Creek / A1 Mine Settlement	-	-	-	-	-		
Howqua	1	FO	Fair flood mapping has been placed into planning scheme using recent valley LiDAR data. Detailed hydrology recently completed should be utilised to provide improved flood mapping and intelligence.	Yes	1		
Jamieson	2	LSIO and FO	Flood mapping is based on hydraulic mapping as part of Jamieson Scoping Study. Detailed hydrology recently completed that may be utilised to provide improved flood mapping and intelligence.	-	2		
Maindample	1	LSIO	Rudimentary mapping has been placed into planning scheme	Yes	1		
Mansfield	3	LSIO and FO	Flood mapping based on detailed 2D- hydraulic modelling.	Yes	3		
Merton	-	-	-	-	-		
Merrijig	-	-	-	-	-		
Wood's Point	0	LSIO	Rudimentary mapping has been placed into planning scheme	Yes	1		

Actions to address Service Level Scores – Mansfield Shire Council

	Mansfield Shire Council						
Jamieson	LUP DSL = 2; Service Level = 2						
	GB CMA will seek to improved regional flood mapping and intelligence for major floodplain valleys in the Shire including Jamieson due to availability of completed hydrologic study. This lifts the service level above 2.						

Mitchell Shire Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Provides good coverage of floodplain management matters	Yes	A LFDP is incorporated in planning scheme for the Goulburn River but requires a review.	Overall fair to good coverage. Five major areas will require updating. over the next few years	Medium

Location	Land Use	Existing Planning Scheme Information					
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Broadford ⁱ	3	LSIO and FO	Parts of the town are known to be subject to flooding. New flood mapping and intelligence project will provide revised flood mapping for the planning scheme.	Nil	2		
Kilmore	4	Nil	New flood mapping and intelligence project will provide new flood mapping for the planning scheme.	Nil	-		
Kilmore East ⁱ	0	Nil	Extent of flooding has yet to be defined. New flood mapping and intelligence project will provide new flood mapping for the planning scheme.	Nil	3		
Pyalong	0	Nil	Flooding is unlikely given the incised nature of the waterways relative to the developed areas. A check could be carried out using approximate modelling techniques	Nil	-		
Ready Creek ⁱⁱ	1	Nil	Extent of flooding is unknown and yet to be defined. New flood mapping and intelligence project will provide new flood mapping for the planning scheme as part	Nil	-		

			of the regional study for Dabyminga Creek.		
Seymour (Goulburn River)	4	Nil	Current flood mapping is sound along the Goulburn River – refer Whiteheads Creek	Yes	4
Tallarook	1	Nil	Rudimentary low accurate broad-brush mapping has been used in the current planning scheme. More accurate mapping is available from the Tallarook Flood Mapping Project that should be used if the regional Dabyminga Creek Regional Study is delayed.	Nil	1
Tyaak "	0	Nil	Extent of flooding is unknown and yet to be defined. New flood mapping and intelligence project will provide new flood mapping for the planning scheme as part of the regional study for Dabyminga Creek.	Nil	-
Whiteheads Creek	4	UFZ, FO and LSIO	Current mapping is broad-brush along Whiteheads Creek and its tributaries. Planning scheme requires updating once Whiteheads Creek Flood Mapping Study is completed.	Nil	2

ⁱ Part of Sunday Creek and Dry Creek Regional Study ⁱⁱ Part of the Dabyminga Creek Regional Study

Actions to address Service Level Scores – Mitchell Shire Council

	Mitchell Shire Council
Broadford	LUP DSL = 4; Service Level = 2
	Introduce new UFZ, and revise FO and LSIOs from the Sunday Creek and Dry Creek Flood Mapping and Intelligence Study (funding approved late 2017).
	This lifts the service level above 4.
Kilmore	LUP DSL = 4; Service Level = 0
	Introduce new UFZ, FO and LSIOs from the Kilmore Flood Mapping and Intelligence Study.
	This lifts the service level above 4.
Whiteheads	LUP DSL = 4; Service Level = 2
Creek	Update the UFZ, FO and LSIOAs from the Whiteheads Creek Flood Mapping Study.
	This lifts the service level above 4.
Pyalong	LUP DSL = 0; Service Level = -
	A low priority. Plan to carry out approximate mapping methods to provide rudimentary mapping.
	This lifts the service level to 0.

Moira Shire Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Provides fair coverage of floodplain management matters	Yes but requirement updating	LFDPs drafted but not incorporated in planning scheme	Overall good coverage but require updating along the Murray River, Broken Creek and lower Goulburn areas	High

Location	Land	Existing Planning Scheme Information				
	Use Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level	
Barmah	3	LSIO and FO	Mapping based on estimated 1% AEP flood heights against accurate ground level data.	No	3	
Bearii	1	LSIO and FO	Rudimentary brush mapping based on estimated 1% AEP flood heights and one- foot ground contours.	No	1	
Cobram ¹	2	LSIO and FO around protected areas	There is scope to improve overlay controls from the Murray River Regional Flood Study - Dicks/Seppelts levees.	No	2	
Katamatite "	1	LSIO and FO	Mapping based on estimated 1% AEP flood heights and aerial flood photography against one-foot ground level information. May improve mapping from the Upper Broken Creek Regional (Rural) Study	No	1	
Koonoomoo ⁱ	1	LSIO and FO	Mapping based on estimated 1% AEP flood heights and aerial flood photography against one-foot ground level information. May improve flood mapping from the Murray River Regional Flood Study - Dicks/Seppelts levees.	Nil	1	
Lake Rowan ⁱⁱ	1	Nil	Introduce FO and LSIO into planning scheme following completion of the Upper Broken Creek Regional (rural) Flood Study	No	-	
Marungi	-	No required	-	-	-	
Nathalia	2	LSIO and FO	Current mapping is fair. Mapping can be updated on a Shire-wide basis from the Nathalia Floodplain Management Study	No	2	

Location	Land		Existing Planning Scheme Informa	tion	
	Use Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level
Numurkah	3	UFZ, LSIO and FO	Current mapping overall is fair but inaccurate in sections. Mapping can be updated on a Shire-wide basis from the Numurkah Floodplain Management Study.	No	2
St James ⁱⁱ	1	Nil	Introduce FO and LSIO into planning scheme following completion of the Upper Broken Creek Flood Regional (Rural) Flood Study.	No	-
Strath- merton ⁱ	-	Nil	Introduce new LSIO and FO into the planning scheme prepared from the Murray River Regional Flood Study - Dicks/Seppelts levees to downstream of the Ulupna Creek confluence.	No	1
Tungamah ⁱⁱ	2	LSIO and FO	Mapping based on estimated 1% AEP flood heights (from 1974 peak flood heights) against accurate ground level data. A floodplain management plan is required – possibly as part of the Upper Broken Creek (Rural) Study. Revised flood mapping to be utilised for planning scheme.	No	1
Waaia		Not required	Not subject to riverine flooding, but a significant drainage line has been identified that can be shown in the planning scheme. Such effort would be Shire-wide.	-	-
Wilby ⁱⁱ	1	Nil	Introduce new LSIO and FO following completion of the regional upper Broken Creek Regional	-	0
Wunghnu	2	UFZ, LSIO and FO	Rudimentary mapping based on estimated 1% AEP flood heights and foot ground contours.	No	1
Yarrawonga	3	Nil	Flood mapping from Yarrawonga Overland Drainage and Flood Study be introduced into planning scheme	No	-
Yarroweyah ⁱ	2	LSIO	Introduce revised LSIO and FO into the planning scheme from the Murray River Regional Flood Study - Dicks/Seppelts levees to downstream of the Ulupna Creek confluence.	No	1

Murray River Regional Study Cobram to Ulupna Area

² Upper Broken Creek (Rural) Area

	Moira Shire Council
Numurkah	LUP DSL = 3; Service Level = 2 Update flood mapping from findings from the Numurkah Floodplain Management Plan This lifts the service level above 3.
Tungamah	LUP DSL = 2; Service Level = 1 Carry out a floodplain management Study with its finding utilised to update planning scheme flood overlays. This lifts the service level above 3.
Cobram to Ulupna (Urban) Area	 LUP DSL = 2; Service Level 1 Used the finding from the Murray River Regional Flood Study - Dicks/Seppelts levees to downstream of the Ulupna Creek confluence to update planning scheme flood overlay including: Cobram; Koonoomoo; Strathmerton; Yarroweyah; and Associated rural areas This lifts the service level to 2.
Upper Broken Creek (Rural) Area	 LUP DSL = 1; Service Level = 0 Carry out new Regional Upper Broken Creek Flood Study. The finding will be used to update the planning scheme flood overlay including: Lake Rowan St James Tungamah (possibly part of the regional study) Wilby Associated rural area primary along Boosey, Broken, Sandy Creeks This lifts the service level above 2.

Actions to address Service Level scores – Moira Shire Council

Murrindindi Shire Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Zone and Overlays	Priority for LGA-wide amendment (-, L, M, H)
Provides good coverage of floodplain management matters	Yes	A LFDP is incorporated in planning scheme for the Goulburn River but requires a review.	Zone and Overlay used that are mostly based on broad- brush mapping with low accuracy but which significant ground truthing (exception is Yea which is based on Yea Flood Study)	-

Location	Land	Existing Planning Scheme Information					
	Use Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Alexandra	3	LSIO	Broad mapping along UT based on account from the 1975 flood. Many other overland flow paths and tributaries identified. A riverine and overland flood study is required. Findings of the study to be used to introduce new overlay controls in the planning scheme (if warranted).	Nil	1		
Buxton ⁱ	3	LSIO	Broad inaccurate mapping used. Following the completion of the Buxton flood mapping study revise overlay controls in the planning scheme.	Nil	1		
Eildon	1	Nil	Possible minor overland flooding. Could carry out an overland flood mapping study but is unlikely to be a priority over the next ten-years	Nil	-		
Flowerdale	2	LSIO and FO	Planning scheme overlay controls require updating based on completed Flowerdale Flood Intelligence and Mapping Study.	Nil-	1		
Kinglake Central	-	No required	Minor drainage lines are deeply incised and unlikely to create major flooding problems.	-	-		
Marysville ⁱ	3	LSIO	Broad inaccurate mapping used. Following the completion of the Maryville flood mapping study revise overlay controls in the planning scheme.	Nil	1		

Location	Land	Existing Planning Scheme Information					
	Use Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Molesworth ⁱⁱ	1	LSIO and FO	Fair representation. Seek to update the planning scheme following completion of the Goulburn and Broken River Regional Study.	Yes	1		
Narbethong		Not required	Some small deeply incised waterways are unlikely to create major flooding problems	-	-		
Kinglake East, Pheasant Creek and King lake West	1		Numerous waterways traverse through these areas and some minor overlay flooding may be possible. If an overland flood study is carried out, introduce new flood overlay control in planning scheme	Nil	-		
Strath Creek	1	LSIO	Broad inaccurate mapping used. Parts of the town subject to possible flooding but severity of flooding is unknown. Introduce new overlay controls when the regional study for lower King Parrot Creek is undertaken	Nil	1		
Taggerty	3	LSIO and FO	Broad brush mapping used but modified based on community input. Revise overlay controls when Taggerty Flood Mapping Study is completed	Nil	1		
Thornton ⁱⁱ	3	FO	Fair representation. Seek to update the planning scheme following completion of the Goulburn and Broken River Regional Study.	Yes	1		
Toolangi	-	Not required	Yea River runs north of the town, which is deeply incised and unlikely to create any flooding issues.	Nil	-		
Yarck	0	LSIO	Broad-brush mapping used along Home Creek (along the western edge of town). Some minor waterways (with a catchment area of around 2 square kilometres) are not likely to pose flooding issues.	Nil	0		
Yea	3	UFZ, LSIO and FO	Accurate mapping exists for riverine type flooding from the Yea River and Boundary Creek and the SL score is 3. However, overlay flooding has been identified as an issue. Introduce new flood overlay controls in the planning scheme following a completion of an overland flood study.	Nil	- (Overland flooding)		

Complete Buxton, Marysville and Taggerty together

" Undertake as part of the Goulburn and Broken River Regional Studies (new initiative for 2018)

	Murrindindi Shire Council
Alexandra	LUP DSL = 3; Service Level = 1 Carried out a riverine and overland flood intelligence and mapping study. Revise and introduce new overlay controls in the planning scheme This lifts the service level to 3.
Buxton	LUP DSL = 3; Service Level = 1 Complete the current Buxton Flood Mapping Study and revise overlay controls in the planning scheme. This lifts the service level to 3.
Flowerdale	LUP DSL = 2; Service Level = 1 Introduce revised flood overlay controls into the planning scheme. This lifts the service level to 3.
Marysville	LUP DSL = 1; Service Level = 0 Carried out a flood mapping study. Revise and introduce new overlay controls in the planning scheme. This lifts the service level above 2.
Thornton	LUP DSL = 3; Service Level = 1 Complete the Goulburn and Broken Rivers Regional Flood Study and revise flood overlay controls in the planning scheme. This lifts the service level to 3.
Yea	LUP DSL = 3; Service Level = - Carried out an overland flood mapping study. Introduce new overlay controls into the planning scheme. This lifts the service level to 3.

Actions to address Service Level Scores – Murrindindi Shire Council

Strathbogie Shire Council

LGA-wide Assessment

Local Planning Policy Framework	Schedule to the flood Overlay Controls	Other	Zone and Overlay	Priority for LGA-wide amendment (-, L, M, H)
Provides good coverage of floodplain management matters	LSIO and FO	Agreement in place until Schedules are incorporated into planning scheme	Poor to fair coverage and requires LGA-wide improvements to the UFZ, FO & LSIO	High

Location	Land Use Planning DSL	Existing Planning Scheme Information					
		Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Avenal ⁱ	2	UFZ, LSIO and FO	Broad-brush flood mapping used. Revise and introduce flood overlay controls following the completion of the Granite Creek Regional Flood Study.	Nil	1		

Location	Land Use Planning	Existing Planning Scheme Information					
	DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Euroa	4	UFZ, LSIO and FO	Mapping based on a 1997 flood study, which has some mapping anomalies. Revise flood zone and overlay controls from the completed Euroa Flood Intelligence and Mapping Study.	Yes	3		
Graytown	-	Not required	Possible minor flooding possible through this largely undeveloped area. This is a low priority and if a scoping study provides flood mapping information, then introduce into the planning scheme.	Nil	-		
Locksley ⁱ	2	LSIO	Broad-brush mapping used. Town is mostly high. Revise and introduce flood overlay controls following the completion of the Granite Creek Regional Flood Study.	-	0		
Longwood ⁱ	1	LSIO	Broad-brush mapping used. Some possible is suspected. Revise and introduce flood overlay controls following the completion of the Granite Creek Regional Flood Study.	Nil	0		
Mangalore	1	Not required	Flooding is suspected based on the past major storm of 2016. If a scoping study is carried out, then introduce flood overlay controls into the planning scheme.	Nil	-		
Nagambie	3	Nil	Introduce zone and overlay controls into the planning scheme from the completed Nagambie Flood Study.	Nil	-		
Old Longwood ⁱ	2	Nil	Town is mostly high. Introduce flood overlay controls following the completion of the Granite Creek Regional Flood Study.	Nil	-		
Ruffy	-	Not required	-	-	-		
Strathbogie	-	Not required	Creeks are deeply incised and unlikely to create major flood issues.	-	-		
Violet Town	3	UFZ, LSIO and FO	Broad-brush mapping used. Revise zone and flood overlay controls into the planning scheme for the completed Violet Town Flood Study.	Yes	1		

ⁱPart of the Granite Creeks Regional Flood Study

	Strathbogie Shire Council
Euroa	LUP DSL = 4; Service Level = 3 Revise flood zone and overlay controls from the completed Euroa Flood Intelligence and Mapping Study. This lifts the service level to 4.
Granite Creeks Area	 LUP DSL = 2; Service Level = 1 Revise and introduce zone and flood overlay controls following the completion of the Granite Creeks Regional Flood Study for: Avenal; Locksley Longwood Old Longwood And associated rural areas from the Hume Freeway to the Goulburn River.
Nagambie	LUP DSL = 3; Service Level = - Introduce zone and flood overlay controls following the completion of the Nagambie Flood Study. This lifts the service level above 3.
Violet Town	LUP DSL = 3; Service Level = 1 Revise zone and flood overlay controls into the planning scheme for the completed Violet Town Flood Study. This lifts the service level above 3.

Actions to address Service Level Scores – Strathbogie Shire Council

Regional (rural centres)

Location	Land Use Planning		Existing Planning Scheme Informa	tion	
	DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level
			Broken Creek		
Broken Creek Tributaries	1	LSIO and FO	Mapping is mostly good, which has been based on 1993 flood information and available imperial ground contours. Unlikely that a regional flood study will be justified in the short.	Yes	1
Lower Broken Creek	2	LSIO and FO	Mapping is mostly good, which has been based on 1974 and 1993 flood information and available imperial ground contours. Revise flood overlay controls from the Nathalia and Numurkah Floodplain Management plans.	No	1
Mid Broken Creek	1	LSIO and FO	Mapping is mostly good, which has been based on 1974 and 1993 flood information and available imperial ground contours. Revise flood overlay controls from the Numurkah Floodplain Management plans.	No	1
Muckatah Depression	1	LSIO and FO	Mapping is mostly good, which has been based on 1974 and 1993 flood information and available imperial ground contours. Unlikely that a regional flood study will be justify overlay control amendments. However, 2012 historical data would assist in updating flood maps	No	1
Upper Broken Creek	2	Nil, LSIO and FO	Many towns are known to be impacted by major floods and have no overlay controls. A regional flood study is required to improve flood mapping and intelligence. Revise and introduce zone and overlay controls following completion of the study.	No	-
		1	Broken River	ı	
Lower Broken River	2	LSIO and FO	Flood mapping from Benalla to Nalinga is poor missing substantial parts of the floodplains. Revised historical mapping underway for BRCC. In the longer-term, the Goulburn and Broken River Regional flood study will provide high quality flood mapping and intelligence information.	No	1

Location	Land Use	Existing Planning Scheme Information				
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level	
Upper Broken River	0	Nil	The FDTP (available via the VFD) data is available but is broad-broad based on limited aerial photography interpretation but should be utilised. In the longer- term, the Goulburn and Broken River Regional flood study will provide high quality flood mapping and intelligence information.			
	1	1	Goulburn System	II		
Acheron River	1	LSIO and FO	Broad-brush inaccurate flood mapping used. From the current Acheron hydrology work being carried the GB CMA will developed revised mapping based on 2D hydraulic modelling based on LiDAR and surveyed features (bridges). This work will provide revised flood mapping for the planning scheme.	No	0	
Corop Lakes	1	LSIO and FO	Available 1973, 1974 and 1975 aerial flood photography together with imperial contours were utilised in the current flood mapping for this area. The Corop Scoping study found that the overlay controls are mostly sound.	Yes	1	
Dabyminga Creek	1	LSIO and FO (in part for Tallarook)	Dabyminga regional flood study, would include the small towns of Reedy Creek, Tallarook and Tyaak.	No	-	
Delatite River	1	FO (partial)	Flood overlay is based on valley survey data from LiDAR and is a fair presentation of the floodplain. Detailed hydrology recently completed should be utilised to provide improved flood mapping and intelligence	Yes	1	
Ford Creek	1	Nil	Detailed hydrology recently completed, which could be utilised to provide improved flood mapping and intelligence for rural areas and for Mansfield urban centre.	Yes	-	
Goulburn Seymour to Shepparton	1	LSIO and FO	1974 RAAF aerial flood photography, peak flood level (1974, 1916) and limit imperial contours utilised. In the longer-term, the Goulburn and Broken River Regional flood study will provide high quality flood mapping and intelligence information, which should be used to update planning schemes (Mitchell, Strathbogie and Greater Shepparton Councils)	Yes	1	

Location	Land Use	Existing Planning Scheme Information					
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Granite Creeks	1	LSIO and FO	Mostly broad-brush mapping based on aerial photography, oblique 1980s aerial photography. The Regional Granite Creek Flood Mapping and Intelligence Study should be utilised to refined planning schemes (BRCC and SSC).	Yes (for SCC)	1		
Howqua River	1	FO	Flood overlay is based on valley survey data from LiDAR and is a fair presentation of the floodplain. Detailed hydrology recently completed should be utilised to provide improved flood mapping and intelligence.	Yes	0		
Lower Goulburn	2	LSIO and FO	Flood mapping bases on 1987 flood study, ground contours and historical peak flood heights and is considered a fair representation. Revised flood mapping from the Lower Goulburn Floodplain Rehabilitation Project could be used to revise flood overlay controls for Campaspe, Greater Shepparton City and Moira Shire Councils.	Yes (for CSSC and GSCC)	2		
Lower King Parrot Creek	0	LSIO and FO	Broad-brush mapping used based on aerial photography but modified based on ground truthing.	Yes	0		
Maindample Region	1	LSIO	Broad-brush mapping used initially based on aerial photography but modified based on ground truthing with community input.	Yes	1		
Mid Goulburn	1	FO	Broad-brush mapping used initially based on aerial photography with some ground truthing. In the longer-term, the Goulburn and Broken River Regional flood study will provide high quality flood mapping and intelligence information, which should be used to update planning schemes (Mitchell, and Murrindindi Councils)				
Sunday & Dry Creeks	1	LSIO and FO	Broad-brush mapping used initially based on aerial photography. Utilise the Sunday and Dry Creek Regional flood study to introduce and revise zone and flood overlay flood controls in the planning scheme (Mitchell Shire).	No	0		
Tatura/ Tongala Region	1	LSIO and FO	Historical data used including 1950 flood and imperial ground data. Detail studies unlikely to add meaningful information at this time.	No	1		

Location	Land Use		Existing Planning Scheme Information				
	Planning DSL	Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Upper Goulburn	1	Nil (excluding Jamieson)	Flood overlay is based on valley survey data from LiDAR and is a fair presentation of the floodplain. Detailed hydrology recently completed should be utilised to provide improved flood mapping and intelligence.	Yes	1		
Upper King Parrot Creek	2	LSIO and FO	Broad-brush mapping based on aerial photography interpretation, and ground truthing with community input. Update flood overlay control; using the Flowerdale Flood Intelligence and Mapping Study	No	1		
Whiteheads Creek	1	UFZ, FO and LSIO	Reasonable flood mapping used based on limited ground contours and recorded historical data. Update zone overlay flood controls following the completion of the Whiteheads Creek flood intelligence and Flood Mapping Study.	No	1		
Yea River	3	UFZ, LSIO and FO	Mapping is up to date including mapping from the Yea Flood Study.	No	4		
			Murray System				
Murray Barmah to Echuca	1	LSIO and FO	Mapping based on a range of flood studies (historical peak flood levels and sound ground level data). Could update mapping using outputs from the Lower Goulburn Floodplain Rehabilitation Scheme Study	Yes	1		
Murray Cobram to Ulupna	2	LSIO and FO	Mapping based historical peak flood levels, aerial flood photography (including satellite) and imperial ground level data. Should update mapping using outputs from the Regional Murray Flood Study to include rural towns: Koonoomoo, Yarroweyah and Strathmerton.	No	1		
Murray Ulupna to Barmah	0	LSIO and FO	Mapping based historical peak flood levels, aerial flood photography (including satellite) and imperial ground level data. A regional flood study for this area unlikely given the low priority compared with other areas at this point of time	No	0		
Murray Upstream of Yarrawonga	0	LSIO and FO	Mapping based on a historical peak flood levels and imperial ground level data but some errors have been found. Could update mapping as part of the global LGA upgrade.	No	0		

Location	Land Use Planning DSL	Existing Planning Scheme Information					
		Zone/Overlay	Description of flood mapping use and location	Incorporated LFDP	Service Level		
Murray Yarrawonga to Cobram East	0	LSIO and FO	Mapping based on a historical peak flood levels and imperial ground level data. Could update mapping as part of the global LGA upgrade (in part, includes the Regional Murray Flood Study).	No	1		

Appendix H: Service levels – Total Flood Warning System (TFWS)

Background

There are two service level report cards produced, the first (RS1) based on all known variables aligned with the above, and the second (RS2) where the adjusted flood risk scores (for Factor G) are assigned based on stakeholder experience and input. In this regard, there are very few adjustments made to the flood risk scores that are documented below.

The service level comparisons with the flood risks are presented below. The following colour codes visually aid where the Flood Warning Service (as a whole) are commensurate with the flood risk as follows:

Red:	Service level of the TFWS is less than level of flood risk
Yellow:	Service level of the TFWS is same as the level of flood risk
Green:	Service level of the TFWS is greater than the flood risk
Further, the elements	(the factors) that make up a TFWS system are coded:

Pink: Element (factor) is less than the flood risk

The Tool has been "gamed" (a trial and error process) allowing possible improvements to some of the elements to elevate the score of the TFWS service level against the adjusted flood risk that is largely guided by the initial actions in the priority assessment in **Chapter 3:**. The detailed methodology is presented in **Appendix K**: TFWS assessment Tool methodology

The following approach, key considerations and assumptions was carried out:

- 1. Using the (TFWS Tool) existing catchments Excel workbook:
 - a) Update Tool input data to reflect regional Strategy actions identified following the input from stakeholder input.
 - b) Review Factor G (Social and Economic Assessment flood risk score) following the input from stakeholder input.
 - c) For those management units where TFWS levels remain less than the adjusted score, "game" (trial) the Tool input data to achieve service level commensurate with the flood risk level.
- 2. Benefits to the TFWS arising from delivery of proposed detailed flood studies have been placed through the Tool where flood intelligence can be incorporated into planning schemes, response plans and the like.
- 3. Where the service level of a TFWS element is less than the adjusted flood risk level, opportunities exist to initiate action to improve that element. It is important to note as a number of elements (factors) within the Tool have a time component that acts to reduce their value to the overall TFWS as time pass (e.g. last major flood, Local Flood Guide, LFG, flood study and mapping, flood intelligence and MFEP) it is important to recognise that service levels for Factor D, E and F will continue to decline unless renewal or update activity occurs.
- 4. The reworked Tool has been extended to July 2017

The TFWS service levels are presented on the local government areas for urban centres, and followed by regional rural areas across the Goulburn Broken CMA region. Under each assessment, a summary of action/improvements are provided to match to flood risk scores.

			Service	Levels				F	Factor							
Location/	A	В	С	D	E	F			G		I s settent					
Diver Darah	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)		sted Flood sk Score		Location/ River Reach					
addaginnie	1	0	0	0	3	0	1		1	В	addaginnie					
enalla	2	2	2	2	4	4	3			В	enalla					
evenish	1	0	0	0	0	0	1		0	D	evenish					
lenrowan (Rural City of Wang)	0	0	0	0	0	0	1		0	G	lenrowan (Rural City of Wang)					
wanpool	2	0	0	0	0	0	1		1	S	wanpool					
atong	1	0	0	0	0	0	1		1	T	atong					
hoona	0	0	0	0	0	0	0		0	Т	hoona					
lote Flood Risk Levels are the sa	ame as the Adjusted	Flood Risk Score														
								Risk	k Level Cold	our Co	ding					
							TFV	VS Element S	Service Level	l is less	than Level of Risk					
							Overall	TWFS Servi	ice Level is g	greater t	han the Level of Risk					
							Overa	all TWFS Se	rvice Level is	s equal	to the Level of Risk					
									vice Level is	less th	Overall TWFS Service Level is less than the Level of Risk					

Benalla Rural City Council (Urban Centres)

	Benalla Rural City Council											
Benalla TFWS SL = 3; Flood risk score = 4												
	Improve dissemination and communication, awareness and education including introduction of planning scheme mapping from available flood data. Share site-specific property information - seek option using HydroNET hoisting. This lifts the TFWS SL above 3, which is still a little lower than the flood risk score											

Campaspe Shire Council (Urban Centres)

			Service		Factor				
Location/	A	8	C	D	E	F		G	Location/
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)	Adjusted Flood Risk Score	River Reach
olbinabbin	0	0	0	0	4	0	1	1	Colbinabbin
lirgarre	0	1	0	0	0	0	1	0	Girgarre
(yabram	.1	1	0	0	0	0	1	2	Kyabram
Rushworth	0	1	0	0	4	0	-1		Rushworth
Stanhope	0	1	0	0	0	0	1	1	Stanhope
Tongala	Ð	1	0	0	0	0	1	1	Tongala
Wyuna	0	1	0	0	0	0	1	1	Wyuna
Note Flood Risk Levels are the s	same as the Adjusted I	Flood Risk Score							
								Risk Level Colou	ir Coding
							TFV	VS Element Service Level is	less than Level of Risk
							Overal	TWFS Service Level is gre	ater than the Level of Risk
							Over	rall TWFS Service Level is e	qual to the Level of Risk
								all TWFS Service Level is in	ss than the Level of Risk

	Campaspe Shire											
Kyabram	TFWS SL = 1; Flood risk score = 2											
	Improve service level factors C, D, E and F through the completion of a new overland flood study.											
	This lifts the TFWS SL above 2 which is still a little lower than the flood risk score											

Greater Bendigo City Council

			Service	Levels				Factor	
Location/	A	В	C	D	E	F		G	Location/
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)	Adjusted Flood Risk Score	River Reach
Costerfield	1	1	0	0	0	0	1	0	Costerfield
Costerfield South	1	1	0	0	0	0	1	0	Costerfield South
Heathcote East (Rural Living)	1	1	0	0	0	0	1	0	Heathcote East (Rural Living)
Heathcote North (Rural Living)	0	0	0	0	0	0	0	0	Heathcote North (Rural Living)
Mount Camel	0	0	0	0	0	0	0	0	Mount Camel
Redcastle	0	0	0	0	0	0	0	0	Redcastle
Note Flood Risk Levels are the san	ne as the Adjusted Fi	lood Risk Score							
								Risk Level Co	lour Coding
							TFV	WS Element Service Lev	el is less than Level of Risk
							Overal	II TWFS Service Level is	greater than the Level of Risk
							Over	rall TWFS Service Level	is equal to the Level of Risk
							Over	rall TWFS Service Level	is less than the Level of Risk

No identified priorities in terms of overall TFWS services.

			Service	Levels					Factor				
Location/	A	В	С	D	E	F			G		Location/		
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)		Adjusted Flood Risk Score		River Reach		
Bunbartha	0	1	0	0	0	0	1		1		Bunbartha		
Cooma	0	1	0	0	0	0	1		1		Cooma		
East Murchison	1	1	0	0	4	4	2		1		East Murchison		
East Shepparton	1	1	0	1	4	4	2		2		East Shepparton		
Katandra West	0	0	0	0	0	4	1		0		Katandra West		
Kialla West	3	3		3	4	0	2		1		Kialla West		
Merrigum	0	1	0	2	4	0	1		2		Merrigum		
Murchison	4	3	0	1	4	4	3		1		Murchison		
Shepparton/Mooroopna	3	2	0	4	4	4			4		Shepparton/Mooroopna		
Tallygaroopna	0	0	0	2	0	4			3		Tallygaroopna		
Tatura	1	1	0	2	4	0			2		Tatura		
Toolamba	1	1	0	0	0	0	1		1		Toolamba		
Note Flood Risk Levels are the sa	ame as the Adjusted	Flood Risk Score ex	cept for Shepparton/	Mooroopna where i	t has been increase	from 3 to 4.							
							Risk Level Colour Coding						
							TFV	NS EI	ement Service Level i	is les	s than Level of Risk		
											r than the Level of Risk		
							Over	all T	WFS Service Level is	equa	I to the Level of Risk		
							Over	all TA	VFS Service Level is I	less t	han the Level of Risk		

Greater Shepparton City Council (Urban Centres)

	Greater Shepparton City Council
Merrigum	TFWS SL = 1; Flood risk score = 2
	Improve awareness and education (Local Flood Guide) and Response Planning (MFEP).
	This lifts the TFWS SL to 2, the same as the adjusted flood risk score
Shepparton/	TFWS SL = 3; Adjusted Flood risk score = 4
Mooroopna	Improve dissemination and communication (SMS Service), awareness and education (property-specific flood information on web portal) and including revised planning scheme mapping from floodplain management study.
	This lifts the TFWS SL above 3, nearing the same as the adjusted flood risk score of 4.
Tally-	TFWS SL = 1; Flood risk score = 3
garoopna	A full flood study would be required to provide appropriate flood intelligence to improve interpretation, education and awareness. Improve dissemination and communication would also be required to be improved.
	This lifts the TFWS SL to 3, the same as the adjusted flood risk score
Tatura	TFWS SL = 1; Flood risk score = 2
	Improve awareness and education (Local Flood Guide) and Response Planning (MFEP).
	This lifts the TFWS SL to 2, the same as the adjusted flood risk score

Mansfield Shire Council

			Service	Levels					Factor	1				
	Α	В	С	D	E	F			G					
Location/ River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)		Adjusted Flood Risk Score		Location/ River Reach			
Bonnie Doon	1	0	0	0	0	0	1		1		Bonnie Doon			
Gaffneys Creek (Castle Point/A1 Mine)	0	0	0	0	0	0	1		0		Gaffneys Creek (Castle Point/A1 Mine)			
Howqua	1	0	0	0	0	0	1		1		Howqua			
Jamieson	1	0	0	3	3	4	2		2		Jamieson			
Maindample	0	0	0	0	0	0	1		0		Maindample			
Mansfield	1	0	0	2	4	4	2		1		Mansfield			
Merrijig	0	1	0	0	0	0	1		1		Merrijig			
Merton	0	0	0	0	0	0	1		0		Merton			
Woods Point	0	0	0	0	0	0	1		0		Woods Point			
Jamieson adjusted to include Flo	odSafe and new ove	erlay control and lift	ed Factor D from 1 to	3										
							Risk Level Colour Coding							
							TF\	NS EI	ement Service Leve	l is le	ss than Level of Risk			
											er than the Level of Risk			
							Over	all T	WFS Service Level i	s equ	al to the Level of Risk			
							Over	all T\	WFS Service Level is		than the Level of Risk			

No identified priorities in terms of overall TFWS services.

Mitchell Shire Council (Urban Centres)

			Service	Levels					Factor					
Location/	A	В	С	D	E	F			G		Location/			
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)		Adjusted Flood Risk Score		River Reach			
Broadford	1	0	0	2	0	4	1		2		Broadford			
Kilmore	0	0	0	0	4	0	1		1		Kilmore			
Kilmore East	1	0	0	0	0	0	1		0		Kilmore East			
Pyalong	2	0	0	0	0	0	1		0		Pyalong			
Reedy Creek	1	0	0	0	0	0	1		0		Reedy Creek			
Seymour	4	3	0	2	4	4	3		3		Seymour			
Tallarook	1	0	0	0	4	4	2		1		Tallarook			
Tyaak	1	0	0	0	0	0	1		0		Tyaak			
Whiteheads Creek	2	0	0	2	4	0	1		1		Whiteheads Creek			
Note Adjusted Flood Risk Scores	are unchanged from	n Flood Risk Scores												
							Risk Level Colour Coding							
							TF	WS EI	ement Service Leve	el is le	ess than Level of Risk			
							Overa	II T W	FS Service Level is	great	er than the Level of Risk			
							Ove	rall T	WFS Service Level i	s equ	al to the Level of Risk			
							Over	rall T V	VFS Service Level i		than the Level of Risk			

	Mitchell Shire											
Broadford	TFWS SL = 1; Flood risk score = 2 Flood study is proposed for Broadford as part of the Sunday Creek Flood Intelligence and Mapping Study. This will provide flood intelligence to improve interpretation and flood overlay controls for the											
	planning scheme. This lifts the TFWS SL above 2 which meets the flood risk score											

Moira Shire Council (Urban Centres)

			Service	Levels					Factor				
Location/	Α	В	С	D	E	F			G		Location/		
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)		Adjusted Risk Score	-	River Reach		
Barmah	3	3	0	2	4	4	3		3		Barmah		
Bearii	3	1	0	2	0	4	2		1		Bearii		
Cobram	3	1	0	0	4	4	2		3		Cobram		
Katamatite	1	0	0	2	4	4	2		2		Katamatite		
Koonoomoo	2	1	0	2	3	4	2		1		Koonoomoo		
Lake Rowan	1	0	0	2	0	0	1		1		Lake Rowan		
Marungi	0	0	0	2	0	0	1		1		Marungi		
Nathalia	3	2	1	3	4	4	3		2		Nathalia		
Numurkah	1	0	0	2	4	4	2		4		Numurkah		
St James	1	0	0	2	0	0	1		1		St James		
Tungamah	2	0	0	2	0	4	1		3		Tungamah		
Waaia	0	0	0	1	3	0	1		1		Waala		
Wilby	1	0	0	1	0	0	1		1		Wilby		
Wunghnu	0	0	0	2	4	4			3		Wunghnu		
Yarrawonga	2	2	0	2	3	4	3		1		Yarrawonga		
Lake Rowan & Wilby scores were	increased to 1										Lake Rowan & Wilby scores were increased		
							Risk Level Colour Coding						
							TF	WS EI	ement Service Leve	el is le	ss than Level of Risk		
							Overa	IITW	FS Service Level is	greate	er than the Level of Risk		
							Ove	rall T	WFS Service Level i	s equ	al to the Level of Risk		
							Over	rall TV	VFS Service Level is	s less	than the Level of Risk		

	Moira Shire Council
Cobram	TFWS SL = 2; Flood risk score = 3
	Improve dissemination and communication, awareness and education including introduction of planning scheme mapping from floodplain management study
	• This lifts the TFWS SL to 3, the same as the adjusted flood risk score
Numurkah	TFWS SL = 2; Flood risk score = 4
	Implementation of Data Collection Network in-train together with new flood warning services (ERRTS). Numurkah floodplain management study will provide flood intelligence for all service level factors.
	• This lift the TFWL SL to near 4, the same as the adjusted flood risk score
Tungamah	TFWS SL = 1; Flood risk score = 3
	A full floodplain management study is flagged as a high priority that will assist with service level factors C, D and E.
	Flood Warning Services requirements will be reviewed as part of the study.
	This lifts the TFWL SL to 3, the same as the adjusted flood risk score
Wunghnu	TFWS SL = 2; Flood risk score = 3
	Improved dissemination and communication.
	• This lifts the TFWL SL to 3, the same as the adjusted flood risk score

Murrindindi Shire Council (Urban Centres)

			1	Factor	1									
	A	В	С	D	E	F			G					
Location/ River Reach	DCN			Adjusted Flood Risk Score		Location/ River Reach								
Alexandra	1	1	0	0	0	0	1		1		Alexandra			
Buxton	1	1	0	0	4	0			2		Buxton			
Eildon	1	0	0	2	2	0	1		0		Eildon			
Kinglake Central	1	0	0	0	0	0	1		0		Kinglake Central			
Kinglake East	1	0	0	0	0	0	1		0		Kinglake East			
Marysville	1	0	0	0	4	0	1		1		Marysville			
Molesworth	1	1	0	2	0	0	1		1		Molesworth			
Narbethong	1	0	0	0	0	0	1		0		Narbethong			
Pheasant Creek & Kinglake West	1	0	0	0	0	0	1		0		Pheasant Creek & Kinglake West			
Strath Creek	1	0	0	2	0	0	1		1		Strath Creek			
Taggerty	3	2	0	2	4	0	2		1		Taggerty			
Thornton	1	0	0	2	0	0			2		Thornton			
Toolangi	1	0	0	0	0	0	1		0		Toolangi			
Yea	1	0	0	2	4	4	2		2		Yea			
Note Adjusted Flood Risk Scores	s are unchanged from	m Flood Risk Scores												
							Risk Level Colour Coding							
										_	ss than Level of Risk			
											er than the Level of Risk			
											al to the Level of Risk			
							Over	all TV	VES Service Level is	less	than the Level of Risk			

	Murrindindi Shire									
Buxton	TFWS SL = 1; Flood risk score = 2									
	Flood study is underway for Buxton. This will provide flood intelligence to improve Factors C, D, E and F including overlay controls for the planning scheme, Local Flood Guide and inclusion into MFEP. This lifts the TFWS SL above 2 which meets the flood risk score.									
Thornton	TFWS SL = 1; Flood risk score = 2									
	Scoping flood study has been identified with a focus of improve flood intelligence around TFWS elements (Factors C, D, E and F).									
	This lifts the TFWS SL above 2 which meets the flood risk score.									

Strathbogie Shire Council (Urban Centres)

			Levels			Factor								
Location/	A	В	С	D	E	F			G		Location/			
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	Service Level Tier (Factors A-F)		Adjusted Flood Risk Score		River Reach			
Avenel	1	1	0	0	4	4	2		1		Avenel			
Euroa	3	2	0	2	4	4	2		3					
Graytown	1	1	0	0	0	0	1		0					
Locksley	1	1	0	0	3	0	1		1					
Longwood	1	1	0	0	3	0	1	1 0			Longwood			
Mangalore	1	1	0	0	0	0	1			0		Mangalore		
Nagambie	2	2	0	0	4	4	2		2		Nagambie			
Old Londwood	1	1	0	0	3	0	1		0		Old Londwood			
Ruffy	1	0	0	0	0	0	1		0		Ruffy			
Strathbogie	2	1	0	0	0	0	1		0		Strathbogie			
Violet Town	2	1	0	2	4	4	2		3		Violet Town			
Note Adjusted Flood Risk Scores	are unchanged from	n Flood Risk Scores	, except for Euroa and	d Violet Town where	the scores been in	creased from 2 to 3.								
							Risk Level Colour Coding							
							TF\	NS EI	ement Service Leve	lisle	ss than Level of Risk			
							Overall TWFS Service Level is greater than the Level of Risk							
							Over	all TV	WFS Service Level i	s equ	al to the Level of Risk			
							Over	all TV	VFS Service Level is	less	than the Level of Risk			

	Strathbogie Shire
Euroa	TFWS SL = 2; Adjusted Flood risk score = 3
	Flood intelligence is available to improve awareness and education by providing site-specific property flood information via the web portal initiative, and improved dissemination and communication.
	This lifts the TFWS SL above 3 which meets the adjusted flood risk score.

Violet Town	TFWS SL = 2; Flood risk score = 3
	Flood intelligence is available to improve awareness and education by providing site-specific property flood information via the HydroNET initiative, and improved dissemination and communication.
	This lifts the TFWS SL above 3 which meets the flood risk score.

Regional (rural) areas

			Service	Levels				Factor						
Location/	A	В	С	D	E	F	Service Level Tier	G	Location/					
River Reach	DCN	Forecasting	Dissemination & Communication	Awareness & Education	Interpretation	Response Planning	(Factors A-F)	Adjusted Flood Risk Score	River Reach					
BROKEN CREEK SYSTEM									BROKEN CREEK SYSTEM					
Broken Effluent Tributaries	0	0	0	2	0	4	1	2						
Lower Broken Creek	2	1	0	2	0	0	1	1						
Mid Broken Creek	1	1	0	2	4	4	2	1	Mid Broken Creek					
Muckatah Depression	1	0	0	2	0	4	1	1	Muckatah Depression					
Upper Broken Creek	1	0	0	2	0	0	1	1	Upper Broken Creek					
BROKEN RIVER SYSTEM									BROKEN RIVER SYSTEM					
Lower Broken River	1	0	0	0	0	0	1	0	Lower Broken River					
Upper Broken River	2	1	0	0	0	0	1	0	Upper Broken River					
GOULBURN RIVER SYSTEM									GOULBURN RIVER SYSTEM					
Acheron River & Tribs	1	0	0	2	4	0	1	1	Acheron River & Tribs					
Corop Lakes	0	0	0	0	4	0	1	1	Corop Lakes					
Dabyminga Creek	1	0	0	0	4	0	1	1	Dabyminga Creek					
Delatte River (at Delatte Rd)	0	0	0	0	0	4	1	1	Delatite River (at Delatite Rd)					
Ford Creek	1	0	0	2	4	0	1	1	Ford Creek					
Goulburn R (Seymour to Shepparton)	3	2	0	1	2	0	1	1	Goulburn R (Seymour to Shepparton)					
Granite Creeks	1	1	0	0	3	0	1	1	Granite Creeks					
Howqua River	1	0	0	0	0	0	1	1	Howqua River					
Lower Goulburn (d/s of Sheppaton)	2	2	0	2	4	0	2	1	Lower Goulburn (d/s of Sheppaton)					
Lower King Parrot Creek	1	0	0	2	0	0	1	1	Lower King Parrot Creek					
Maindample Region (at Dry Creek Road)	0	0	0	0	0	0	1	1	Maindample Region (at Dry Creek Road)					
Mid Goulburn	1	2	0	0	0	0	1	1	Mid Goulburn					
Sunday & Dry Creeks	1	0	0	0	0	0	1	1	Sunday & Dry Creeks					
Tatura/Tongala Region	0	1	0	0	0	0	1	1	Tatura/Tongala Region					
Upper Goulburn (u/s of Elidon)	1	0	0	0	0	0	1	1	Upper Goulburn (u/s of Elidon)					
Upper King Parrot Creek	2	0	0	0	4	0	1	1	Upper King Parrot Creek					
Whiteheads Creek	2	0	0	2	4	0	1	1	Whiteheads Creek					
Yea River	1	0	0	2	4	4	2	1	Yea River					
MURRAY RIVER SYSTEM									MURRAY RIVER SYSTEM					
Barmah to Echuca	3	2	0	2	3	4	2	1	Barmah to Echuca					
Cobram to Ulupna	3	1	0	2	3	4	2	1	Cobram to Ulupna					
Piree Creek to Barmah	3	2	0	2	3	4	2	1	Piree Creek to Barmah					
Ulupna to Piree Creek	2	1	0	2	3	4	2	1	Ulupna to Piree Creek					
Upstream of Yarrawonga	2	2	0	0	4	0	1	1	Upstream of Yarrawonga					
Yarrawonga to Cobram	3	1	0	2	3	4	2	1	Yarrawonga to Cobram					
Note Adjusted Flood Risk Scores	are unchanged fror	n Flood Risk Scores												
								Risk Level Colour Coding TFWS Element Service Level is less than Level of Risk Overall TWFS Service Level is greater than the Level of Risk						
							0	Risk Level Colour	<u> </u>					
							Overa	II TWFS Service Level is les	ss than the Level of Risk					

Regional (rural) Areas									
Broken Effluent Tributaries (Pine Lodge, Daintons, Congupna, Guilfus and O'Keefe Creeks)	TFWS SL = 2; Flood risk score = 3 Improvements to Factors D, E and F may be gained from a regional study This lifts the TFWS SL above 2 which meets the flood risk score.								

Appendix I: Comments, Issues and Feedback Received at Public Information Sessions

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Seymour – 6 th Feb 2017, 12 noon to 2pm				
	Goulburn River (Seymour to Shepparton) – higher priority for land-use planning.				
1	Although flood overlays do exist in planning schemes along this river reach, they are based on limited information. New flood mapping will improve the accuracy in terms of flood extent.			х	
	Response 1				
	Medium priority is already appropriate				
	The urban centres prioritisation for Mitchell Shire suggests that a flood assessment of Tyaak will be part of the Sunday Creek study. It is not in that catchment.				
2	Response 2			х	
	The rural towns of Tyaak and Reedy Creek are within the Dabyminga Creek catchment. Correct error in Main report but leave original in Appendix.				
3	 Johnsons Lane Northwood Built new house, floor height 700-800mm above 1% flood level, and decommissioned old house. During the 2010-2011 floods, the home was isolated for 5 days, as access is cut by floodwater. Flood levels, via the computer, are checked which is very important. When Goulburn River reaches just below minor flood level, floodwater will start back flowing and filling local lagoons. Owners have been on the property for 8 years and established a good level of flood awareness. 		x		

Note an "x" has been placed in the relevant four RHS columns to signify topic under consideration

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Response 3				
	This is a good example of self-resilience and the good use of information on the web. Access to fit-for- purpose flood information is an important priority for the Regional Floodplain Management Strategy.				
4	Reedy Creek (north-east of Avenal) is a perched waterway, where maintenance is constantly required by VicRoads to reduce the change of flooding over the Hume Freeway.		x		x
	Should look at re-vegetation opportunities to assist with reducing run-off. Suggestion was made in relation to ongoing maintenance cost, for instance for a town levee, should be Bourne by the beneficiaries.				
	Like fire – provide good quality information improve flood resilience				
	Response 4				
	Opportunities for an integrated catchment management approach, such as re-vegetation of upstream catchments is supported.				
	The beneficiary pay principle for on-going maintenance cost should apply in line with the Victorian Floodplain Management Plan.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Access to fit-for-purpose flood information is important priority for the Regional Floodplain Management Strategy				
5 FF	 Whiteheads creek affects their area, Goulburn River is a worry for main part at Seymour and tourism business Local agencies should put signs when they know Whiteheads Creek is flooding. Don't want another death – use radio, Facebook and social media as well as TV if enough time Difficult to balance flood risks and environmental/cultural heritage considerations - hasn't liked loss of old (heritage) buildings in the past Response 5 New flood intelligence and mapping study is advanced and should assist with fit-for-purpose flood information for communities and MFEP. Also VICSES are looking at ways to improve community messaging 		x	x	x
	for flash flood areas. Nagambie – 6 th Feb 2017, 5pm to 7pm				
	High Street Nagambie – once a year water is not able to drain, which can be in the order 500mm deep. Land has a drainage easement along the southern boundary that collects water from upstream areas. Eight trees grown in easement. Two trees have died in the drought.				
	The floor of the dwelling is level with the ground, and at risk of over floor flooding. Part of office recently flooded due to poor drainage.				
	Park Street has septic issues. End of Park Street has a retardation basin that requires to be emptied by pumping				
6	Group meeting of Issues	Drainage			
	Drainage was a key issue. In particularly over Council requirements for new development (subdivision) that doesn't include old infrastructure (retrospective drainage needs).				
	Response 6				
	Depending on priority of Council a drainage implementation plan for Nagambie could be an option. The new flood model may be utilised by Strathbogie Shire Council to consider drainage management options.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Possibly explore strategic approach such of Contribution Plans and Master Strategic Plan to address a raft of matters to be resolved.				
	This issue is acknowledged but not part of the RFMS.				
	Nagambie - drainage from east of High Street down Vickers Road, and drainage from the east Tabilk Depression around the Barwon Street area.				
7	Response 7	Drainage			
	See Response 6				
8	Minor flooding caused by bad drainage of High Street, Nagambie at southern end of town – affects her home, driveway and street past front gate. A new drainage system needs to be implemented to address this.				
FF	Response 8				
	See Response 6				
	 Flood impacts include fencing, access and stock loss Need more water level stations Have concerns for catchment area concerning native forest habitat for native animals and birds, fish survival Assessments at regular intervals of damage caused by clear felling of catchment areas to water supply, erosion, etc. 				
9	Response 9	Drainage	x		
FF	See Response 6				
	The matter of clear felling impacts on water supply rest with the water authorities. Furthermore, operator must comply with the Code of Practice for Timber Production (2014)				
	Note the comment of more water stations. Warning for Nagambie will be looked at a part of TFWS Assessment tool being prepared by Michael Cawood and Associate.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Benalla – 8 th Feb 2017, 12noon to 2pm				
10	Hollands Creek – 3 km upstream of Tatong. Impact of Handcocks timber plantations on sedimentation in creek and hence fish habitat. Impact on flooding. Response 10 Plantation operations must adhere to the Code of Practice for Timber Production (2014)	х			
11	Issue of Council potentially cutting urban drainage channels through the alluvial ridge of the Broken River and letting floodwater into new subdivision areas. Example is around Cowan Street.	x			x
	Euroa – 8 th Feb 2017, 5pm to 7pm				
12	Low vegetation (understorey vegetation) planted on the floodplain and the impact on flooding. Part of the water management scheme is to remove vegetation regrowth on the floodplain. Also has discussions around vegetation within the channel and on the floodplain along Honeysuckle Creek. Response 12	x			

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	This matter is noted. Need to ensure that such proposed works are vetted by Strathbogie Shire Council to ensure planting programs are not counter to Euroa Water Management Scheme.				
13	Railway culverts/bridges have substantial sediment accumulation impacting on capacity. Also spoke broadly about catchment management activitiesand what can be done upstream.				
	Response 13				
	Cardno Consulting has made recommendation on management, particularly around managing the colonisation of vegetation that "locks" the sediment. Loose sediment is likely to be scoured during the height of major floods.	x			x
	Integrated Catchment Management opportunities, including planning/fencing programs are encouraged in upstream catchment areas to assist within improved waterway health and assisting somewhat for "slowing" floodwaters – but limited to smaller floods.				
	Euroa has a high ranking for all four themes.				
	Dam construction should be considered in terms of providing multiple benefits such as flood mitigation, tourism, water of agriculture.				
14	Response 14	x			
	The sheer size required and thus the enormous cost would never see the economic benefit. In addition, new large dams would likely be counter with the MDBA water cap.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
15	The Seven Creeks is constricted at butter factory bridge. The bridge abutments on the east side of the bridge is the cause of the constriction. Figure 15 Response 15 The butter factory bridge flood modelling was loaded and shown to the audience. Flood depth over this bridge is in the order of 900-1200mm deep for a repeat of a 100-year ARI flood. Also the flood mapping for the 5-year ARI was presented. The floodwater is contained upstream of the bridge and disperses across the floodplain downstream. The flood surface profile did show some minor afflux (increase in flood level) in the 5-year flood that could be attributed by the butter factory bridge. The complete removal of the bridge/abutment would have very limited benefit (and only extend meters upstream) in reducing the impacts of flooding.	X			
16	More community information for better understanding. Good data assists people to make informed decisions. Response 16 <i>Access to fit-for-purpose flood information for the community is important priority for the RFMS.</i>		x		x
17	Honeysuckle Creek – Moved to include with 12. Colbinabbin – 9 th Feb 2017, 12noon to 2pm				

ltem & Response	issue / location / comments	Mittigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Homes on the Bendigo-Murchison Road and on the Wanalta-Corop Road were threatened by flooding in the 2011(?) flood. Two on Wanalta Creek. Approximately 5-6kms north of Bendigo-Murchison Rd there's around 15 houses at risk.				
18	Colbinabbin School is difficult to manage/evacuate in a flood. Response 18 Need to review MFEP		X		X
	Issues with landholders blocking the floodplain via earthworks/levees and issues with the raised Midland Highway. Important to maintain flood paths. Levee constructed in the past may need to be removed to restore functioning floodplains. Comments were made about LGA enforcement processes to deal with illegal activities on the floodplain. Management of the planning overlay.				
19	Response 19 Very difficult to manage if the works are a decade old or so (even more so if pre-planning scheme of 1998) as works are considered part of the landscape. Further if works are be removed, compensation is likely to be paid to the beneficiary of the works. For new works the planning system can be used but this approach is complex and expensive.	x		x	
	If there is an overwhelming community desire to have particular works removed, then the Water Management Scheme (Water Act 1989) process should be followed that is likely to include a detailed flood study to determine the impacts and benefits.				
20	Lack of information available to landholders on the operation of the irrigation system, including the western channel, flood gates, Groves Weir, the lakes to manage flooding. The "operation of the system" during last year floods were beneficial. Comments made around strengthen community relationships.		x		x
	Response 20				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Noted. However, the benefits may not always transpire due to the size of the flood and due to capacity constraints of the Waranga Channel and during times when Lake Cooper is already at full supply level. Summary of GMW operation is as follows:				
	• GMW will divert water from Wanalta Creek or Cornella Creek or both into the Waranga Western Channel (WWC) whenever possible. GMW diverts the water into the WWC for disposal to the Campaspe River, Greens Lake or Lake Cooper (in this order of priority). Diversions for offsite disposal are not permitted if the disposal causes or adds to flooding at the discharge point.				
	• Diversions from Cornella Creek in Colbinabbin occurred in 2016 because the Campaspe River was below the Minor Flood Classification at Rochester. Disposal to the Campaspe River, Greens Lake or Lake Cooper did not occur in January 2011 because the Campaspe River at Rochester was in flood and both Greens Lake and Lake Cooper were full to capacity. Under these circumstances, the standard GMW procedure is to lower the level of the WWC as much as possible, close all regulators and allow creeks to follow natural drainage lines.				
	• GMW does not currently publish the WWC operating rules for Wanalta Creek and Cornella Creek on its website. GMW did publish material describing channel operations during floods following the flooding in 2011 and 2012, but this material was removed at an unknown time. GMW will investigate reinstating material for the general public, although it notes that landholders should not rely on the channel system to act as a flood management device. The channel systems provide very limited protection against floods and are not designed for flood protection.				
	Consider the need for a Local Flood Guide. Follow up recommendation from the Corop Lakes Scoping Study. Medium priority for TFWS has been applied for Colbinabbin.				
	Community relationships are encouraged to build community resilience. Flood warden approach within MFEP may be considered in the MFEP. However see Response 27(b)				
	Lack of focus by GMW on drainage infrastructure/operations. GMW not maintaining their drainage infrastructure.				
21	GMW won't pump floodwater out of Greens Lake to assist with drainage. Landholders not getting anything for their drainage rates.	Drainage			

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Response 21				
	GMW uses Greens Lake as a water storage and captures catchment inflows wherever possible. It is not designed to act as a flood detention basin.				
	The Goulburn Broken Catchment Management Authority received new Victorian government funding to restart the surface drainage program across the Shepparton Irrigation Region. The priority for investment in new drainage systems will be decided by GMW and the GBCMA in consultation with stakeholders and beneficiaries.				
	Some new government money is available for community drainage. Priority for investment is determined by GMW (check this). In terms of drainage rates this is GMW matter and is beyond the scope of the RFMS.				
	A few years ago there was a proposal to clean the Cornella Creek out.				
22	Response 22	x			
	Noted. However, this is of limited benefit during major floods.				
23	Comments concerning development of a compositing operation. Discussion about existing use rights land forming etc. Concern with communications between agencies such as LG, CMA, and GMW. For example, the Shire undertaking road works that will influence flood flows.			x	
	Response 23				
	Planning permits are required for such activities.				
	1973, 1974, 1975 were the worst floods in the Corop Lakes district lasting many months/years severely impacting of agriculture. Also have significant drainage problems				
24	Response 24				
	Noted.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Should identify opportunities where positive things can be achieved in the rural landscape, such as managing minor floods with appropriate levee protection.				
25	Response 25 New levees, particularly, in rural areas would need to cost effective, and not create adverse impacts to neighbouring property. New levee programs would been to follow the Water Management Scheme process outlined in the Water Act 1989.	x			
	I understand from your comments (at the Colbinabbin community meeting) that GBCMA is not prepared to bite the bullet when it comes to dealing with levee bank or other obstructions to what are clearly 'natural' water courses where these have been in existence for more than a few years. This is largely due to a fear of expensive litigation - hardly a good (if practical) reason looking at the big picture. I find this disappointing, as it means that the declaration of drainage courses is somewhat meaningless if the natural flow is impeded by un-natural barriers. Response 26(a)				
26 EC	Refer to response to Response 19 . Further experience in these matters are complex and the recommended approach under the Victorian Floodplain Management Strategy suggests a Water Management Scheme approach would be process. If the community has a particular levee, or a group of levees in mind that should be removed to create a prima facie benefit to the community than the matter could be explored further. Refer to Section 17 of the Victorian Floodplain Management Strategy.	x	x	x	x
	We discussed the need for closer co-ordination between authorities - specifically GBCMA, GMW, VicRoads, and Shire of Campaspe. There were examples cited where there was little evidence of this, and I wonder what plans are in place to remedy the problem. Maybe they are already in place, and it would be helpful to us to know how this will be done. The catchment between Colbinabbin and the Midland Highway is very flat, and even quite low obstructions such as road formations can cause significant flooding if culverts are not properly designed and maintained, or road re-sheeting is done without an understanding of drainage paths. This may not be a big issue as far as the built infrastructure is concerned, but even a few centimetres of water can damage or destroy a valuable				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	crop. In this regard we are of the opinion that the 2012 GHD flood study was too limited in its scope, and more needs to be done to develop a real understanding of floods, their impact, and their management.				
	Response 26(b)				
	In relation of co-ordination of authorities, the Campaspe Planning Scheme requires particular requirements in relation to approvals.				
	It is noted that low works in the flat terrain may cause adverse flood impacts. If not designed correctly.				
	In terms of the 2012 GHD report, its purpose was to scope out fundamental matters and recommend further actions. The recommendations did not warrant further hydrologic or detail hydraulic flood modelling. This is because such effort and cost (many \$100,000s) would provide little benefit in terms of managing legacy flood risk. It is agreed, that such further work in this area would provide insightful knowledge in understanding the nature of flooding, including how made-made features influence flooding, but the cost is prohibited. Furthermore, the current flood mapping serves land-use and development assessment process well.				
	We talked about the value of local knowledge, and particularly where early action on flood mitigation can be effective. Are there any plans to implement any form of local advisory system such as flood monitors or the like?				
	Response 26(c)				
	Local knowledge, during both flood studies and the preparation for floodplain management plans, is considered paramount.				
	At the outset of significant rainfall, and during major floods, the use of local "flood observers" is being addressed by the Control Agency for flood which is VICSES. Such arrangements may add significant intelligence, particularly where gauge networks are lacking.				
	Flood inquiry acknowledged the importance of local flood knowledge. Such knowledge is built into the Municipal Flood Emergency Management Plan.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	There was no discussion on the deployment and use of environmental water while I was there. Is there any current policy and/or strategy regarding the Corop wetlands overall? I gather the control structure planned for the Willoughby's Bridge location is now off the agenda, but an alternative lower-cost option for putting water into Gaynor Swamp is to proceed. Are there any other plans in this regard? I assume One-Tree and Two-Tree Swamps are now forgotten. Perhaps this was outside the scope of the meeting.				
	Response 26(d)				
	Environmental watering is more aligned with the river health strategy and is beyond the scope of Regional Floodplain Management Strategy.				
	Kyabram – 9 th Feb 2017, 5pm to 7pm				
	Statements made by a Wyuna farmer:				
	Has good awareness of river heights, relating to minor, moderate and major flood class levee predictions which are very positive and assist with flood response, i.e., shutting gates etc. The predictions are accurate, with a good amount of time to prepare i.e. 3-4 days lead time.				
	Offset pump into river at the end of Alfred Road operated by GMW and works well.				
	Management of water storages e.g. Eildon Weir should include flooding management outcomes				
27	Response 27(a)	х	x	х	x
	GMW has target filling curves that are applied to manage storage operations. Storages are primary used for the provision of water responses. There is some flexibility in the operations with rainfall forecast (check with GMW).				
	Flood wardens was in place, but doesn't seem to be as active anymore. More flood awareness is required across the community. There need to be a better liaising emergency structure in Campaspe Shire. Campaspe Shire should come out to the community and engage				
ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
--------------------	--	------------------	-------------------------------	-------------------	------------------------------------
	Response 27(b)				
	The use of local "flood observers" is being addressed by the Control Agency for flood which is VICSES. Such arrangements may add significant intelligence, particularly where gauge networks are lacking. Flood inquiry acknowledged the importance of local flood knowledge. Such knowledge is built into the Municipal Flood Emergency Management Plan.				
	Whole Farm Plans - structural grades of the landscape need to be properly considered with neighbours to be considered.				
	Response 27(c)				
	Whole farm plans are considered under the planning scheme process				
	GMW take over private drainage schemes.				
	Response 27(d)				
	This is considered beyond the scope of the RFMS. Whole farm plans are considered under the planning scheme process.				
	Access during flood emergencies should require the maintenance of existing gravel road systems. Such road maintenance must be taken into consideration by local governments to ensure the right roads are passable.				
	Response 27(e)				
	The maintenance of key roads may be considered under the Municipal Flood Response Plan, in concert with flood warning arrangements, where flood consequences are significant.				
	There has been no maintenance along to tracks within the Lower Goulburn National Park this season, which impacts on the ability for emergency response (e.g. end of Alfred Rd has been an issue, which has flood access implications).				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Response 27(f) This park falls under the management of Parks Victoria. There should be no access into the park during times of major floods. However, key well maintained tracks may assist during evacuations. This is a matter for Parks Victoria. Levee system has a lot of low spots due to 4WDs and motor bikes, which cause unnecessary damage. Levee				
	maintenance is required. How do you pay for it and who does? Response 27(g) The beneficiary pay principle for on-going maintenance cost should apply in line with the Victorian Floodplain Management Plan. Otherwise landowners may carry out maintenance works under the new permitting where levees are on Crown land.				
28 FF	 Flood impacts - How does flooding across the floodplain affect you and your community? Does flooding impact on your livelihood such your home, business and/or agriculture use? It greatly affects the community by causing loss of livelihood, inconvenience, damage to property, pastures, crops and plants. As a member of the Kyabram Urban Landcare Group, our areas are greatly affected by flood. We plant and revegetate two areas that have been affected by flood in the last six years: firstly in the 2010/11 floods and secondly with flooding that took place in the Spring of 2016. In these two events many plants – thousands of trees and shrubs that we had planted and grown in the Ern Miles Reserve and the Grey Box Reserve were inundated by water. If that were a fairly short time of inundation, e.g. 1 week to 10 days, plants and trees would mostly cope and recover. However in both 2010/11 and 2016, water lay in a stationary state for several weeks and hundreds of shrubs and trees were lost - a/ because in 2010/11 of the uncleared drain running along the north side of South Boundary road which runs west into the Parkland Golf course and then north until it meets the concrete drain running west to McEwen Rd. This prevented water draining off the Ern Miles Reserve (formerly known as the South Boundary Rd. Drainage Basin) three times during the Summer of 2010/11. 	X(d)			

ltem & Response	iss	ue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
		eased west from the Fauna Park along the concrete drain to McEwen reding the capacity of the drain, much water overflowed into Grey Bo or many weeks.	x			
		shrubs, planted and cared for by our Group and many members of th ost and energy being spent on the work, were lost.	ie			
	from the impacts of flooding? How do yo	aration - How can your floodplain be better protected or managed u think flood warnings for your community could be improved? Are yo ne next flood? How could preparation be improved? What flood	u			
	Ern Miles Reserve, west and all the way t runs further west to McEwen Rd. Even at drainage water runs at a trickle along this	H need of a clean, right along its length, from the north-east corner of to the Parkland Golf Course until it reaches the concrete drain which t present the large dam in the Ern Miles Reserve is at capacity and s clogged drain all the way to the concrete drain. Flooding occurs on because of this clogged and uncleaned drain.				
		nuch encouragement and persuasion from our group and Kyabram's ection of this drain west of Lake Rd in about 2014. However this did no f the drain was not cleaned.	ot			
	If this above mentioned drain were clean alleviated.	ed much of the drainage problem in the Ern Miles Reserve would be				
	-	dam in the Ern Miles Reserve into the South Boundary Rd. drain also nteer group and lack financial resources to pay for its cleaning we buld clean it for us.				
	Both the above mentioned drains are in t face would be mitigated.	urgent need of cleaning and consequently the drainage issue that we				
	and protecting the cultural heritage and	siderations - How do you see the balance between managing flood risl environmental values of waterways and wetlands? versity within our wetlands and waterways.	s			

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	As I have stated many hundreds of trees and shrubs were lost in an area that has benefited greatly from our Landcare group's effort to revegetate over 30 ha of land within the Kyabram precinct. Numerous birds have reappeared in our town due to our planting program at Ern Miles Reserve and the Grey Box Reserve e.g. The Singing honeyeater, Red-capped robin, White-tailed warbler (gerygone), Golden whistler, Jacky winter, White-winged chough, to name a few. Revegetating with indigenous species brings about a great result! Well over 100 native bird species, a great indicator of the health of the environment, have now been recorded in the Ern Miles Reserve with only 40 species prior to revegetation in 2001.				
	Excess flooding, without sufficient drainage ruins this biodiversity.				
	Good drainage is vital to the health and vitality of wetlands.				
	Response 28				
	The lie of the land makes these areas vulnerable to overland flooding from localised storms. All the recommendations of the GHD report are yet to complete. Given the age of the GHD report and the release of Australian Rainfall and Runoff (2016) a review into flooding is considered a priority.				
	Local drainage works rests with the priorities of local government.				
	Shepparton – 10 th Feb 2017, 12 noon to 2pm				
	Improved flood information & better community information is welcomed				
29	Response 29		x		
	Access to fit-for-purpose flood information is important priority for the RFMS				
	Congupna – 10 th Feb 2017, 5pm to 7pm				
	Drain 12 Issues over blockage – South of Boundary Road. Recent flooding such as August 2016.				
30	Offer to meet landowners to explore that matter further.	x			
	Response 30				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	A site meeting was carried out with concerned community members. A background review revealed that approval for the works have been granted. It is therefore difficult to alter the works without the landowner's agreement. Also see item 70.				
	Alexandra – 11 th Feb 2017, 11am to 1pm				
	Concerned with potential impact of the proposed environmental floods in the Acheron River valley. That is, water backing up the Acheron River from the Goulburn River.				
31	Response 31				
	The environmental flow proposal is beyond the scope of the Regional Floodplain Management Strategy. However, the concern is noted and must be addressed as part of the constraints management strategy.				
32 EC	 Need to understand the impact of tributaries, not just the Goulburn River High annual rainfall is variable in nature and impacts flood forecasting Impact of Eildon Weir when full Community confusion with Constraints – need to make clear to community that this flood strategy is not from MDBA or associated with Constraints (states that Constraints proposal will cause a 1993 size flood to the area every 2 years) Believes that floodplain strategy work will be wasted effort if constraints project goes ahead Response 32 		x		x
	See Response 31 . Further, TFWS may require further rain and river gauge networks to take into account of variable rainfall. The Regional Floodplain Management Strategy's vision is to assist with flood resilient communities as opposed to the MDBA objective around environmental watering.				
	Environmental watering downstream of Eildon would see flows up to 9,500 ML/d (made up from natural flows with the balance from Eildon), which significantly lower than the 1993 flood of 48,000 ML/d (Check number)				
	Yea – 11 th Feb 2017, 3pm to 5pm				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Concerned with the lack of flood warning for the Yea valley and the township downstream.				
	Response 33				
33	Link the flood mapping to the new gauge in Yea. This is considered a priority. Such knowledge should be uploaded into the MFEP and Local Flood Guide.		x		x
	If flood warning prediction services are to be arranged, the telemetered river and rain gauging network would need to be augmented. This is considered a low to medium priority given that there is limited consequence in Yea. The impacts are largely limited to the Caravan Park.				
	Review the Minor flood level for Devlins Bridge. It is currently 1.8m and should be 1.5m.				
	Response 34				
34	The initial review of available flood photography indicates that there is merit is reviewing the Minor Flood Class level.		x		
	The Bureau of Meteorology has recently prepared standard forms that allows a request for such a change. This will be looked into by the GBCMA and Murrindindi Shire Council.				
	The AAD should consider the cost of on-farm damage including fencing and pasture, loss of trees, erosion of banks.				
35	Response 35				
	The risk assessment is a first-cut rapid approach to set regional/statewide consistent priorities and has damage estimates for agricultural losses.				
	Flood risk to dwellings in the township of Reedy Creek is potentially an issue.				
36	Response 36	x		х	x
	Noted. This is part regional study along Dabyminga Creek.				
37	Reduce the risk of flooding by reducing environmental flows to in-stream flows under the Constraints Strategy.				
57	Response 37				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Environmental flow proposal in beyond the scope of the Regional Floodplain Management Strategy. However, the concern is noted and must be addressed as part of the constraints management strategy.				
38 WL	 Believes Yea river gauge flow level of 1.5 represents actual minor flood level, not the current 1.8m level at which a minor flood level warning is issued (photos supplied of flooding at lower gauge height) Supplied a number of photos of flooding in 2010 with notes as to times/dates/gauge heights – believes flooding in Goulburn River has significant impacts upstream in tributaries and that impacts of flooding at various gauge heights are under estimated in official records/maps. Response 38 		x		X
	See Responses 34 and 37.				
	Tungamah – 13 th Feb 2017, 10am to 12noon				
	Warning is provided (~2 days) but it is only by word of mouth. There is a lack of warning and information on ABC radio about Boosey Creek.				
	Despite the potential for good warning times, in 2012 there was not much warning time for doing sand bagging. Some people in town were given only 1 hours warning to protect houses in 2012.				
39	Major issue with Tungamah is complete isolation for 48 hours in all directions, i.e. the town becomes completely isolated.	x	x		х
	Warning is important to the town and for the emergency response.				
	Response 39				
	This town is considered a high priority for all four themes to build flood resilience.				
	Rural drainage is a problem after the flood. Causeways have been built up and culverts are sometimes blocked (3 Chain Road recently).				
40	Elvin Street, Tungamah pipes recently blocked and causing flooding issues.	X			
	Response 40				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	These need to be reviewed as part of a floodplain management study.				
41	Banks and levees in the landscape push water onto other landholders and reduce flood storage. Response 41				
42	Refer to Response 19 . Wilby and Almonds soil conservation scheme was never completed. Currently ends at Creek Road. Lack of drainage downstream of this point.				
	Response 42 Generally local drainage is beyond the scope of the Regional Floodplain Management Strategy.				
	The weir in Tungamah was recently turned into a permanent structure and that influences flooding. In floods before 2012 the boards were pulled out of the structure prior to the flood and this reduced levels in town.				
43	The rail line is important for ponding/ storing flood water and protecting the town. Response 43	x			х
	These need to be reviewed as part of a floodplain management study.				
	Tungamah sewerage infrastructure - pumping stations and treatment plant are probably at risk of flooding. Need to ensure information is provided to NE Water.				
44	Response 44				x
	These need to be reviewed as part of a floodplain management study. Flood information would be shared with the asset owners.				
45	Milk Bar and Post Office in Tungamah are the best places to notify the community of public meetings. Need to consider putting notices up in towns for next meetings.				
45	Response 45				
	Noted. Seek to utilised for future meetings				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Drainage once the flood is over is a major problems.				
	There were five minor floods last season. Levee around house and sheds have been constructed in rural areas. Local floodplain development plans allow for ring levees to be constructed to protect homes. Moira planning scheme may not have this.				
	Response 46(a)				
	Flood recovery response may assist with the impacts of floods during their recession.				
	It is usual practice to allow ring levees around a home if over floor flooding is evident.				
	Emergency response- if an emergency alert is set off will trigger the siren at the local CFA shed to inform people about sand bagging. A lot of the people in town are unaware where the relief centre/ evacuation centre is				
	Response 46(b)				
46	Centres will be established depending on the nature of the emergency. Circumstances will dictate where centres will be established.	X	x	х	X
	It would be better to have flood warning services for Tungamah. An upstream gauge of the town would be better. A suggestion was made at the confluence of Sandy and Boosey Creek.				
	Response 46(c)				
	Warning is considered a high priority.				
	Could be linked with operations around permanent levees and/or temporary levees, sandbagging etc. through emergency response. The greater the warning time means the better opportunity for the community response.				
	As part of a total flood warning system flood and floor level data can be linked to gauge heights.				
	Tungamah has a sewerage scheme (sewerage pumps at Alvin St and Barr Streets). Failure of the ponds following a flood and associated problems with contamination and health problems. Critical infrastructure is an issue.				

ltem & Response	issue / location / comments	Mittigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Response 46(d)				
	These need to be reviewed as part of a floodplain management study. Flood information would be shared with the asset owners.				
	Comments from the community meeting suggested the flood overlays aren't that accurate as its flood extent was "undergone".				
	Response 46(e)				
	These needs to be reviewed as part of a floodplain management study.				
	Strathmerton – 13 th Feb 2017, 1.30pm to 3.30pm				
	A lot of irrigation channels have been piped due to the connections project and this is likely to change the extent of flooding.				
47	Response 47				
	GMW has been working with both the Goulburn Broken and North Centre CMAs to assess non-back irrigation channels across the Goulburn Murray Irrigation District to ensure that the nature of flooding remain is not unduly altered.				
	Strathmerton was flooded in 1975 due to the levee breaching at Koonoomoo. The Koonoomoo Road was closed for over a fortnight.				
48	Response 48				
	Noted and has been documented.				
49	NSW levees failing in the October 2016 potentially redirected 65,000 ML/day into NSW and helped prevent a major levee failure in Victoria. NSW levees are being built up in response to the recent failures – funding announced by Barnaby Joyce.	x			
	Response 49				
	Noted and damaged levees may be repaired following flood.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Emergency response and need for the evacuation for campers on the Ulupna Island. The threat of a levee breaching/flooding closing Ulupna Bridge Road.				
50	Response 50				x
	Parks Victoria played a major role in managing campers. The MFEP may be reviewed in terms of Ulupna Bridge Road.				
	Better management of the levees is the key strategic flood management issue for the Strathmerton/Murray River area.				
	Response 51				
	The potential management arrangements for rural levees have been documented in the Victorian Floodplain Management Strategy (VFMS).				
	However, some commentary was made as follows:				
51	 Levees for urban centres has been clear with the lead agency being local government Rural levees- private benefits as been the logic. Now the Victorian Floodplain Management Strategy indicates that all the beneficiaries play are part (not just private). This could include the broader community, VicRoads, LGAs etc. Councils do not have the capacity to manage rural levees. There would be many things that would need to be considered. There are serious questions about the condition of the existing rural levees. Difficult to prioritise works. Question around legal liability is a major issue because of the unknown condition of the levels. Council would be looking for external funding support. The Road Management Act allows for the creation of a road management plan, which gives some parameters around what can be done based on available resources/priority. The VFMS is suggesting the used of the Water Act process known as Water Management Scheme. DELWP are reviewing legal liability. Levee permitting process for individuals/groups is now available through the GB CMA for levees on Crown land. This is strictly for maintenance of levees. This is now on the GBCMA's website. 1996 a levee audit was undertaken along the Murray levees. 	X			

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Concerns were expressed in the huge community effort in defending the levee. On this basis the community group believe that there would be interest in management arrangements.				
52	Response 52	x			
	The potential management arrangements for rural levees have been documented in the Victorian Floodplain Management Strategy (VFMS). Refer to item 51 for further response.				
	A number of weak spots/issues with the PWD levees that were issues in October 2016, including Ulupna Island, have not been fixed.				
53	Response 53	x			
	There are Natural Disaster Relief Arrangements whereby failed infrastructure may be repaired. This is usually done via a sponsoring authority e.g. the lower Goulburn levees were repaired via the local government on behalf of the community. The Goulburn Broken CMA will raise this with the CEOs.				
	Yarroweyah and Strathmerton should be on the prioritisation list for towns in the strategy.				
54	Response 54		x	x	x
	These towns have been included in the Murray River Regional Floodplain Management Study.				
	Question about the lack of notice of community meetings: how can that be done better. Better use of posters in shops.				
55	Response 55				
	Noted. Need to improve engagement.				
	Asked questions about the use of drones in emergency response				
56	Response 56				x
	VICSES are using drones.				
57	Raised issues with the operating rules of Hume Weir. Need to consider a concept of declaring a "wet year". Request for better operating rules.				x

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Response 57				
	Floods can occur at any time of the year and as such there is no flood season or no ability to declare a wet year.				
	Target filling curves are applied to manage storage operations. Storages are primary used for the provision of water responses. There is some flexibility in the operations with rainfall forecast. (check with GMW)				
	Nathalia – 13 th Feb 2017, 5pm to 7pm				
58	 Sandbagging concerns as follows: More communication – last floods there was poor information at north of Barmah, near the Murray. Told 2 weeks before that the flood was coming, bought sand bags and sand. Sand bags could not be sent back to NSW. Landholder between Numurkah and Walshs Bridge - sand bags were not available in Numurkah when required. 2016 flood – public meeting in Cobram said there was only 5,000 sandbags available from VICSES. Important to have them available early so people don't have to work 24 hours a day. Sandbags were made available too late in Barmah on a Sunday night after volunteers had left. Response 58 The communication and coordination of sand, sandbagging, resourcing is complex. Need to rely on multiagency approach and good ICC communications. Understand that communication can be improved. Always seeking to improve the Municipal Flood Emergency Plan. 				x
59	Potential to improve flood mapping and warning for the lower Broken Creek, below the Nathalia town study. Response 59 There are flood warning services to Nathalia that can be used downstream of Nathalia. Flood mapping extends to Narioka linked to the Nathalia gauge. Further mapping is considered a low priority in this particular point of time.		x		x
60	Showing the flood mapping to the community may help reassure them.		x		

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Response 60				
	Agreed. Mapping would assist with flood resilience, but would need to be fit-for-purpose.				
	A priority to do a flood study on the Murray River downstream of Ulupna Creek.				
61	Response 61	x	x	x	x
	Agreed. This work is required particularly if the question of levee management is to be addressed. Otherwise this is a low priority at this particular point of time.				
	Identify weak links in the PWD levee and the potential consequences (flood extent) of such a failure for the public to understand the risk. Otherwise there is a lot of unnecessary stress.				
62	Response 62		x		x
	Some of this information does broadly exist but is complex to understand. The Water Technology – Rural Levee Assessment Report will be placed on to GB CMA's website.				
	On Broken Creek in 2012 a lack of information caused a lot of grief, need accurate information at Numurkah.				
63	Response 63				x
00	Significant improvements have been made to the Municipal Flood Emergency Plan. Furthermore, the Bureau of Meteorology is investigating a new flood prediction service for Numurkah.				
	Landholder highlighted the need for a river gauge at Yambuna Bridge.				
64	Response 64		x		
	Flood warning are provided to McCoy Bridge and the need for further river gauge needs to be explored.				
65	The beneficiaries for levees include the infrastructure adjacent the levee, including the major roads, VicTrack, Telstra, Environmental Water Holder, Power infrastructure.	x			
	Response 65				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	The potential management arrangements for rural levees have been documented in the Victorian Floodplain Management Strategy (VFMS) that includes the beneficiary pay principle. Refer to item 51 response for further background reading.				
	Need to access local knowledge to inform the flood plan and monitor flood heights/extent.				
	Response 66				
	Local knowledge, during both flood studies and the preparation for floodplain management plans, is considered paramount.				
66	At the outset of significant rainfall, and during major floods, the use of local "flood observers" is being addressed by the Control Agency for flood which is VICSES. Such arrangements may add significant intelligence, particularly where gauge networks are lacking.		x		x
	Flood inquiry acknowledged the importance of local flood knowledge. Such knowledge is built into the Municipal Flood Emergency Management Plan.				
	Concern that environmental flows in combination with rain events will cause flooding.				
67	Response 67				
	This is a matter of operation procedures for managing environmental flows which is beyond the scope of this Regional Floodplain Management Strategy.				
	2012 flood was bigger than 1993. Authorities need to refer to historic information. Raised issues with the way the 2012 flood was managed. Flood awareness local information and input is critical				
68	Response 68		x		х
	Flood inquiry acknowledged the importance of local flood knowledge. Such knowledge is built into the Municipal Flood Emergency Management Plan.				
60	Four critical issues:				
69	1. Information	X	X	X	X
	2. communication				

ltem & Response	issue / location / comments	Mittigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	 Authorities take more note of local knowledge Who will implement the issues Response 69 				
	The above, to a large extent has been delivered through floodplain management plans and its implementation. The Regional Floodplain Management Strategy is seeking to prepare an ongoing three year rolling plan to deliver flood mitigation, total flood warning systems, land-use planning and municipal flood emergency plan to make community flood resilient. The Victorian Floodplain Management Strategy sets out accountabilities for delivery.				
	Mansfield – 18th Feb 2017, 11am to 1pm				
	Big flood risk above Jamieson and Goulburn – what about a risk assessments on the camping grounds. Howqua river has ability to rise pretty quickly, e.g. of campers having problems. Response 70				
70	Camping grounds are managed by Parks Victoria. There would be some merit in establishing flood levels within the camp grounds. This can be built into the regional flood study. Works has been done in this space for fire. Limited communication in the camping sites.		x	x	x
	EM has Camp Sites for fire evacuation in GIS that could be useful for the MFEP				
	Mansfield needs targeted forecasting information (2011 event is an example). Individuals that need rainfall information are likely to already have it built in resilience.				
	Response 71				
71	Flood warning systems need to be fit for purpose. E.g. relying on rainfall information maybe one approach suitable for Mansfield rather than an expensive rain and river gauge network. This example would be different if there were dozens of over floor flooding problems.		x		х
	Weather underground stations (ground) – created by weather enthusiasts could be a good source of unofficial rainfall data, particularly during major storms. Also CFA Shed Weather gauges.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	Maindample drainage issue, suggested two or three houses could be impacted by flooding				
72				х	x
	Response 72				
	Noted. Worth doing a visual inspection. There is no ground level information for this area.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	 Flood impacts - How does flooding across the floodplain affect you and your community? Does flooding impact on your livelihood such your home, business and/or agriculture use? The flooding of Guilfus Creek has caused a lot of paddock damage and caused cattle to get sick due to water hanging around longer than usual and grass won't grow where water laid for a long time. 				
	2. Flood protection, management and preparation - How can your floodplain be better protected or managed from the impacts of flooding? How do you think flood warnings for your community could be improved? Are you and your community well prepared for the next flood? How could preparation be improved? What flood information would be most useful? The flooding would be better managed if the outfall of Guilfus Creek was made so it starts to run as soon as the water gets to the drainage channel rather than having to build up and rely on it being released into the drainage channel manually.				
73	 Environmental and cultural heritage considerations - How do you see the balance between managing flood risks and protecting the cultural heritage and environmental values of waterways and wetlands? (nil) 			x	
FF	4. Other comments As there has been a permit for the structure at the end of the creek. If it can't be made bigger and automated or removed to drain all the upstream properties, approx. 1000 acres. Suggest clean out the drain on left hand side of Boschetti Road going north and bring the water in at the front of the bank as there is a pipe across the road. All that needs doing is earthworks as the work that has been done will not fix the problem this may help a little.				
	Response 73				
	Refer to item 30. Further Greater Shepparton City Council is actively managing this complex matter with the local community.				
74	1. Flood impacts - How does flooding across the floodplain affect you and your community? Does flooding impact on your livelihood such your home, business and/or agriculture use?	x			
FF	We own a farm at Strathmerton that borders the Ulupna Creek. Approx. 100 acres of our farm was under water in the flood as this could not get into the creek. Loss of crop was a major issue.				

ltem & Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	2. Flood protection, management and preparation - How can your floodplain be better protected or managed from the impacts of flooding? How do you think flood warnings for your community could be improved? Are you and your community well prepared for the next flood? How could preparation be improved? What flood information would be most useful? The levee along the Ulupna Creek needs to be topped up in a number of places. The flaps on some pipes need to be fixed up to keep the water in the creek. The levee from Ulupna Island road downstream needs topping up to the junction of Ulupna Creek to Murray River junction.				
	3. Environmental and cultural heritage considerations - How do you see the balance between managing flood risks and protecting the cultural heritage and environmental values of waterways and wetlands? You must protect farmers from flood over environmental. The water is flooding Barmah Forest more now that 20 years ago, not always a benefit to the environment.				
	4. Other comments (nil)				
	Response 74				
	The Victorian Floodplain Management Strategy sets out the framework for existing mitigation infrastructure (namely levees). This includes a permitting process for individuals or the collection of individuals to carry out maintenance works. The Victorian Floodplain Management Strategy sets out policy about the three tiers of government will on invest in existing flood mitigation infrastructure if the investment criteria can be met. Given the "primary benefits" (VFMS wording) relate to private land, and given a strong reluctance of local government to manage such infrastructure (due to legal liability, particularly as the standard of levees are poor), then the levees may be maintained privately under the permitting process (if on private land).				
75 EC	Our property borders the river roughly between Koonoomoo and Strathmerton and the main issue which I think should be dealt with is the general maintenance of the banks which have been allowed to deteriorate to such a state that they couldn't cope with a small event such as October's flood. A more specific issue is the weir on the Sheepwash Creek just prior to where it flows into the Ulupna Creek.	x			
	During the flood, while we were frantically sandbagging the levees on both sides of the Ulupna Creek we were flooded from the South side of the bank by water which flowed up the Sheepwash from the Ulupna creek and onto our land. This resulted in				

Item & Response

Response	issue / location / comments	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
	about 100ha of pasture being inundated and 60ha of crop resulting in the loss of about 100t of wheat and 50t of barley. My proposal is to alter the structure on the Sheepwash to allow drop boards to be put in to prevent water from the Ulupna Creek backing up when the river rises above 100,000ML/day. At the moment there is nothing stopping water flowing up the Sheepwash from the Ulupna and flooding our property.				
	I can't see there being any problems with preventing the creek backing up at Farrell's Rd. This also removes the pressure on the levees upstream of the weir and the need to maintain them (not that anyone does this now). I have attached a photo of the weir.				
	Response 75				
	There is a long history associated with this structure. The structure built on Sheepwash Creek controls further propagation of a head cut and the function of the bed control. The invert on the downstream side of the creek is lower compared with the upstream side. As such the structure prevents backwater flooding for minor Murray River flow by virtue of the height of the upstream invert. Larger floods create further backwater flooding over lands as described in the above comments.				
	As part of the works, an flood easement was created over the land – check files				
	The Goulburn Broken CMA would not endorse the proposal of block this backwater due to unintended consequences, with doing detailed studies into third party impacts.				
	In terms of maintenance of levees the comments provided in Response 74 are relevant.				

Appendix J: DELWP's Rapid Appraisal Methodology

Key data requirements

The data required to estimate damages using DELWP's rapid appraisal of flood risk methodology is publicly available as explained in **Table J-33** and includes flood hazard data and asset datasets.

Table J-33: Datasets used in the rapid appraisal of flood risk methodology

	Туре	Source	Layer Name
	Land use	Vic Map Catchments (obtained from the DEPI CSDL data)	Varies with Region
Asset Datasets - used to	Rural buildings	Vic Map features of interest (FOI)	BUILDING_POINT.shp
identify which assets are at risk of inundation.	Cadastre	Vic Map Properties (VMPROP) (obtained from the DELWP CSDL data)	V_PROPERTY_MP.shp
	Planning Zones	Vic Map Planning zones (VMPLAN)	PLAN_ZONE.shp
Flood Hazard Data - required to determine the	100 year flood extent (indicative)	Victorian Flood Database	extent_100yr_ari.shp
probability and extent of inundation.	Floodway	Victorian Flood Database	floodway.shp

These data sources are used to determine the inventory at risk and assess flood damages using a loss probability curve as explained in the following section.

Approach

The rapid appraisal of flood risk methodology is comprised of three core tasks:

- 1. Establishing management units
- 2. Quantifying assets at risk
- 3. Quantifying flood damages and developing risk metrics.

1. Establishing management units

The region under the management of a CMA can occupy a very substantial area and it is sensible to consider flood damages and floodplain management measures for sub-regions. A CMA's region usually consists of the catchments of several rivers and smaller streams, and will contain a varied mix of urban and rural areas with differing characteristics. It is thus necessary to define smaller management units that allow the rapid appraisal to be applied systematically.

How management units are established is a matter of judgement for the analyst and those who are formulating management strategies and programs. The critical task is to define study areas which allow flood risk to be assessed in a manageable and systematic way. The broad criterion that should be used to guide the definition of study areas is that areas where the effects of a given cause are felt should be combined into a single study area.

As a general guide:

• Urban flooding is separated from rural flooding. An individual town may be further divided, depending on whether flood mitigation is best managed separately in discreet management units.

- Rural flooding should be divided into practical management units where the assets at risk and the available flood warning time are comparable.
 - Rural study areas should be determined separately where significant land-uses (e.g. intensive animal or horticultural industries) are identified
 - Rural study areas should commence (or terminate) at a major waterway confluence where additional inflows and/or stream capacity can result in substantial changes in the annual exceedance probability of a single rainfall event
 - Rural study areas should be separated where flood warning is substantially different.
 Flash flooding (less than 6 hours), should be assessed separately from areas with between 6-12 hours of warning, and areas with greater than 12 hours.

Similarly, with regard to the strategic output from the appraisal, the analyst may wish to consider how the findings can be communicated most effectively to engage with affected communities. The following may be taken into account:

- Local Government Area (LGA) boundaries defining management units along LGA boundaries may be used to better rationalise local government contribution to flood risk mitigation.
- Communities of interest where a cohesive community group are reflected in a homogenous geographic unit, support for a specific risk mitigation strategy may be leveraged.

2. Quantifying assets at risk

Flood damages can be grouped as follows:

- Direct (tangible) damages comprise the physical impact of the flood, for example, damages to structure and contents of buildings, agricultural enterprises and regional infrastructure.
- Indirect (tangible) damages comprise losses from disruption of normal economic and social activities that arise as a consequence of the physical impact of the flood; for example, costs associated with emergency response, clean-up, and disruption to transport and commerce.
- Intangibles, or 'non-market' impacts, comprise losses which cannot readily be quantified in monetary terms (since market prices cannot be used). For example, loss in biodiversity, physical injury or increased stress levels for residents following a major flood event.

For the purpose of DELWP's rapid appraisal of flood risk methodology, only the following damages are quantified.

- Direct damage to buildings and contents (residential and non-residential)
- Direct damages to agriculture
- Indirect damages, resulting from the cost of emergency response (measured as a % of direct damage to buildings).
- Building and contents

The assumptions for determining the number of urban and rural building assets at risk are shown in **Table J-34**.

Table J-34: Property at risk assumptions

	Urban Areas	Rural Areas			
Dataset used	Vic Map properties	Vic Map features of interest			
Property count Assumptions	For a property to have a building and/or be suited for development, the cadastre must be > 100 m2 and < 10,000 m2	One rural building is inundated for every two FOI (points) inundated			
Planning	Properties (buildings) were classified based on the planning zones outlined Residential – TZ, GRZ, GRZ1, LDRZ, MUZ, NRZ1				
assumptions	Commercial – C1Z, C2Z				
	Industrial – IN1Z, IN2Z, IN3Z				

• Agriculture

The digital flood datasets are overlayed on the land-use dataset to produce estimates of the exposure of each land-use to inundation. Data estimating the duration of inundation is also required.

3. Quantifying flood damages and developing risk metrics

• Damage to buildings

State-wide depth grids are not available with the flood extents in the VFD. Therefore in developing assumptions for the depth of flooding across the flood extent, an analysis was undertaken of 30 Victorian depth grids. The distribution of depth of flooding was used to determine unit damages for residential, commercial and industrial buildings (Table J-35).

Table J-35: Distribution of flood depth by flood annual exceedance probability (AEP)

AEP	Flood depth above ground (m)							
ALP	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	0.8-1.0	1.0-1.2	>1.2	Total
10%	49.4%	40.9%	5.7%	1.3%	0.5%	0.2%	2.0%	100.0%
1%	29.4%	39.1%	17.2%	5.3%	2.3%	1.2%	5.4%	100.0%

Source: DELWP depth grids from 30 Victorian flood studies (Aither 2015)

Residential buildings

Unit damages for each flood extent were calculated using depth damage data that is provided by the NSW Office of Environment and Heritage (OEH)¹¹. Damage assumes generic losses for a single storey slab/low set residence. The calculation is shown in **Table J-36**.

¹¹ A file from which residential damages can be adjusted for local conditions can be found at <u>http://www.environment.nsw.gov.au/floodplains/StandardFloodplainRiskManagement.htm</u>.

AEP	Flood Depth	% distribution	Damage	Weighted damage
10%	<-0.1	52%	\$10,921	\$5,690
	-0.1-0.1	42%	\$29,159	\$12,358
	0.1-0.3	4%	\$67,445	\$2,599
	0.3-0.5	1%	\$73,685	\$774
	0.5-0.7	0%	\$79,924	\$280
	0.7-0.9	0%	\$86,164	\$75
	>0.9	0%	\$100,000	\$175
		100%		\$21,951
1%	<-0.1	30%	\$10,921	\$3,298
	-0.1-0.1	40%	\$29,159	\$11,780
	0.1-0.3	18%	\$67,445	\$11,886
	0.3-0.5	5%	\$73,685	\$3,392
	0.5-0.7	2%	\$79,924	\$1,702
	0.7-0.9	1%	\$86,164	\$947
	>0.9	4%	\$100,000	\$3,951
		100%		\$36,955

Table J-36: Weighted damage calculation per property (residential, commercial and industrial) by flood frequency

The weighted unit damages for each flood extent are therefore:

Floodway - \$21,951

1% AEP flood extent - \$36,955

These weighted unit damages are then applied as part of DELWP's rapid appraisal of flood risk methodology to assess the damage to residential buildings within each flood extent. For example, where 10 properties (identified using Vic Map data) were inundated within the floodway, then residential damages were estimated at \$210,000. Furthermore, the damages for 100 properties inundated by the 1% AEP flood event were assessed at \$3,700,000.

• Non-residential buildings

Damage for commercial and industrial buildings are estimated using the United States of America's Federal Emergency Management Agency (FEMA) relative depth damage curves. These curves are relative curves, meaning that they specify damage as a percentage of building replacement value (BRV). Given that no data is available for BRV, the following assumptions were made (**Table J-37**).

Table J-37: Assumed building replacement value for commercial and industrial buildings

	Building footprint (m ²)	Unit cost (\$/m²)	BRV (\$)
Commercial	250	\$1,400	\$350,000
Industrial	1,000	\$1,200	\$1,200,000

The BRV for industrial and commercial buildings is calculated by multiplying assumed building costs (Rawlinsons 2012) by the assumed building footprint of 1,000 m². The weighted unit damages for each flood extent that are calculated are shown in **Table J-38**.

Table J-38: Weighted average damages for commercial and industrial buildings

Flood extent	AEP	Commercial	Industrial
Floodway	10%	\$5,584	\$8,489
1% AEP flood extent	1%	\$18,362	\$55,352

Damages to Agriculture

The assumptions for assessing damages to agriculture are summarised in Table J-39.

Table J-39: Estimated agricultural losses

				Land	Total		
	Unit	Annual Damages	Establishment Costs	Clean- up and Rehab	Less than 5 days inundation	More than 5 days inundation	
Dryland pastures	\$/ha	-	\$90	\$40	\$40	\$130	
Dryland broadacre crops	\$/ha	\$100	\$60	\$40	\$140	\$200	
Orchard	\$/ha	\$4,600	\$5,000	\$500	\$5,100	\$10,100	
Grapes	\$/ha	\$2,300	\$1,500	\$500	\$2,800	\$4,300	
Vegetables	\$/ha	\$9,500	-	\$500	\$10,000	\$10,000	
Irrigated pastures	\$/ha	\$110	\$430	\$40	\$150	\$580	
Irrigated broadacre crops	\$/ha	\$220	\$220	\$40	\$260	\$480	

When certain perennial land-uses are inundated for longer than 5-7 days, waterlogging causes plant death and it becomes necessary to re-establish the plant species. The number of "threshold days" varies according to the land-use and time of year, but for modelling purposes is assumed to be 5 days.

DELWP's rapid appraisal of flood risk methodology assumes that no losses in production are attributed to flooding of dryland pastures less than 5 days. In addition to losses of production, flooding will generally require expenditure to repair erosion, repair fences, remove debris, rocks or silt deposits from fields, and replace soil. The following clean-up costs are added to production losses:

- pastures and broadacre crops, \$25 per hectare
- horticulture, \$350 per hectare.

No assumptions for livestock losses are made given the typically long warning times in Victoria.

Indirect damages

For the purpose of DELWP rapid appraisal of flood risk methodology, the main indirect tangible losses as a result of a flood event are the cost of the emergency response and repair. This includes the cost of clean-up, evacuation and emergency response.

Limited data is available from where indirect impacts can be quantified. For this reason, it is typical to account for all indirect impacts as a ratio of "direct" damage. Indirect damages are estimated as 25% of direct damage to both urban and rural buildings.

Using the loss probability curve

Flood risk is calculated using a loss probability curve. The curve plots damages against their probability of occurrence. The loss probability curve is based on three known points:

- Damages based on areas of inundation shown on the flood maps for the 1% AEP flood extent;
- Damages based on areas of inundation shown on flood maps for the floodway area (assumed to represent a 10% AEP event); and
- The flood event where damages are judged to commence (20% AEP event is assumed).

As demonstrated in **Figure J-15** below, the large damages from low probability events are combined with lower damages from more frequent flood events using data for probability and calculated damage.



Figure J-15 Loss probability curve

The integral, or area under a loss probability curve, represents the annual average damage (AAD) resulting from all flood events over a long period of time. This risk metric is used to assess the benefit of mitigation options.

Population at risk

The population at risk is estimated by assuming the average number of people living in an inundated house. The population at risk is estimated by multiplying 2.6 residents per household (derived from the Australian Bureau of Statistics) by the estimate of buildings affected during each flood extent.

Developing comparable risk metrics

Given differences in the size of each study area, it is necessary to develop consistent flood risk metrics so that damages can be compared. There is no one risk metric that is likely to best capture the importance of flood risk within a study area.

The DELWP flood risk assessment methodology assesses flood risk within each management unit using the following metrics:

- Density of damages (measured as the ADD divided by the AEP of hundred year flood event)
- Absolute risk (the absolute size of the AAD from the cost-probability curve)
- Population affected (measured as the AAPA divided by the population of the town)

A summary of each metric and its relative flood risk severity ranking is provided in Table J-40.

Table J-40: Comparable risk metrics used in the rapid appraisal of flood risk methodology

Flood Risk Severity	Density of Flood Damages ¹	Absolute risk ²	Population affected ^{3,4}
0	No Data	No Data	No Data
1	0	0	0
2	\$500	\$100,000	4
3	\$1,000	\$200,000	10
4	\$2,500	\$500,000	30
5	\$5,000	\$1,000,000	60

Notes: 1. Measured as the AAD divided by the area of inundation for the 1% AEP flood extent.

2. The absolute size of the AAD.

3. Measured as AAPA divided by a town's population (multiplied by 1,000).

4. No population has been determined for "rural" study areas. They are given a score of 1.

Other things to consider

- The rapid appraisal of flood risk methodology does not capture:
- The presence of critical infrastructure (roads, hospitals, utilities)
- More at risk populations (retirement homes, hospitals etc.)
- Flood risk where flood hazard data is absent
- The potential risk to life (where flood depth and velocity is high for flash flooding)
- The potential for regional growth (i.e. need for new planning overlays).

Appendix K: TFWS assessment Tool methodology

The process followed by CMAs and Melbourne Water included:

- Assess and rank regional flood risks (see Chapter 3:);
- Determine existing TFWS service levels;
- Identify those locations in need of TFWS improvements;
- Identify a scope of works that will deliver the improvements sought for each identified location; and
- Establish priorities for improvements.

Establishing Regional Flood Risk

DELWP has developed a flood risk assessment methodology that can be used to assess and rank regional flood risks (refer to Section 4 of the VFMS and the Guidance Notes for "Using DELWP's Rapid Appraisal Methodology", "Identifying important regional and community infrastructure"). It is applied at the location and river reach scale and delivers relative risk rankings for different locations based primarily on annual average damages and the population at risk. More specifically, the methodology focuses on the social impacts of flooding at different locations in the region and uses available flood and asset information to assess flood likelihood and associated consequences. Secondary issues include the potential for key infrastructure to be damaged or disrupted by flooding (up to and including the 1% AEP event), the relative vulnerability of the population at risk, and any access or egress issues that may limit safe evacuations.

The TFWS Service Level Framework

A TFWS service level can be thought of in terms of the complexity or completeness of the information that support that particular element of the TFWS and is provided (or available) to an agency and / or community before and during a flood.

The TFWS Service Level Framework comprises five (5) service level tiers – from zero (0) to four (4) where Tier 0 designates a simple or basic service level and Tier 4 a complex / comprehensive level of service.

TFWS element service levels are detailed in Attachment A. The descriptors for each TFWS element deliver a broad level narrative of the features / level of development / sophistication expected to be present for each of the service level tiers. Service level tier descriptors are also provided for the sub-factors with due regard for what is measurable, scalable, and relevant and appropriate. The descriptors facilitate a quantifiable (deterministic) discrimination between the service level tiers.

It is generally not a trivial task to determine service levels for either a TFWS element or the system as a whole by considering the Framework descriptors alone without using the Tool. It is also likely to result in some inconsistencies as well as a subjective bias, particularly in the case where a number of sub-factors contribute to a service level score. It is therefore suggested that the service level descriptors are used to:

- Confirm Tool results (i.e. do Tool results match expectations and if not why not);
- Inform discussions about an existing TFWS and its elements;
- Verify or adjust perceptions of the service level being delivered by an existing TFWS, or its elements;
- Guide adjustment of Tool results if and as required; and

• Inform discussions and decisions regarding improvements to or development of a TFWS.

The TFWS Assessment Tool

The current version of the TFWS Assessment Tool is described in the Tool Version 4A User Manual. The User Manual is available from DELWP.

Data Collection Network

The data collection network refers to the detection, collection and transfer of rainfall, river heights and streamflow data. This data supports other activities associated with the other building blocks of the Total Flood Warning System. The more extensive the data network and the more automated the data collection processes, the higher the value of the data collection element within the total system. Typically, locations with a greater flood risk benefit from a higher DCN service level.

Service		TWFS Assessment Tool A Sub factors								
Level	Service Level Descriptor	A1 Rain Gauge Sub factor	A2 Event Reporting RG Sub factor	A3 Stream Gauge Sub factor	A4 Rated Sites Sub factor	A5 Elevation Sub factor #1	A6 Elevation Sub factor #2	A7 Distance Sub factor #1	A8 Distance Sub factor #2	
0	No real time rainfall or river data available. Manual gauges only, if any.	Manual rain gauges only, if any.	No event reporting rain gauges in catchment	Manual stream gauges only within catchment, if any.	No rated sites in catchment.	No (or negative) elevation difference between the most remote TBRG and the first forecast location.	Large elevation difference between the closest forecast location and the at- risk location (or reach) or the forecast location is downstream of the at-risk location (or reach).	No (or negative) distance between most remote TBRG and first upstream forecast location.	Large distance between at-risk location (or reach) and closest forecast location or forecast location is downstream of at- risk location (or reach).	
1	Real time rainfall and river height data available from sites upstream of the at- risk location within the basin.	Few rain gauges in the catchment.	A low number of event reporting rain gauges in catchment. No event- reporting rain gauges at the at- risk location or reach.	A low number of stream gauges within catchment.		Little elevation difference between the most remote TBRG and the first forecast location.	Medium elevation difference between the closest forecast location and the at- risk location (or reach).	Very little distance between most remote TBRG and first upstream forecast location.	Medium distance between at-risk location (or reach) and closest upstream forecast location.	

Service			TWFS Assessment Tool A Sub factors								
Level Tier	Service Level Descriptor	A1 Rain Gauge Sub factor	A2 Event Reporting RG Sub factor	A3 Stream Gauge Sub factor	A4 Rated Sites Sub factor	A5 Elevation Sub factor #1	A6 Elevation Sub factor #2	A7 Distance Sub factor #1	A8 Distance Sub factor #2		
2	Real time and rainfall river height data available from sites upstream of the at-risk location within the basin. River level information available for the agreed forecast location during rain / flood events.	Some rain gauges in catchment, including upstream. No gauges at the at-risk location or reach.	A low number of event reporting rain gauges in catchment. No event- reporting rain gauges at the at- risk location or reach.	A low number of stream gauges within catchment including a non- telemetered gauge at the at- risk location or reach.	There is a rated site downstream of the at-risk location or reach.	Low to medium elevation difference between the most remote TBRG and the first forecast location.	Small to medium elevation difference between the closest forecast location and the at-risk location (or reach).	Small to medium distance between most remote TBRG and first upstream forecast location.	Small to medium distance between at-risk location (or reach) and closest upstream forecast location.		
3	Real time and rainfall river height data available from sites upstream of the at-risk location within the basin. Permanent telemetered river level gauge operational for the agreed forecast location.	Some rain gauges in catchment, including at the at- risk location or reach and upstream.	A moderate number of event reporting rain gauges in catchment including upstream of the at-risk location or reach. No event- reporting rain gauges at the at- risk location or reach.	A moderate number of stream gauges in the basin. Permanent telemetered stream gauge at the at-risk location or reach.	There is a rated site upstream of the at-risk location or reach, but the at-risk location (or reach) itself is not rated.	Moderate to high elevation difference between the most remote TBRG and the first forecast location.	Very small elevation difference between the closest forecast location and the at- risk location (or reach).	Large distance between most remote TBRG and first upstream forecast location.	Very small distance between at-risk location (or reach) and first upstream forecast location.		

Service		TWFS Assessment Tool A Sub factors								
Level	Service Level Descriptor	A1 Rain Gauge Sub factor	A2 Event Reporting RG Sub factor	A3 Stream Gauge Sub factor	A4 Rated Sites Sub factor	A5 Elevation Sub factor #1	A6 Elevation Sub factor #2	A7 Distance Sub factor #1	A8 Distance Sub factor #2	
4	Real time and rainfall river height data available from sites upstream of the at-risk location within basin. Permanent telemetered and rated river level gauge operational for the agreed forecast location. Information available for storm surge and tidal flooding for coastal flood risk locations.	Multiple rain gauges in catchment upstream, downstream and at the at-risk location or reach.	A high number of event reporting rain gauges in the basin, including at the at-risk location or reach.	A high number of stream gauges in the basin. Telemetered stream gauge at the at-risk location (or reach) and upstream.	Rated site at the at-risk location or reach.	Large elevation difference between the most remote TBRG and the first forecast location.	The closest forecast location and the at- risk location (or reach) are at the same elevation (co- located).	Medium to large distance between most remote TBRG and first upstream forecast location.	The at-risk location (or reach) and closest upstream forecast location are at the same location.	

Notes:

i) Stream gauges include manually read staff gauges

- ii) The Service Level descriptors provide a qualitative description rather than quantitative to avoid conflict with the TWFS Assessment tool and ensure that the service level of a location is being considered relative to the size of the basin it is within.
- iii) Negative elevation or distance means that the forecast location is downstream of the at-risk location or river reach.

Prediction (Forecasting)

Prediction (forecasting) refers to the approaches, processes and models that use the data collected for predicting or forecasting the characteristics, behaviour and lead time of flooding in watercourse reaches and at at-risk locations.

Service						
Level Tier	Service Level Descriptor	B1 Forecast Sub factor	B2 Model Sub factor	B3 FWS Charter Sub factor	B4 Significant Storage Sub factor	B5 Response to Need Sub factor
0	Generic basic flood watch and severe weather / flash flood warning services only provided by BoM. No real time data available. No real time flood forecasts provided across the catchment.	Generic flood watch and severe weather / flash flood warning services only. No formal or informal flood forecast methods in catchment.	No forecast methods or models available. No real time data available.	No FWS charter in catchment.	Storages exist upstream and would benefit from being forecast through but are not forecast through.	Not needed if breaking down to locations.
1	No formal prediction service. Rainfall and / or river height data available in near real time at or near the location of interest (available locally or from BOM website).	Generic basic service only from BoM (flood watches, flash flood warnings). No formalised forecast service however informal forecast techniques may exist.	No formal forecast methods or models available. Informal models or methods may be available at local level. Real or near real time data may be available.	No FWS charter in catchment.		
2	Non-location specific qualitative forecasts may be provided by BoM. Rainfall and river height data available from BoM website in near real time, at or near the location of interest. Flood class levels or trigger levels determined for information locations or monitored sites.	Generic basic service from BoM (flood watches, flash flood warnings). Non-location specific formal qualitative forecast may be provided by BoM based on exceedance of flood class levels or trigger levels for	Forecast is based on observed behaviour against flood class levels or (rainfall or river) trigger levels. Rainfall and river height data available in near real time.	FWS charter exists downstream of the at-risk location (or reach).		

Service						
Level Tier	Service Level Descriptor	B1 Forecast Sub factor	B2 Model Sub factor	B3 FWS Charter Sub factor	B4 Significant Storage Sub factor	B5 Response to Need Sub factor
	Flood charter may exist downstream of the at-risk location or reach.	information locations or monitored sites.				
3	Location specific qualitative flash or riverine flood warnings provided by BoM or local entity (e.g. LG, RWA, etc.). Flood class or trigger levels determined for that location. Flood charter may exist upstream of the at- risk location or reach.	Generic basic service from BoM (flood watches, flash flood warnings). Location specific qualitative flood (riverine, flash) warnings are issued based on observed exceedance of flood class levels or flows at river sites or exceedance of trigger levels at monitored rain or river sites.	Observed behaviour coupled with analogue or qualitative assessment (e.g. peak height / flow correlations, flood curves, IFD assessments, rates of rise, etc.). Rainfall and river height data available in near real time.	FWS charter exists upstream of the at-risk location (or reach).	Storages exist at or upstream and the nearest storage is forecast through. No storages upstream that require forecasting through.	
4	Quantitative river height and timing forecasts (rise, fall, peak, critical levels) across flood event duration at the location of interest within agreed and specified accuracy bounds. Flood class or trigger levels determined for the at-risk location. Flood charter exists for the at-risk location or reach.	Generic basic service from BoM (flood watches, flash flood warnings). Quantitative forecasts (riverine, flash) are issued for the duration of the flood.	Rainfall / Runoff model available for at-risk location (or reach). Rainfall and river height data available in near real time.	FWS Charter exists for the at-risk location (or reach).		

Notes:

i) Formal forecasts refer to those issued by the BoM or a LG-owned flash flood warning system while informal forecasts refer to those issued by others (e.g. RWA, local group, etc.).

ii) Significant storages refers to storages that would benefit from being considered in forecasting models because of the impact they may have on flooding.

iii) It is assumed that even if a location does not have a FWS Charter, there will be a benefit to that location if an upstream or downstream location does have a FWS Charter.

- iv) Locations that have no upstream storages requiring forecasting are assigned the same rating as those locations that have storages upstream with forecasting. This is aimed at avoiding any skewing or biasing of results, particularly for locations without an upstream storage.
- v) Forecasting through refers to the practice of developing and disseminating a downstream forecast ahead of outflows from a storage being confirmed either through head / tail gauge readings or gate operations.
Dissemination (Dissemination and Communication)

Dissemination (and Communication) accounts for the various methods and technologies used to disseminate flood warning information between agencies and to at-risk communities.

Service		TWFS Assessment Tool C Sub factors
Level Tier	Service Level Descriptor	C1 Dissemination Sub factor
0	Standard arrangements only.	Generic messaging: included in weather forecasts and disseminated via standard dissemination
	No specific flood related messaging and thus no specific dissemination.	arrangements.
1	General messaging at area / basin scale using standard arrangements via website and media outlets. May include local government websites or social media.	Generic messaging: included in weather forecasts and disseminated via standard dissemination arrangements.
	At least one dissemination method of Faxstream, phone tree, recorded message.	At least one of Faxstream, phone tree, recorded message.
2	General messaging at area / basin scale using standard arrangements via website and media outlets. May include local government websites or social media.	Generic messaging: included in weather forecasts and disseminated via standard dissemination arrangements.
	At least one dissemination method of Local Wardens, FM-88, limited manual dissemination methods such as non-automated SMSing.	At least one of local wardens, FM-88, limited manual dissemination method (e.g. non-automated SMSing).
3	Specific and targeted messaging to at-risk location or river reach from authorities using standard arrangements.	Generic messaging: included in weather forecasts and disseminated via standard dissemination arrangements.
	Either direct non-automated (i.e. manual) mass dissemination methods such as social media or limited automated dissemination.	Either manual mass dissemination (e.g. social media) or limited automated dissemination.
4	Specific and targeted messaging to at-risk location or river reach from authorities using standard arrangements.	Generic messaging: included in weather forecasts and disseminated via standard dissemination arrangements.
	A combination of different dissemination methods are used, both automated and non- automated.	A combination of different dissemination and communication methods used. Automated mass dissemination method.
	At least one direct automated dissemination method, such as mass automated SMS, is used to disseminate warning information to individuals / communities.	

Notes:

i) It is assumed that the higher service levels will include multiple different dissemination methods. The sub factor lists the minimum requirements to achieve that service level.

Interpretation and Consequences Assessment (Interpretation)

Interpretation is the use of historic and modelled flood data (e.g. past events, flood study outputs and mapping) to identify consequences including likely flood extents, depths, velocities and properties affected. Studies may deliver detailed assessments of risk and flooding consequences, including details of infrastructure, properties and floors affected.

Service		TWFS Assessment	TWFS Assessment Tool E Sub factors			
Level Tier	Service Level Descriptor	E1 Flood Study Sub factor	E2 Mapping Sub factor			
0	No flood studies, mapping or historical recorded data. May be anecdotal evidence.	No flood studies undertaken for the at-risk location or reach.	No flood mapping undertaken for the at-risk location or reach.			
1	Flood extent mapping limited to where historical data available. Consequences assessment at region / basin scale.	No flood studies undertaken for the at-risk location or reach. Flood information is based on historical data.	Flood mapping for the at-risk location (or reach) is based on historic events and may be incomplete. Any flood mapping was undertaken more than 20 years ago.			
2	Limited flood study completed for the location / river reach. Flood extent mapping for some river heights using old modelling methods and / or historical data. Some at-risk properties may be identified. Consequences assessment at district / river reach scale.	A flood study for the at-risk location (or reach) was undertaken more than 20 years ago. Flood information and river heights are based on old modelling methods or historical data. Some interpretation may be required to determine properties at risk.	Flood mapping for the at-risk location (or reach) was undertaken more than 20 years ago.Any flood mapping has been undertaken at a low resolution or modelling (that requires some interpretation) has been completed for cross sections.May include mapping of historic flood extent(s).			
3	 Flood study and / or floodplain management plan completed for the location / river reach. Flood mapping for a river height range showing extent, depths (possibly velocity) at a street scale. The likelihood of isolation and depth of flooding of at-risk properties identified. Consequences assessment at at-risk location or reach scale. 	A flood study for the at-risk location (or reach) has been undertaken within the last 20 years. Flood information including extents and river heights are based on contemporary modelling methods and historical data. At-risk properties are identified along with issues such as isolation, egress and high risk areas.	Flood mapping for the at-risk location (or reach) has been undertaken within the last 20 years. Flood mapping has been undertaken at a high resolution showing extent at the property scale. Depth information can be interpreted.			

Service		TWFS Assessment	Tool E Sub factors
Level Tier			E2 Mapping Sub factor
4	Comprehensive flood study and / or floodplain management plan completed for the at-risk location / river	A flood study for the at-risk location (or reach) has been undertaken within the last 20 years.	Flood mapping at the at-risk location has been undertaken within the last 20 years.
	reach. Flood mapping for a range of river heights and historical events showing extent, depths (possibly velocity) at a property / street scale. Building floor levels surveyed and at-risk properties and floors identified. Likelihood of isolation identified. Comprehensive consequences assessment at property / street scale.	Detailed flood information including extents and river heights are based on contemporary and appropriate modelling methods and historical data. All at-risk properties are identified along with issues such as isolation, egress and high risk areas. Depths, velocities, depth of over-floor flooding of affected properties and other intel exists and is available.	Flood mapping has been undertaken at a very high resolution showing extent at the property scale. Depth, velocity, roads, properties and buildings affected are easily identifiable on the flood map.

Notes:

i) Although the service levels are specific in relation to flood studies and mapping, the Tool does not as yet discriminate further in terms of (say) the number of properties affected or consequences at various AEPs, etc.

Flood Response (Response Planning)

Flood response planning is currently biased towards the preparation of a Municipal Flood Emergency Plan (MFEP).

Service		TWFS Assessment Tool F Sub factors
Level Tier	Service Level Descriptor	F1 MFEP Sub factor
0	No region / basin MFEP or actions.	No MFEP for region or basin.
1	Actions at the region / basin scale as per action column in MFEP Flood Information	An MFEP was developed for the region more than 10 years ago.
	Card.	An MFEP exists. It has many gaps but is competent at the regional / basin scale.
2	Actions at the district / river reach scale as per action column in MFEP Flood Information	An MFEP was developed for the region more than 10 years ago.
	Card.	An MFEP exists. It has some gaps but is competent at the catchment / reach scale.
		Action column in Flood Information Card completed for district / river reach.
3	Actions at the at-risk location or reach as per action column in MFEP Flood Information	An MFEP has been developed for the location or reach in the last 10 years.
	Card.	An MFEP is available and competent at the at-risk location / reach or community scale.
	Includes an assessment of areas that will (and won't) be affected by flooding.	Action column in Flood Information Card completed for at-risk location.
4	Detailed MFEP. Actions at the property / street scale as per action column in MFEP	An MFEP has been developed for the location or reach in the last 10 years.
	Flood Information Card.	An MFEP is available and competent at the at-risk location / reach or community scale.
	Includes an assessment of areas that will (and won't) be affected by flooding.	The MFEP includes actions at a detailed street and property scale in the Flood Information Card.
	Includes identification of and delineation between different flood sources / types and the extents.	The MFEP may include indicative flood prediction tools.

Notes:

i) Although the service levels are specific in relation to the state of development of the MFEP, the Tool does not as yet discriminate in terms of scale and the level of detail present in flood information cards.

ii) Flood Action Guides (FAGs) are prepared as part of the MFEP development process. Ideally, FAGs will assist both community flood awareness and flood response. However, the availability or sophistication of a FAG has not been consider in any of the Flood Response sub-factors as it is considered unlikely that a FAG will actively drive an individual's response.

Community Awareness & Education

Education and Awareness tools are used or applied to improve the awareness of a community's flood risk and in relation to flood safety, risk minimisation and flood action plans.

			TWFS Assessmen	t Tool D Sub factors		
Service Level Tier	Service Level Descriptor	D1 Time since last major flood Sub factor	D2 FloodSafe Program Sub factor	D3 Planning Scheme Sub factor	D5 Individual Property Flood Chart Sub factor	D4 Flood Class Level Sub factor
0	No formal awareness of flood risk at a local or regional scale. No flood awareness or education programs.	Has no recorded major flood.	No FloodSafe Program run at any scale through the catchment.	No identification of flood prone land in planning scheme.	No individual property flood charts.	Removed - does not contribute sufficiently to education or awareness of community to justify
1	Community awareness program / material at region / basin scale. (No FloodSafe program at location or within reach). Community awareness material updated and refreshed on a greater than 5 year basis.	Last major flood was more than 10 years ago.	No community or township FloodSafe Program. A catchment or basin scale FloodSafe Program (with no or minimal individual engagement) was run more than 5 years ago.			inclusion as a factor.
2	Community awareness program, / material at district / river reach scale (e.g. FloodSafe brochures). Flood awareness is at a general level. Community awareness material updated and refreshed approximately every 5 years.	Last major flood was less than 10 years ago.	Generic community or township FloodSafe Program has been run and the local Flood Action Guide updated within the last 5 years.	Flood extents identified in Planning Scheme zones and / or overlays to low resolution and are either not based on flood mapping or do not reflect most up-to- date flood mapping extents.		

			TWFS Assessmen	t Tool D Sub factors		
Service Level Tier	Service Level Descriptor	D1 Time since last major flood Sub factor	D2 FloodSafe Program Sub factor	D3 Planning Scheme Sub factor	D5 Individual Property Flood Chart Sub factor	D4 Flood Class Level Sub factor
3	Specific and targeted community awareness program / material at at-risk location or river reach scale (e.g. up to date FloodSafe brochures and other materials). Flood awareness is good. Local community awareness material updated and refreshed more frequently than every 5 years. Development of individual and business flood plans actively encouraged.	Last major flood was less than 10 years ago.	FloodSafe Program has been run within the last 5 years for the at-risk community. Involved update of the local Flood Action Guide as well as engagement at the street scale.	Flash and / or riverine flood extents identified in Planning Scheme zones and / or overlays to a high resolution such that extents on individual properties can be identified.	Individual Property Flood Charts for at-risk location or river reach.	
4	Locally specific and targeted community awareness program / material at property / street scale (e.g. up to date FloodSafe brochures and other materials). Excellent flood awareness. Local community awareness updated and refreshed on an annual basis. Development of individual and business flood plans actively encouraged and assisted. Planning Scheme delineations reflect current flood mapping and flood risk.	Last major flood occurred within the last year.	FloodSafe Program run for the at-risk community during the last 12 months. Involved update of the local Flood Action Guide as well as engagement at the street scale. Development of individual and business Flood Action Plans actively encouraged with assistance / guidance provided.	Flood extents identified in Planning Scheme overlays / zones to a high resolution consistent with latest flood mapping, such that extents on individual properties can be identified.	Individual Property Flood Charts for at-risk location or river reach. Meter box stickers distributed to all at-risk properties.	

Notes

i) Not all MFEPs are publicly available. Thus, while an MFEP does provide a source of local flood intelligence and can have an influence on community flood awareness, the MFEP does not feature in any of the Community Awareness and Education sub-factors.

Appendix L: Goulburn Broken regional population statistics

Municipality / Town	2016	2016 Total	2011	2011 Total	2006 Total	2001 total
	Urban		Urban			
Benalla		13,861		13,252	13,252	13,319
Campaspe		37,061		35,747	35,452	34,611
Colbinabbin	304		106			
Echuca	14,043		1,2596			
Girgarre	561		191			
Gunbower	551		260			
Kyabram	7,331		5,477			
Lockington	808		347			
Rochester	3,113		2,551			
Rushworth	1,335		950			
Stanhope	828		470			
Tongala	1,926		1,216			
Greater Shepparton		63,827		59,648	56,115	55,210
Arcadia downs / South	292		284			
Dookie	328		233			
Katandra west	476		215			
Kialla west	431		203			
Merrigum	679		396			
Mooroopna	7,942		7,813			
Murchison	925		737			
Shepparton east	31,197		218			
Shepparton	1,138		29,553			
Tallygaroopna	579		252			
Tatura	4,669		3574			
Toolamba	769		289			
Mansfield		8,584		8,791	7,739	8,515
Bonnie Doon	570		166			
Goughs Bay	261		168			
Jamieson	301		114			
Mansfield	4,787		3,151			

The following population is sourced from 2016 census data.

Municipality / Town	2016	2016 Total	2011	2011 Total	2006 Total	2001 total
	Urban		Urban			
Sawmill Settlement	88		365			
Mitchell		40,918		34,405	30,629	27,544
Beveridge	2,330		468			
Broadford	4,319		3,342			
Kilmore	7,958		6,189			
Pyalong	660		439			
Seymour	6,327		5,871			
Tallarook	736		204			
Wallan	11,074		7,643			
Wandong-Heathcote junction	2,179		1,618			
Waterford Park	-		201			
Moira		29,112		27,923	26,525	25,475
Barmah	282		175			
Bundalong	428		312			
Cobram	6,01		5,370			
Katamatite	401		218			
Katunga	996		177			
Nathalia	1,880		1,434			
Numurkah	4,477		3,745			
Strathmerton	1,052		477			
Tungamah	408		282			
Wunghnu	334		239			
Yarrawonga	7,930		6,824			
Murrindindi		13,732		12,852	13,387	13,111
Alexandra	2,695		2,245			
Buxton	492		234			
Eildon	974		678			
Hazeldene			250			
Kinglake	1,536		1,031			
Kinglake West-Pheasant Cks	1,488		818			
Marysville	394		246			

Municipality / Town	2016	2016 Total	2011	2011 Total	2006 Total	2001 total
	Urban		Urban			
Thornton	299		136			
Yea	1,587		1,087			
Strathbogie		10,274		9,333	9,064	9,169
Avenel	1,048		762			
Euroa	3,275		2668			
Longwood	240		173			
Nagambie	1,886		1513			
Violet Town	874		661			

Appendix M: Vulnerability and Infrastructure assessment

Summary table:

At risk locations	Vulnerability (no. of groups)	Key Infrastructure (no. of assets)
Acheron River & Tribs		
Alexandra		
Avenel		
Baddaginnie		
Barmah	2	
Bearii		
Benalla	7	4
Bonnie Doon		
Broadford	1	
Broken Effluent Tribs		2
Broken River Shep -Benalla	1	
Bunbartha		
Buxton		
Castle Point		
Cobram	5	
Colbinabbin		
Cooma		
Corop Lakes Area		
Costerfield		
Costerfield South		
Dabyminga Ck		
Delatite River (at Delatite Rd)		
Devenish		
East Murchison		
East Shepparton		
Eildon		
Euroa		
Ford Creek		
Girgarre		
Glenrowan		
Goulburn River Seymour- Shep		
Goulburn u/s Eildon		

At risk locations	Vulnerability (no. of groups)	Key Infrastructure (no. of assets)
Granite Creek		
Graytown		
Heathcote East		
Heathcote North		
Howqua		
Jamieson		
Katamatite	1	
Katandra West		
Kialla West		
Kialla West (Orrvale)	7	2
Kilmore		
Kilmore East		
King Parrot Ck & Strath Ck d/s Flowerdale		
King Parrot Ck u/s Flowerdale		
Kinglake Central		
Kinglake East		
Коопоотоо		1
Kyabram		
Lake Rowan		
Locksley		
Longwood		
Lower Broken Creek		
Lower Goulburn d/s Shep		
Maindample		
Maindample Region (at Dry Ck Rd)		
Mangalore		
Mansfield		
Marysville		
Merrigum		
Merrijig		
Merton		
Mid Broken Creek		
Mid Goulburn		
Molesworth		
Mt Camel		

At risk locations	Vulnerability (no. of groups)	Key Infrastructure (no. of assets)
Muckatah Depression		
Murchison		
Murray Barmah-Echuca		
Murray Cobram-Ulupna		
Murray Piree Ck-Barmah		
Murray u/s Yarrawonga		
Murray Ulupna-Piree Ck		
Murray Yarrawonga-Cobram		
Marungi		
Nagambie	1	
Narbethong		
Nathalia	3	
Numurkah	4	2
Old Longwood		
Pheasant Creek & Kinglake West		
Pyalong		
Redcastle		
Reedy Creek		
Ruffy		
Rushworth		
Seymour	2	
Shepparton/Mooroopna	1	2
St James		
Stanhope		
Strath Ck		
Strathbogie		
Sunday & Dry Ck		
Swanpool		
Taggerty		
Tallarook		
Tallygaroopna	2	2
Tatong		
Tatura	1	
Tatura/Tongala Rural		
Thoona		

At risk locations	Vulnerability (no. of groups)	Key Infrastructure (no. of assets)
Thornton		
Tongala		
Toolamba		
Toolangi		
Tungamah	1	1
Tyaak		
Upper Broken River		
Upper Broken, Boosey & Majors Creeks		
Upper Howqua River (historical area)		
Violet Town	1	
Waaia		
Whiteheads Creek		
Wilby		
Woods Point		
Wunghnu	1	1
Wyuna		
Yarrawonga		
Yea	2	
Yea River		

Appendix N: Final priority and risk assessment scores

Terminology: H = High Priority, M = Medium Priority, L = Low Priority, - = No further action

Benalla Rural City

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plan
Baddaginnie	2	2	3	-	L	Н	Н
Benalla	5	5	4	L	Н	Н	Н
Devenish	0	0	0	-	-	Н	М
Glenrowan (Rural City of Wangaratta)	1	1	0	-	-	-	-
Swanpool	0	0	0	-	-	-	-
Tatong	1	1	0	-	-	М	L
Thoona	1	1	0	-	-	М	L
Winton ⁱ	0	0	0	L	-	М	-

i. New town area introduced following stakeholder consultation

Campaspe Shire

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plan
Colbinabbin	1	1	0	-	М	-	М
Girgarre	0	0	0	-	-	-	-
Kyabram	5	5	4	L	-	Н	М
Rushworth	0	0	0	-	-	-	-
Stanhope	5	1	2	-	-	-	-
Tongala	4	1	0	-	-	-	-
Wyuna	1	1	0	-	-	-	-

Greater Bendigo City Council

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Costerfield	0	0	0	-	-	-	-
Costerfield South	0	0	0	-	-	-	-
Heathcote East (Rural Living)	0	0	0	-	-	-	-
Heathcote North (Rural Living)				-	-	-	-

Mount Camel	0	0	0	-	-	-	-
Redcastle	0	0	0	-	-	-	-

Greater Shepparton City Council

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Bunbartha	1	1	0	-	-	L	-
Cooma	1	1	0	-	-	-	-
Katandra West	0	0	0	-	-	Н	-
Kialla West	3	1	2	-	-	-	-
Merrigum	4	3	4	-	L	-	L
Murchison / Murchison East	2/3	1	2/3	М	L	Н	-
Shepparton East	4	5	3	-	Н	Н	Н
Shepparton/ Mooroopna	3	5	4	М	Н	Н	Н
Surplus Irrigation Channels				М	-	-	-
Tallygaroopna	1	1	1	М	-	Н	-
Tatura	5	5	3	-	L	-	-
Toolamba	4	1	3	-	-	М	М

Mansfield Shire

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Bonnie Doon	1	1	0	-	-	-	-
Gaffney's Creek / A1 Mine Settlement "	0	0	0	-	-	-	-
Howqua ⁱ	1	1	0	-	-	-	-
Jamieson	4	2	3	-	L	L	L
Maindample	3	1	3	-	-	-	-
Mansfield	4	3	1	-	-	L	М
Merrijig	3	1	2	-	-	-	-
Merton	0	0	0	-	-	-	-
Woods Point "	0	0	0	-	-	-	-

i. Include in Howqua River (Rural) Area

ii. Include in Upper Goulburn (Rural) Area

Mitchell Shire

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Broadford ⁱ	3	2	1	-	М	Н	Н
Kilmore	0	0	0	L	L	Н	Н
Kilmore East ⁱ	0	0	0	-	L	L	L
Pyalong	0	0	0	-	-	L	L
Reedy Creek "	0	0	0	-	-	L	L
Seymour	5	5	3	Н	Н	Н	Н
Tallarook "	3	1	2	-	-	М	М
Tyaak ⁱⁱ	0	0	0	-	-	L	L
Whiteheads Creek	1	1	0	М	Н	Н	Н

i. Include in the Sunday and Dry Creeks (Rural) Flood Study

ii. Include in the Dabyminga Creek (Rural) Flood Study.

Moira Shire

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Barmah	5	5	5	L	М	-	М
Bearii ⁱ	1	1	0	-	-	-	-
Cobram	5	5	4	Н	М	-	-
Katamatite	3	2	4	-	-	L	М
Koonoomoo ⁱⁱ	1	1	0	-	-	L	-
Lake Rowan ⁱⁱⁱ	0	0	0	-	-	L	-
Marungi	1	1	0	-	-	-	-
Nathalia	2	2	2	Н	Н	-	М
Numurkah	4	5	3	Н	Н	Н	Н
St James ⁱⁱⁱ	2	1	1	-	-	-	-
Strathmerton ⁱⁱ				-	-	-	-
Tungamah	4	3	4	Н	Н	Н	Н
Waaia	0	0	0	-	-	L	-
Wilby"	0	0	0	-	-	-	-
Wunghnu	3	3	4	М	М	М	М
Yarrawonga	3	4	1	Н	-	Н	Н
Yarroweyah ⁱⁱ				-	-	-	-

i. Include in the Murray Ulupna to Piree Creek (Rural) Area

ii. Include in Murray Cobram to Ulupna (Rural) Area

iii. Include in Upper Broken Creek (Rural) Area

Murrindindi Shire

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Alexandra	3	2	2	L	М	Н	н
Buxton	4	3	5	М	М	Н	н
Eildon	0	0	0	-	-	-	-
Flowerdale ⁱ				-	-	-	-
Kinglake Central	0	0	0	-	-	-	-
Marysville	3	1	1	-	-	М	М
Molesworth	1	1	0	-	-	-	-
Narbethong	0	0	0	-	-	-	-
Kinglake East, Pheasant Creek & Kinglake West	0	0	0	-	-	-	-`
Strath Creek iii	1	1	1	-	-	-	-
Taggerty	3	1	2	-	-	М	М
Thornton "	4	3	5	-	-	-	-
Toolangi	0	0	0	-	-	-	-
Yarck ⁱⁱⁱ				-	-	-	-
Yea	3	2	2	-	М	-	Н

i. Include in the Upper King Parrot Creek (Rural) Area

ii. Include in Mid Goulburn (Rural) Area

iii. Include in Lower King Parrot Creek (Rural) Area

Strathbogie Shire

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Avenel	3	2	3	М	М	Н	М
Euroa	5	4	5	Н	Н	Н	Н
Graytown	0	0	0	-	-	L	L
Locksley	1	1	0	-	-	L	L
Longwood	3	2	3	-	-	М	L
Mangalore	0	0	0	-	-	L	L
Nagambie	4	1	1	Н	М	Н	н
Old Longwood	0	0	0	-	-	L	L
Ruffy	0	0	0	-	-	-	-
Strathbogie	0	0	0	-	-	L	L
Violet Town	4	4	4	Н	Н	Н	Н

Rural Study areas

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
			Broken Cr	eek			
Broken Creek Tributaries (Pine Lodge, Daintons, Congupna Guilfus & O'Keefe Creek)	1	5	0	-	L	-	L
Lower Broken Creek	1	5	0	-	-	L	L
Mid Broken Creek	1	5	0	-	-	L	L
Muckatah Depression	1	3	0	-	L	М	L
Upper Broken Creek	1	4	0	-	М	М	М
			Broken Ri	iver			
Lower Broken River	1	5	0	-	L	Н	Н
Upper Broken River	1	2	0	-	М	Н	М
			Goulburn Sy	ystem			
Acheron River	1	2	0	-	L	Н	L
Corop Lakes	1	5	0	-	-	L	L
Dabyminga Creek	1	1	0	-	-	L	L
Delatite River	1	2	0	-	-	L	L
Ford Creek	1	1	0	-	-	L	L
Goulburn Seymour to Shepparton	1	5	0	-	-	М	М
Granite Creeks	1	5	0	-	L	М	М
Howqua River	1	1	0	-	-	L	L
Lower Goulburn	1	5	0	-	-	L	L
Lower King Parrot Creek	1	1	0	-	-	L	L
Maindample Region	1	1	0	-	-	-	-
Mid Goulburn	1	5	0	-	L	М	М
Sunday & Dry Creeks	1	1	0	-	Н	Н	Н
Tatura/ Tongala Region	1	5	0	-	-	-	-
Upper Goulburn	1	1	0	-	L	L	L
Upper King Parrot Creek	1	1	0	-	-	Н	Н
Whiteheads Creek	1	1	0	-	Н	Н	Н
Yea River	1	1	0	-	-	L	L
			Murray Sys	stem			
Murray Barmah to Echuca	1	4	0	-	М	Н	М
Murray Cobram to Ulupna	1	5	0	-	-	Н	М
Murray Ulupna to Barmah	1	1	0	-	-	L	М
Murray Upstream of Yarrawonga	1	1	0	-	-	L	L

Name	Density of damages	Absolute damages	Proportion population affected	Mitigation Works	Total Flood Warning System	Land Use Planning	Municipal Flood Emergency Plans
Murray Yarrawonga to Cobram East	1	2	0	-	L	L	L