


NOTES

1. The May 1974 flood at Numurkah was adopted as being equivalent to the 1% probability flood. This is a flood which has a 1% chance of being equalled or exceeded in any year; or put another way, would occur, once in 100 years.
2. This plan is based on recorded 1974 flood levels adjusted to allow for conditions existing in May 1983. For a record of the data used to compile this plan refer to File No. 83/2535.
3. The flood levels are shown in the form of lines linking points of equal flood level.
4. Flood levels can be assumed to change uniformly from one line to the next. Flood levels for points between lines can be obtained by linear interpolation.
5. The length of flood level lines as drawn should not be taken as an indication of the extent of flooding. An accurate delineation of the extent of flooding must be determined by ground survey.
6. All flood levels are in metres to Australian Height Datum.
7. These flood levels were designated by the Commission under the Provisions of the Drainage of Land Act 1975, Clause 37A on the 23rd day of February 1984.

REVOKED 19 March 2026



REFERENCES		ZONE 55 SW. E 357370 N 6003220 N.E. E 362720 N 6006600	
50692	LONGITUDINAL SECTION	NO	DATE
146585	NUMURKAH FLOOD STUDY (1974)		
DRG NO	TITLE	DESCRIPTION	APPROVED



MICROFILM DESIGNED 4 1-2-84	CHECKED 1-2-84	DESIGNED ENGINEER <i>W. W. Johnson</i>	CHIEF DESIGNING ENGINEER
DRAWN K. G. Gaudin	CHECKED K. Gaudin	PRINCIPAL DESIGNING ENGINEER <i>W. W. Johnson</i>	DIRECTOR, ENG. & TECH. SERVICES
MICROFILM OPERATOR 1974		DIVISIONAL ENGINEER	COMMISSIONER

RURAL WATER COMMISSION OF VICTORIA	
BROKEN CREEK - NUMURKAH	
DESIGNATED FLOOD LEVEL LINES	
CORR. REF. 83/0093	DRG. NO 146616